

Technical data IT3125-A1

Model number	: IT3125-A1
Type of tool	: Impact Wrench
Weight of tool (Aluminium)	: 6.89 lb (3.15 kg)
Compressed air	
Maximum permissible operating pressure	: 90 psi (6.2 bar)
Recommended operating pressure	: 90 psi (6.2 bar)
Air Consumption @90psi	: 6.9 CFM (195 L/min)
Square drive	: 3/4"
Impact mechanism	: Twin Hammer
Max torque	: 1,200 Ft-lb (1,626 Nm)
Free speed	: 5,750 rpm
Min hose size	: 1/2" (13mm)
Standard bolt size	: 1 1/4" (32mm)
Noise characteristic values in accordance with	
Maximum A-weighted surface impulse sound pressure level	: 89.6 dBA
Maximum A-weighted impulse sound power level	: 100.6 dBA
Vibration	
Average of 3 highest averages	: 1.71 m/s ²
Highest level of averages	: 1.75 m/s ²
Recommended lubrications	: MoS ₂ grease

Declaration of Conformity

We

Basso Industry Corp.,
No. 24, 36th Rd., Taichung Industrial Zone,
Taichung, Taiwan, R.O.C.

declare under our sole
responsibility that the

Impact Wrench IT3125-A1

conforms with the directive
and the standards

98/37/EC
EN 292-1: Section 5 of 1992
EN 292-2: Section 3 of 1992
EN 1050: 1996 and DIVN 19250
EN 792-1: 2000 and EN 792-6: 2000
EN ISO 15744: 2002 and ISO 8662-7: 1997

Serial number:
(to be filled by the customer)

Signed: Kevin Lin
Kevin Lin (Quality Manager)

Date: **22 Jul, 2006**