

Reka Glue Gun Pneumatic



TR 80 LCD Cartridge Hot-Spray-System



Fig. TR 80 LCD Cartridge Hot-Spray-System

Made in Germany

The TR 80 LCD Cartridge Hot-Spray-System consists of the TR 80 LCD Cartridge gun and the stand on which the gun may be deposited, with pressure regulator and manometer.

The TR 80 LCD Cartridge Hot-Spray-System is capable of spraying melting glues contained in 310 ml aluminium cartridges.

The TR 80 LCD Cartridge gun has considerable advantages: It works with 310 ml aluminium cartridges. The nozzle is screwed with the spray-adaptor on to the cartridge thus enabling quick cartridge change.

The TR 80 LCD Cartridge gun can spray PUR melting glues. PUR melting glues distinguish themselves by an extremely high thermal stability.

The electronic temperature control is integrated into the handle for easy operation.

The electronic temperature control responds to the slightest deviation, thus providing for the optimum working temperature.

The regulator for the compressed air and the manometer scale are integrated into the stand. The precise adjustment of the compressed air ensures an optimum and accurate application of the adhesives.

Material air and spray air are separately adjusted. You may work without interruption since the spray air is heated in the gun, thus preventing the glue from cooling down during its application.

Thanks to the great variety of Reka accessories you can choose an appliance configuration adapted to your individual requirements.

Subject to technical modifications

Technical Data

Voltage	TR 80 LCD
Heating capacity	230 V / 50 Hz (120 V on request)
Air pressure for glue max.	400 W
Air control spray max.	approx. 90 psi/6 bars
Air consumption max.	approx. 90 psi/6 bars
Temperature control	100 l / min.
Temperature control range	electronic/digital
Overheat protection	50 – 210°C
Fuse	temperature controller
Heat-up time	4 A
Length of connections (stand to handgun)	3 – 10 min. *
Length of electric cord	4,5 m
Contents of aluminium cartridge	4,0 m
Minimum application of glue per m²	310 ml
Weight of handgun	3 g
	1400 g

* Depending on type of adhesive.



Accessories

Pneumatic foot switch
Stationary equipment
Balancer

Reka Klebetechnik GmbH & Co.KG
 Siemensstr. 6
 D-76344 Eggenstein
 Tel. +49 (0)721/97 07 80
 Fax +49 (0)721/70 50 69
 Internet: www.reka-klebetechnik.de
 Email: info@reka-klebetechnik.de

*** Stand for dipositing with 2 regulators and 2 manometers are included in the delivery.