

HOSE REELS AND CABLE REELS

No. 223-AV



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**






HELP THE ENVIRONMENT

Depending on the item, the packaging may contain one or more of the following materials - to be recycled according to local municipal or state regulations.

cardboard • polyethylene bag • polystyrene
paper • wood • nails • plastic straps
cellophane • paper clips • gummed paper





**ADVANCED FLUID
MANAGEMENT SOLUTIONS**



DESIGN IS

Art





founded in 1975



*the human side
of Quality*



CONCEPT, RESEARCH AND DESIGN

The real strength of a company lies in the ability of its concept and research departments to continuously find the solutions that best meet market demands.



ASSEMBLY LINES

Special equipment, expressly designed to facilitate assembly operations and which, at the same time, allows for effective, automatic quality control.

PACKAGING

The product is carefully packed with special cover to protect it from risks during transport.



COMPONENT STORAGE

Our vertical warehouses enable quick, precise preparation of components and spare parts for assembly and sale.



TECHNOLOGY
INNOVATION
QUALITY
SAFETY
RELIABILITY



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

TECHNICAL ASSISTANCE

RAASM has the most complete range of products for lubrication and fluid distribution. The goal is to always provide a comprehensive response to customer demands and fully meet their every need.





TO PREVENT:



BREAKAGE

The hose reel protects the hose against wear and possible breakage.



CLUTTER

With the hose reel, rewinding the hose is fast and safe, letting you keep the workplace tidy.



ACCIDENTS

The hose reel allows workers to operate in full safety, the equipment always ready for use.

THE HOSE REEL



TO IMPROVE:

✓ EFFICIENCY

The hose reel cuts down on wasted time, letting you set the equipment where and when you need it, organising the workplace to meet your needs and keeping it clean and functional.

✓ FLEXIBILITY

Thanks to slotted holes and quick coupling supports, the hose reel assembly is safe and easy. Designed to be mounted on the wall - with narrow or wide arm - on the workbench, ceiling or HEA beam.

✓ HOSE LIFE

All components in the hose reel have been tested to last for decades, thus guaranteeing long-term savings and compliance with a conscious, farseeing environmental protection policy.



HOW TO CHOOSE THE HOSE REEL

To choose the right hose reel, it is important to consider the following 4 characteristics. These must be stated when telephoning in your request to our sales-technical office.

1 What fluid will be used?

RAASM hose reels are compatible with any type of fluid. First check density, corrosiveness and flammability: we have hose reels that can handle any operating condition. Below is a list of the main fluids that can be used.

Air	AdBlue®
Hot water	Oil-Water
High pressure water	Oil-Paints
Oil and similar	Welding
Grease	LPG
Diesel	Methane

2 What is the required operating pressure?

Knowing the operating pressure is a key element in choosing the correct model hose reel. Our product range can operate at pressures from 10 to 700 bar. Identify the pressure that best suits your needs depending on the type of fluid, application and size of the system used.

10 bar
20 bar
50 bar
70 bar
100 bar
150 bar
200 bar
400 bar
700 bar

3 What is the maximum hose length needed?

The wide range of models available lets you choose from lengths ranging from just a few metres to hundreds of metres long. This parameter is to be integrated with the choice of hose diameter.

4 What flow rate is required?


The diameter is very important as it determines the flow rate and the flow throughput. Together with length, this parameter limits the choice of the series of hose reel and determines the type of power supply.



HOW TO CUSTOMIZE THE HOSE REEL

The arms can easily be repositioned as needed to adapt the hose reel to the workplace. This operation is very simple and can be performed by the end user.

Standard installation



Floor or bench
installation



Ceiling installation



Depending on the material (ABS or painted steel), the drum can be customized with the following 4 colours. The brackets and arms will remain in the standard colour. To order an article in a colour other than the standard, the suffix indicated in the image below must be added to the code.

RAL 7035 

RAL 1004 

RAL 3020 

RAL 5002 

RAL 9005 



standard



/C2



/C4






/C5



/R9005

The spring force can be customized according to the specific requirements of the application (ceiling installation, particularly heavy utilities etc.). By intervening on the bushing on the side of the drum and following the safety instructions given in the manual, the hose spring force can be easily increased or decreased.



PRODUCT FAMILIES INDEX

page	painted		s. steel 304 - 316	
	page	ABS page	page	ABS page

SPRING OPERATED OPEN HOSE REELS

ADVANTAGES AND TECHNICAL CHARACTERISTICS	14	-	-	-	-
AIR-WATER 10-20 bar	-	18		20	
HOT WATER 50-100 bar	-	22		24	
HOT WATER 200 bar	-	26		28	
HOT WATER 400-700 bar	-	30	-	32	-
HOT WATER 100-200-400 bar in AISI 316	-	-	-	34	
OIL AND SIMILAR 50-100-150 bar	-	36		38	
GREASE 400-600 bar	-	40		42	
DIESEL 10-20 bar	-	44		46	-
ADBLUE® 10-100 bar	-	48		48	
LPG-METHANE 20 bar	-	50	-	-	-
WELDING 20 bar	-	52	-	-	-
DOUBLE INLET-OUTLET	-	54	-	-	-
ACCESSORIES	78	-	-	-	-

SPRING OPERATED ENCLOSED HOSE REELS

ADVANTAGES AND TECHNICAL CHARACTERISTICS	56	-	-	-	-
AIR-WATER 20 bar	-	60		-	-
OIL AND SIMILAR 150 bar	-	60		-	-
GREASE 400 - 600 bar	-	60		-	-
FOR SUCTION OF OIL AND SIMILAR	-	60	-	-	-
ACCESSORIES	78				

SPRING OPERATED HOSE REELS WITH POLYURETHANE HOSE

ADVANTAGES	62	-	-	-	-
TECHNICAL CHARACTERISTICS S. 250-288-328-378-438	64	-	-	-	-
AIR-WATER 20 bar	-	66		-	-
TECHNICAL CHARACTERISTICS CASING S. 260-280	68	-	-	-	-
AIR-WATER 20 bar	-	-	70	-	-
TECHNICAL CHARACTERISTICS CASING S. 250-300	72	-	-	-	-
AIR-WATER 20 bar	-	74	-	74	-
ACCESSORIES	78	-	-	-	-



page	painted		s. steel 304 - 316	
	page	ABS page	page	ABS page

MANUAL HOSE REELS

ADVANTAGES AND TECHNICAL CHARACTERISTICS	84	-	-	-	-
AIR-WATER 20 bar	-	92		94	
HOT WATER 70-100-200-400 bar	-	96		98	
OIL AND SIMILAR 150 bar	-	100		102	
GREASE 600 bar	-	104		106	
DIESEL 20 bar	-	108		110	
ACCESSORIES	120	-	-	-	-

MANUAL TROLLEY-MOUNTED HOSE REEL

ADVANTAGES AND TECHNICAL CHARACTERISTICS	112	-	-	-	-
AIR-WATER 20 bar	-	116	-	120	-
HOT WATER 100 bar	-	116	-	120	-
HOT WATER 200 bar	-	116	-	120	-
HOT WATER 400 bar	-	116	-	120	-
ACCESSORIES	120	-	-	-	-

MOTORIZED HOSE REELS

ADVANTAGES AND TECHNICAL CHARACTERISTICS	122	-	-	-	-
AIR-WATER 20 bar	-	126	-	-	-
HOT WATER 70-100 bar	-	128	-	130	-
OIL AND SIMILAR 70-150 bar	-	132	-	-	-
GREASE 400 bar	-	134	-	-	-
DIESEL 20 bar	-	136	-	-	-
ACCESSORIES	138	-	-	-	-

HOSES, STOPS AND FITTINGS

	139	-	-	-	-
--	-----	---	---	---	---

SPRING OPERATED ELECTRIC CABLE REELS

ADVANTAGES AND TECHNICAL CHARACTERISTICS	146	-	-	-	-
S. 280 EXTENSION CORD - 230 V SINGLE PHASE	150	-	-	-	-
S. 280 EXTENSION CORD - 400 V THREE PHASE	152	-	-	-	-
S. 280 EXTENSION CORD WITH SCHUKO PLUG AND SOCKET - 230 V SINGLE PHASE	154	-	-	-	-
S. 280 EXTENSION CORD WITHOUT TRANSFORMER FLUORESCENT LAMP - 230 V SINGLE PHASE	158	-	-	-	-
S. 280 EXTENSION CORD WITHOUT TRANSFORMER LED LAMP - FROM 12 V TO 24 V AC/DC	160	-	-	-	-
S. 280 EXTENSION CORD WITH LED LAMP WITH TRANSFORMER - 230 V AC/DC	162	-	-	-	-
FLUORESCENT AND LED LAMP	164	-	-	-	-
EARTHING CABLE REELS	166	-	-	-	-

ARTICLES INDEX

170




**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED OPEN HOSE REELS



EXAMPLES OF **USE**



IN-SHOP MAINTENANCE OPERATION

HYGIENIC AND SANITARY WASHING OPERATIONS



AUTOMOTIVE

LUBE
TRUCKS AND
INDUSTRIAL
VEHICLES

CLEANING

CHEMICAL
INDUSTRY

BUILDING
AND ROAD
CONSTRUCTION

...and much more



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED OPEN HOSE REELS



STRENGTH POINTS

- Repeated spring stress-tests guarantees decades of life and efficiency.
- All models comply with the ATEX directive for use in environments with potentially explosive atmospheres.
- Hose stop available for all standard models, even those supplied without hose.
- The spring force is both constant and adjustable. Thus use can be fine-tuned to the specific needs of each application.
- All sliding parts, such as bushing and the rack, are made of special technopolymers tested for long-term use.
- Compatible with many types of fluids, even highly corrosive fluids.

TECHNICAL CHARACTERISTICS

Visit our
website



FIXING BRACKET

Has 4 slotted holes for safe, easy installation.

PAWL

Easy to remove for maintenance or when the work requires free sliding.

STOP RACK

Makes it possible to lock the hose around every 0,5 m.

SPRING

Tested to withstand over 20000 work cycles.

MULTI POSITION ARMS

Hose outlet position can be changed manually by modifying installation of the arms.

HOSE GUIDE

Designed with ample width and roller arrangement to reduce wear on the hose.

CENTRAL PIN

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.

DRUM SUPPORT BUSHING

Made of self-lubricating technopolymer with excellent wear and corrosion resistance.

SWIVEL JOINT

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.



Type of fluid
AIR-WATER


Pressure
20 bar

Material
- PAINTED STEEL
- ABS


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 100 °C



In accordance with directive




* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	Viton®	brass	galvanized steel

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H		
				290	186	140	196	226	98	330	300	339	135		470 x 260 x 490	
				330	186	140	196	226	98	390	350	365	155		510 x 260 x 520	
				390	186	140	196	226	98	410	390	410	155		580 x 280 x 590	
				430	186	140	197	226	97	450	415	456	264		580 x 280 x 590	
				430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590	
				530	203	153	221	258	104	535	510	558	315		650 x 290 x 700	
				540	300	218	227	268	165	535	510	572	315		660 x 390 x 690	
				560	488	399	238	272	348	535	510	578	315		670 x 610 x 760	

Overall dimensions SWIVELLING (mm)											Series		A B C D E F G H I											Packaging (mm) W x D x H			
															390	184	146	106	144	98	410	390	482	155		580 x 280 x 590	
															430	208	162	118	164	97	450	415	540	264		580 x 280 x 590	
															530	228	182	154	200	104	535	510	642	315		650 x 290 x 700	
															540	300	218	227	268	165	535	510	700	315		660 x 390 x 690	

(W: width - D: depth - H: height)



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 290	8290.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	10,0 kg	-
	8290.101	-	10 m - 3/8" (995.210)	G 3/8" (f)	G 3/8" (m)	12,0 kg	-
	8290.104	-	15 m - 1/4" (993.215)	G 3/8" (f)	G 1/4" (m)	12,0 kg	-
* Hose reel capacity		inner hose Ø max. length	1/4" 16 m 5/16" 14 m 3/8" 10 m				
s. 330	8330.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
	8330.101	-	12 m - 3/8" (995.211)	G 3/8" (f)	G 3/8" (m)	13,5 kg	-
* Hose reel capacity		inner hose Ø max. length	1/4" 18 m 5/16" 16 m 3/8" 14 m 1/2" 12 m				
s. 390	8390.100	8380.100	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8390.102	8380.102	18 m - 3/8" (995.217)	G 3/8" (f)	G 3/8" (m)	16,0 kg	16,5 kg
* Hose reel capacity		inner hose Ø max. length	1/4" 20 m 5/16" 20 m 3/8" 18 m 1/2" 15 m				
s. 430	8430.100	8420.100	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8430.101	8420.101	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	18,7 kg	19,2 kg
	8430.102	8420.102	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	19,5 kg	20,0 kg
	8430.103	8420.103	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	19,2 kg	19,7 kg
	8430.104	8420.104	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	20,2 kg	20,7 kg
	8430.150	-	without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-
Hose reel capacity		inner hose Ø max. length	* 5/16" 20 m 3/8" 20 m 1/2" 16 m 5/8" 14 m		** 5/8" 14 m 3/4" 8 m		
s. 430 ABS	9430.100	-	without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9430.101	-	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	15,2 kg	-
	9430.102	-	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	16,0 kg	-
	9430.103	-	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	15,7 kg	-
	9430.104	-	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	16,7 kg	-
* Hose reel capacity		inner hose Ø max. length	5/16" 20 m 3/8" 20 m 1/2" 15 m 5/8" 14 m				
s. 530	8530.100	8520.100	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.101	8520.101	20 m - 1/2" (996.220)	G 1/2" (f)	G 1/2" (m)	26,5 kg	27,5 kg
	8530.102	8520.102	25 m - 1/2" (996.225)	G 1/2" (f)	G 1/2" (m)	27,3 kg	28,3 kg
	8530.150	-	without hose **	G 1" (f)	G 1" (f)	22,0 kg	-
Hose reel capacity		inner hose Ø max. length	* 3/8" 25 m 1/2" 25 m 5/8" 22 m 3/4" 12 m 1" 8 m		** 3/4" 12 m 1" 8 m		
s. 540	8540.100	8550.100	without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8540.101	8550.101	15 m - 3/4" (997.215)	G 1" (f)	G 3/4" (m)	35,0 kg	40,5 kg
	8540.102	8550.102	20 m - 3/4" (997.220)	G 1" (f)	G 3/4" (m)	36,5 kg	42,0 kg
	8540.103	8550.103	15 m - 1" (998.215)	G 1" (f)	G 1" (m)	38,6 kg	44,1 kg
	8540.105	8550.105	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg	34,0 kg
	8540.106	8550.106	30 m - 1/2" (996.230)	G 1/2" (f)	G 1/2" (m)	36,4 kg	41,9 kg
Hose reel capacity		inner hose Ø max. length	* 5/8" 20 m 3/4" 20 m 1" 15 m 3/8" 30 m 1/2" 30 m 5/8" 30 m		** 3/8" 30 m 1/2" 30 m 5/8" 30 m		
s. 560	8560.100	-	without hose *	G 1" (f)	G 1" (f)	48,0 kg	-
	8560.101	-	30 m - 3/4" (997.230)	G 1" (f)	G 3/4" (m)	60,0 kg	-
	8560.103	-	40 m - 3/4" (997.240)	G 1" (f)	G 3/4" (m)	63,0 kg	-
	8560.104	-	20 m - 1" (998.220)	G 1" (f)	G 1" (m)	60,6 kg	-
	8560.105	-	30 m - 1" (998.230)	G 1" (f)	G 1" (m)	64,0 kg	-
	8560.106	-	without hose **	G 1/2" (f)	G 1/2" (f)	47,5 kg	-
Hose reel capacity		inner hose Ø max. length	* 5/8" 50 m 3/4" 40 m 1" 30 m 3/8" 60 m 1/2" 60 m 5/8" 60 m		** 3/8" 60 m 1/2" 60 m 5/8" 60 m		



Type of fluid
AIR-WATER


Pressure
10-20 bar

Material
- AISI 304 S. STEEL
- ABS


WITH SPRING




FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 100 °C



In accordance with directive




* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	atoxic hygienic	galvanized steel	Viton®	brass	AISI 304 s. steel
					

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
				290	186	140	196	226	98	330	300	339	135		470 x 260 x 490
				330	186	140	196	226	98	390	350	365	155		510 x 260 x 520
				390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
				430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
				430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
				530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
				540	300	218	227	268	165	535	510	572	315		660 x 390 x 690
				560	488	399	238	272	348	535	510	578	315		670 x 610 x 760



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 290 20 bar	8292.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	10,0 kg	-
	8292.101	-	10 m - 3/8" (995.210)	G 3/8" (f)	G 3/8" (m)	12,0 kg	-
	8292.104	-	15 m - 1/4" (993.215)	G 3/8" (f)	G 1/4" (m)	12,0 kg	-
* Hose reel capacity		inner hose Ø max. length	1/4" 5/16" 3/8"	16 m 14 m 10 m			
s. 330 20 bar	8332.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
	8332.101	-	12 m - 3/8" (995.211)	G 3/8" (f)	G 3/8" (m)	13,5 kg	-
	8333.101	-	12 m - 3/8" (995.112)	G 3/8" (f)	G 3/8" (m)	13,4 kg	-
* Hose reel capacity		inner hose Ø max. length	1/4" 5/16" 3/8" 1/2"	18 m 16 m 14 m 12 m			
s. 390 20 bar	8392.100	8382.100	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8392.102	8382.102	18 m - 3/8" (995.217)	G 3/8" (f)	G 3/8" (m)	16,0 kg	16,5 kg
* Hose reel capacity		inner hose Ø max. length	1/4" 5/16" 3/8" 1/2"	20 m 20 m 18 m 15 m			
s. 430 20 bar	8432.100	8422.100	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8432.101	8422.101	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	18,7 kg	19,2 kg
	8432.102	8422.102	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	19,5 kg	20,0 kg
	8432.103	8422.103	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	19,2 kg	19,7 kg
	8432.104	8422.104	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	20,2 kg	20,7 kg
	8432.150	-	without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-
10 bar	8433.102	-	15 m - 1/2" (996.116)	G 1/2" (f)	G 1/2" (m)	19,2 kg	-
Hose reel capacity		inner hose Ø max. length	* 5/16" 3/8" 1/2"	** 5/8" 3/4"			
s. 430 20 bar	9432.100	-	without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9432.101	-	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	15,2 kg	-
	9432.102	-	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	16,0 kg	-
	9432.103	-	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	15,7 kg	-
	9432.104	-	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	16,7 kg	-
10 bar	9433.102	-	15 m - 1/2" (996.116)	G 1/2" (f)	G 1/2" (m)	15,5 kg	-
* Hose reel capacity		inner hose Ø max. length	5/16" 3/8" 1/2"	20 m 20 m 16 m			
s. 530 20 bar	8532.100	8522.100	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8532.101	8522.101	20 m - 1/2" (996.220)	G 1/2" (f)	G 1/2" (m)	26,5 kg	27,5 kg
	8532.102	8522.102	25 m - 1/2" (996.225)	G 1/2" (f)	G 1/2" (m)	27,3 kg	28,3 kg
	8532.150	-	without hose **	G 1" (f)	G 1" (f)	22,0 kg	-
10 bar	8533.102	-	25 m - 1/2" (996.125)	G 1/2" (f)	G 1/2" (m)	27,1 kg	-
Hose reel capacity		inner hose Ø max. length	* 3/8" 1/2" 5/8"	** 3/4" 1"			
s. 540 20 bar	8542.100	8552.100	without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8542.101	8552.101	15 m - 3/4" (997.215)	G 1" (f)	G 3/4" (m)	35,0 kg	40,5 kg
	8542.102	8552.102	20 m - 3/4" (997.220)	G 1" (f)	G 3/4" (m)	36,5 kg	42,0 kg
	8542.103	8552.103	15 m - 1" (998.215)	G 1" (f)	G 1" (m)	38,6 kg	44,1 kg
	8542.105	8552.105	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg	34,0 kg
	8542.106	8552.106	30 m - 1/2" (996.230)	G 1/2" (f)	G 1/2" (m)	36,4 kg	41,9 kg
s. 540 10 bar	8543.102	-	20 m - 3/4" (997.120)	G 3/4" (f)	G 3/4" (m)	36,5 kg	-
	8543.103	-	15 m - 1" (998.115)	G 1" (f)	G 1" (m)	38,0 kg	-
	8543.106	-	30 m - 1/2" (996.130)	G 1/2" (f)	G 1/2" (m)	36,5 kg	-
Hose reel capacity		inner hose Ø max. length	* 5/8" 3/4" 1"	** 3/8" 1/2" 5/8"			
s. 560 20 bar	8562.100	-	without hose *	G 1" (f)	G 1" (f)	48,0 kg	-
	8562.101	-	30 m - 3/4" (997.230)	G 1" (f)	G 3/4" (m)	60,0 kg	-
	8562.103	-	40 m - 3/4" (997.240)	G 1" (f)	G 3/4" (m)	63,0 kg	-
	8562.104	-	20 m - 1" (998.220)	G 1" (f)	G 1" (m)	60,6 kg	-
	8562.105	-	30 m - 1" (998.230)	G 1" (f)	G 1" (m)	64,0 kg	-
	8562.106	-	without hose **	G 1/2" (f)	G 1/2" (f)	47,5 kg	-
10 bar	8563.103	-	40 m - 3/4" (997.140)	G 1" (f)	G 3/4" (m)	63,5 kg	-
	8563.105	-	30 m - 1" (998.130)	G 1" (f)	G 1" (m)	64,5 kg	-
Hose reel capacity		inner hose Ø max. length	* 5/8" 3/4" 1"	** 3/8" 1/2" 5/8"			
			50 m 40 m 30 m	60 m 60 m 60 m			

Atoxic hygienic hose

Black rubber hose



Type of fluid
HOT WATER


Pressure
50-100 bar

Material
- PAINTED STEEL
- ABS


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	hygienic	galvanized steel	Viton®	AISI 304 s. steel	galvanized steel

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
				330	186	140	196	226	98	390	350	365	155		510 x 260 x 520
				390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
				430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
				430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
				530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
				540	300	218	227	268	165	535	510	572	315		660 x 390 x 690
				560	488	399	238	272	348	535	510	578	315		670 x 610 x 760

Overall dimensions SWIVELLING (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
				390	184	146	106	144	98	410	390	482	155		580 x 280 x 590
				430	208	162	118	164	97	450	415	540	264		580 x 280 x 590
				530	228	182	154	200	104	535	510	642	315		650 x 290 x 700
				540	300	218	227	268	165	535	510	700	315		660 x 390 x 690
(W: width - D: depth - H: height)															

(W: width - D: depth - H: height)



		P/N		Hose supplied	Connection		Weight	
		fixed	swivelling		inlet	outlet	fixed	swivelling
s. 330 100 bar	8330.200	-		without hose *	G 1/2" (f)	G 3/8"(f) G 1/2"(f)	11,2 kg	-
	8330.201	-		12 m - 3/8" (995.313)	G 1/2" (f)	G 3/8" (m)	15,7 kg	-
* Hose reel capacity		inner hose Ø max. length		1/4" 5/16" 3/8" 1/2"	12 m 12 m 12 m 8 m			
s. 390 100 bar	8390.200	8380.200		without hose *	G 1/2" (f)	G 3/8"(f) G 1/2"(f)	13,0 kg	14,0 kg
	8390.202	8380.202		17 m - 3/8" (995.318)	G 1/2" (f)	G 3/8" (m)	19,0 kg	20,0 kg
* Hose reel capacity		inner hose Ø max. length		1/4" 5/16" 3/8" 1/2"	15 m 16 m 17 m 12 m			
s. 430 100 bar	8430.200	8420.200		without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	17,2 kg
	8430.201	8420.201		10 m - 1/2" (996.311)	G 1/2" (f)	G 1/2" (m)	20,7 kg	22,2 kg
	8430.202	8420.202		15 m - 1/2" (996.316)	G 1/2" (f)	G 1/2" (m)	22,1 kg	23,5 kg
	8430.250	-		without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-
Hose reel capacity		inner hose Ø max. length		* 5/16" 3/8" 1/2"	20 m 20 m 16 m ** 5/8" 3/4"			
s. 430 ABS 100 bar	9430.200	-		without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9430.201	-		10 m - 1/2" (996.311)	G 1/2" (f)	G 1/2" (m)	17,3 kg	-
	9430.202	-		15 m - 1/2" (996.316)	G 1/2" (f)	G 1/2" (m)	18,7 kg	-
	9431.202	-		15 m - 1/2" (996.415)	G 1/2" (f)	G 1/2" (m)	20,0 kg	-
* Hose reel capacity		inner hose Ø max. length		5/16" 3/8" 1/2"	20 m 20 m 16 m			
s. 530 100 bar	8530.200	8520.200		without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.201	8520.201		20 m - 1/2" (996.321)	G 1/2" (f)	G 1/2" (m)	30,0 kg	31,0 kg
* Hose reel capacity		inner hose Ø max. length		3/8" 1/2" 5/8"	25 m 25 m 22 m			
s. 540 100 bar	8540.200	8550.200		without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8540.202	8550.202		20 m - 3/4" (997.320)	G 1" (f)	G 3/4" (m)	40,7 kg	46,2 kg
s. 540 50 bar	8540.203	8550.203		15 m - 1" (998.315)	G 1" (f)	G 1" (m)	42,0 kg	47,5 kg
* Hose reel capacity		inner hose Ø max. length		5/8" 3/4" 1"	20 m 22 m 15 m			
s. 560 100 bar	8560.200	-		without hose *	G 1" (f)	G 1" (f)	48,0 kg	-
s. 560 50 bar	8560.205	-		30 m - 1" (998.330)	G 1" (f)	G 1" (m)	78,2 kg	-
* Hose reel capacity		inner hose Ø max. length		5/8" 3/4" 1"	50 m 40 m 30 m			



Hygienic hose



Black rubber hose



Type of fluid
HOT WATER


Pressure
50-100 bar

Material
- AISI 304 S. STEEL
- ABS


WITH SPRING




FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	hygienic	galvanized steel	Viton®	AISI304.s. steel	AISI 304 s. steel
					

Overall dimensions FIXED (mm)						Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
						330	186	140	196	226	98	390	350	365	155		510 x 260 x 520
						390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
						430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
						430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
						530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
						540	300	218	227	268	165	535	510	572	315		660 x 390 x 690
						560	488	399	238	272	348	535	510	578	315		670 x 610 x 760

Overall dimensions SWIVELLING (mm)						Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
						390	184	146	106	144	98	410	390	482	155		580 x 280 x 590
						430	208	162	118	164	97	450	415	540	264		580 x 280 x 590
						530	228	182	154	200	104	535	510	642	315		650 x 290 x 700
						540	300	218	227	268	165	535	510	700	315		660 x 390 x 690

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 330 100 bar	8332.400	-	without hose *	G 1/2" (f)	G 3/8"(f) G 1/2"(f)	11,2 kg	-
	8332.201	-	12 m - 3/8" (995.313)	G 1/2" (f)	G 3/8" (m)	15,7 kg	-
	8333.202	-	12 m - 3/8" (995.412)	G 1/2" (f)	G 3/8" (m)	15,7 kg	-

* Hose reel capacity	inner hose Ø max. length	1/4" 12 m	5/16" 12 m	3/8" 12 m	1/2" 11 m
----------------------	-----------------------------	--------------	---------------	--------------	--------------

s. 390 100 bar	8392.200	8382.200	without hose *	G 1/2" (f)	G 3/8"(f) G 1/2"(f)	13,0 kg	13,5 kg
	8392.202	8382.202	17 m - 3/8" (995.318)	G 1/2" (f)	G 3/8" (m)	19,0 kg	19,5 kg
	8393.201	8383.201	12 m - 3/8" (995.412)	G 1/2" (f)	G 3/8" (m)	17,5 kg	18,0 kg

* Hose reel capacity	inner hose Ø max. length	1/4" 15 m	5/16" 16 m	3/8" 17 m	1/2" 12 m
----------------------	-----------------------------	--------------	---------------	--------------	--------------

s. 430 100 bar	8434.200	8424.200	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8434.250	-	without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-
	8432.201	8422.201	10 m - 1/2" (996.311)	G 1/2" (f)	G 1/2" (m)	20,7 kg	21,2 kg
	8432.202	8422.202	15 m - 1/2" (996.316)	G 1/2" (f)	G 1/2" (m)	22,1 kg	22,6 kg
	8433.202	8423.202	15 m - 1/2" (996.415)	G 1/2" (f)	G 1/2" (m)	22,1 kg	22,6 kg

Hose reel capacity	inner hose Ø max. length	* 5/16" 20 m	3/8" 20 m	1/2" 16 m	** 5/8" 14 m	3/4" 8 m
--------------------	-----------------------------	-----------------	--------------	--------------	-----------------	-------------

s. 430 ABS 100 bar	9434.200	-	without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9432.201	-	10 m - 1/2" (996.311)	G 1/2" (f)	G 1/2" (m)	17,3 kg	-
	9432.202	-	15 m - 1/2" (996.316)	G 1/2" (f)	G 1/2" (m)	18,7 kg	-
	9433.202	-	15 m - 1/2" (996.415)	G 1/2" (f)	G 1/2" (m)	20,0 kg	-

* Hose reel capacity	inner hose Ø max. length	5/16" 20 m	3/8" 20 m	1/2" 16 m
----------------------	-----------------------------	---------------	--------------	--------------

s. 530 100 bar	8534.200	8524.200	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8532.201	8522.201	20 m - 1/2" (996.321)	G 1/2" (f)	G 1/2" (m)	30,0 kg	31,0 kg
	8534.250	-	without hose **	G 1" (f)	G 1" (f)	22,5 kg	-
	8533.202	8523.202	25 m - 1/2" (996.425)	G 1/2" (f)	G 1/2" (m)	32,0 kg	33,0 kg

Hose reel capacity	inner hose Ø max. length	* 3/8" 25 m	1/2" 25 m	5/8" 22 m	** 3/4" 12 m	1" 8 m
--------------------	-----------------------------	----------------	--------------	--------------	-----------------	-----------

s. 540 100 bar	8544.200	8554.200	without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8542.202	8552.202	20 m - 3/4" (997.320)	G 1" (f)	G 3/4" (m)	40,7 kg	46,2 kg
	8544.205	8554.205	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg	34,0 kg
	8543.202	8553.202	20 m - 3/4" (997.420)	G 1" (f)	G 3/4" (m)	40,7 kg	46,2 kg

s. 540 50 bar	8542.203	8552.203	15 m - 1" (998.315)	G 1" (f)	G 1" (m)	42,0 kg	47,5 kg
-------------------------	-----------------	-----------------	---------------------	----------	----------	---------	---------

Hose reel capacity	inner hose Ø max. length	* 5/8" 20 m	3/4" 22 m	1" 15 m	** 3/8" 30 m	1/2" 30 m	5/8" 30 m
--------------------	-----------------------------	----------------	--------------	------------	-----------------	--------------	--------------

s. 560 100 bar	8564.200	-	without hose *	G 1" (f)	G 1" (f)	48,0 kg	-
	8564.206	-	without hose **	G 1/2" (f)	G 1/2" (f)	47,5 kg	-
s. 560 50 bar	8562.205	-	30 m - 1" (998.330)	G 1" (f)	G 1" (m)	78,2 kg	-

Hose reel capacity	inner hose Ø max. length	* 5/8" 50 m	3/4" 40 m	1" 30 m	** 3/8" 60 m	1/2" 60 m	5/8" 60 m
--------------------	-----------------------------	----------------	--------------	------------	-----------------	--------------	--------------

Hygienic hose
 Black rubber hose



Type of fluid
HOT WATER


Pressure
200 bar

Material
- PAINTED STEEL
- ABS


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	hygienic	galvanized steel	Viton®	AISI 304 s. steel	galvanized steel

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
	330	186	140	196	226	98	390	350	365	155		510 x 260 x 520		
	390	186	140	196	226	98	410	390	410	155		580 x 280 x 590		
	430	186	140	197	226	97	450	415	456	264		580 x 280 x 590		
	430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590		
	530	203	153	221	258	104	535	510	558	315		650 x 290 x 700		
	540	300	218	227	268	165	535	510	572	315		660 x 390 x 690		
	560	488	399	238	272	348	535	510	578	315		670 x 610 x 760		

Overall dimensions SWIVELLING (mm)											Series		A		B		C		D		E		F		G		H		I		Packaging (mm) W x D x H	
											390	184	146	106	144	98	410	390	482	155		580 x 280 x 590										
											430	208	162	118	164	97	450	415	540	264		580 x 280 x 590										
											530	228	182	154	200	104	535	510	642	315		650 x 290 x 700										
											540	300	218	227	268	165	535	510	700	315		660 x 390 x 690										
(W: width - D: depth - H: height)																																

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 330	8330.300	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
	8330.301	-	12 m - 5/16" (994.512)	G 3/8" (f)	G 3/8" (f)	14,8 kg	-

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	12 m	12 m	12 m	8 m

s. 390	8390.300	8380.300	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8390.302	8380.302	17 m - 5/16" (994.517)	G 3/8" (f)	G 3/8" (f)	17,0 kg	17,5 kg

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	15 m	16 m	17 m	12 m

s. 430	8430.300	8420.300	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8430.301	8420.301	12 m - 3/8" (995.512)	G 3/8" (f)	G 3/8" (f)	20,3 kg	20,8 kg
	8430.302	8420.302	18 m - 3/8" (995.518)	G 3/8" (f)	G 3/8" (f)	22,4 kg	22,9 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 430 ABS	9430.300	-	without hose *	G 3/8" (f)	G 1/2" (f)	12,5 kg	-
	9430.301	-	12 m - 3/8" (995.512)	G 3/8" (f)	G 3/8" (f)	16,8 kg	-
	9430.302	-	18 m - 3/8" (995.518)	G 3/8" (f)	G 3/8" (f)	18,8 kg	-
	9431.302	-	18 m - 3/8" (995.618)	G 3/8" (f)	G 3/8" (f)	19,0 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 530	8530.300	8520.300	without hose *	G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.301	8520.301	20 m - 3/8" (995.520)	G 3/8" (f)	G 3/8" (f)	27,0 kg	28,0 kg
	8530.302	8520.302	25 m - 3/8" (995.525)	G 3/8" (f)	G 3/8" (f)	28,5 kg	29,5 kg

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	25 m	25 m	22 m

s. 540	8540.300	8550.300	without hose *	G 3/8" (f)	G 1/2" (f)	28,0 kg	33,5 kg
	8540.301	8550.301	30 m - 3/8" (995.530)	G 3/8" (f)	G 3/8" (f)	36,8 kg	42,3 kg

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	30 m	30 m	30 m

s. 560	8560.300	-	without hose *	G 3/8" (f)	G 1/2" (f)	48,0 kg	-
	8560.301	-	40 m - 3/8" (995.540)	G 3/8" (f)	G 3/8" (f)	59,0 kg	-
	8560.302	-	50 m - 3/8" (995.550)	G 3/8" (f)	G 3/8" (f)	64,8 kg	-

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	60 m	60 m	60 m

Hygienic hose
 Black rubber hose



Type of fluid
HOT WATER


Pressure
200 bar

Material
- AISI 304 S. STEEL
- ABS


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	hygienic	galvanized steel	Viton®	AISI 304 s. steel	AISI 304 s. steel
					

Overall dimensions FIXED (mm)						Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
						330	186	140	196	226	98	390	350	365	155		510 x 260 x 520
						390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
						430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
						430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
						530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
						540	300	218	227	268	165	535	510	572	315		660 x 390 x 690
						560	488	399	238	272	348	535	510	578	315		670 x 610 x 760

Overall dimensions SWIVELLING (mm)						Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
						390	184	146	106	144	98	410	390	482	155		580 x 280 x 590
						430	208	162	118	164	97	450	415	540	264		580 x 280 x 590
						530	228	182	154	200	104	535	510	642	315		650 x 290 x 700
						540	300	218	227	268	165	535	510	700	315		660 x 390 x 690

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 330	8332.300	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
	8332.301	-	12 m - 5/16" (994.512)	G 3/8" (f)	G 3/8" (f)	14,8 kg	-
	8333.301	-	12 m - 5/16" (994.612)	G 3/8" (f)	G 3/8" (f)	14,8 kg	-

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	12 m	12 m	12 m	8 m

s. 390	8392.300	8382.300	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8392.302	8382.302	17 m - 5/16" (994.517)	G 3/8" (f)	G 3/8" (f)	17,0 kg	17,5 kg
	8393.301	8383.301	12 m - 5/16" (994.612)	G 3/8" (f)	G 3/8" (f)	16,6 kg	17,1 kg

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	15 m	16 m	17 m	12 m

s. 430	8434.300	8424.300	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8432.301	8422.301	12 m - 3/8" (995.512)	G 3/8" (f)	G 3/8" (f)	20,3 kg	20,8 kg
	8432.302	8422.302	18 m - 3/8" (995.518)	G 3/8" (f)	G 3/8" (f)	22,4 kg	22,9 kg
	8433.302	8423.302	18 m - 3/8" (995.618)	G 3/8" (f)	G 3/8" (f)	22,4 kg	22,9 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 430 ABS	9434.300	-	without hose *	G 3/8" (f)	G 1/2" (f)	12,5 kg	-
	9432.301	-	12 m - 3/8" (995.512)	G 3/8" (f)	G 3/8" (f)	16,8 kg	-
	9432.302	-	18 m - 3/8" (995.518)	G 3/8" (f)	G 3/8" (f)	18,8 kg	-
	9433.302	-	18 m - 3/8" (995.618)	G 3/8" (f)	G 3/8" (f)	19,0 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 530	8534.300	8524.300	without hose *	G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8532.301	8522.301	20 m - 3/8" (995.520)	G 3/8" (f)	G 3/8" (f)	27,0 kg	28,0 kg
	8532.302	8522.302	25 m - 3/8" (995.525)	G 3/8" (f)	G 3/8" (f)	28,5 kg	29,5 kg
	8533.302	8523.302	25 m - 3/8" (995.625)	G 3/8" (f)	G 3/8" (f)	28,5 kg	29,5 kg

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	25 m	25 m	22 m

s. 540	8544.300	8554.300	without hose *	G 3/8" (f)	G 1/2" (f)	28,5 kg	34,0 kg
	8542.301	8552.301	30 m - 3/8" (995.530)	G 3/8" (f)	G 3/8" (f)	36,8 kg	42,3 kg
	8543.301	8553.301	30 m - 3/8" (995.630)	G 3/8" (f)	G 3/8" (f)	36,8 kg	42,3 kg

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	30 m	30 m	30 m

s. 560	8564.300	-	without hose *	G 3/8" (f)	G 1/2" (f)	47,5 kg	-
	8562.301	-	40 m - 3/8" (995.540)	G 3/8" (f)	G 3/8" (f)	59,0 kg	-
	8562.302	-	50 m - 3/8" (995.550)	G 3/8" (f)	G 3/8" (f)	64,8 kg	-

* Hose reel capacity	inner hose Ø	3/8"	1/2"	5/8"
	max. length	60 m	60 m	60 m

Hygienic hose
 Black rubber hose



Type of fluid
HOT WATER


Pressure
400 bar

Material
PAINTED STEEL


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted

Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	Viton® - Teflon®	AISI 304 s. steel	galvanized steel
				

Overall dimensions FIXED (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	330	186	140	196	226	98	390	350	365	155		510 x 260 x 520		
	390	186	140	196	226	98	410	390	410	155		580 x 280 x 590		
	430	186	140	197	226	97	450	415	456	264		580 x 280 x 590		
	530	203	153	221	258	104	535	510	558	315		650 x 290 x 700		
	540	300	218	227	268	165	535	510	572	315		660 x 390 x 690		
	560	488	399	238	272	348	535	510	578	315		670 x 610 x 760		
	(W: width - D: depth - H: height)													

(W: width - D: depth - H: height)

Overall dimensions SWIVELLING (mm)										Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	390	184	146	106	144	98	410	390	482	155		580 x 280 x 590									
	430	208	162	118	164	97	450	415	540	264		580 x 280 x 590									
	530	228	182	154	200	104	535	510	642	315		650 x 290 x 700									
	540	300	218	227	268	165	535	510	700	315		660 x 390 x 690									

(W: width - D: depth - H: height)



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 330	8330.350	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
* Hose reel capacity	inner hose Ø max. length		1/4" 12 m	5/16" 12 m	3/8" 12 m	1/2" 8 m	
s. 390	8390.350	8380.350	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8390.352	8380.352	17 m - 5/16" (994.717)	G 3/8" (f)	G 3/8" (f)	20,7 kg	21,2 kg
* Hose reel capacity	inner hose Ø max. length		1/4" 15 m	5/16" 16 m	3/8" 17 m	1/2" 12 m	
s. 430	8430.350	8420.350	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8430.354	8420.354	15 m - 3/8" (995.815)	G 3/8" (f)	G 3/8" (f)	23,1 kg	23,6 kg
* Hose reel capacity	inner hose Ø max. length		5/16" 12 m	3/8" 15 m			
s. 530	8530.350	8520.350	without hose *	G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.352	8520.352	25 m - 3/8" (995.825)	G 3/8" (f)	G 3/8" (f)	31,8 kg	32,8 kg
* Hose reel capacity	inner hose Ø max. length		3/8" 25 m	1/2" 25 m			
s. 540	8540.350	8550.350	without hose *	G 3/8" (f)	G 1/2" (f)	28,0 kg	33,5 kg
* Hose reel capacity	inner hose Ø max. length		3/8" 30 m	1/2" 30 m			
s. 560	8560.350	-	without hose *	G 3/8" (f)	G 1/2" (f)	48,0 kg	-
* Hose reel capacity	inner hose Ø max. length		3/8" 60 m	1/2" 60 m			



Type of fluid
HOT WATER


Pressure
400-700 bar

Material
- AISI 304 S. STEEL
- ABS


WITH SPRING




FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Hoses		Connections	Seals	Swivel joint	Central pin
black rubber	hygienic	galvanized steel	Viton® - Teflon®	AISI 304 s. steel	AISI 304 s. steel
					

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H		
				330	186	140	196	226	98	390	350	365	155		510 x 260 x 520	
				390	186	140	196	226	98	410	390	410	155		580 x 280 x 590	
				430	186	140	197	226	97	450	415	456	264		580 x 280 x 590	
				430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590	
				530	203	153	221	258	104	535	510	558	315		650 x 290 x 700	
				540	300	218	227	268	165	535	510	572	315		660 x 390 x 690	
				560	488	399	238	272	348	535	510	578	315		670 x 610 x 760	

Overall dimensions SWIVELLING (mm)					Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H		
					390	184	146	106	144	98	410	390	482	155		580 x 280 x 590	
					430	208	162	118	164	97	450	415	540	264		580 x 280 x 590	
					530	228	182	154	200	104	535	510	642	315		650 x 290 x 700	
					540	300	218	227	268	165	535	510	700	315		660 x 390 x 690	

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 330 400 bar	8332.350	-	without hose *		G 3/8" (f)	G 3/8" (f)	11,2 kg	-
--------------------------	-----------------	---	----------------	--	------------	------------	---------	---

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	12 m	12 m	12 m	8 m

s. 390 400 bar	8392.350	8382.350	without hose *		G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8392.352	8382.352	17 m - 5/16" (994.717)		G 3/8" (f)	G 3/8" (f)	20,7 kg	21,2 kg

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	15 m	16 m	17 m	12 m

s. 430 400 bar	8434.350	8424.350	without hose *		G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8432.354	8422.354	15 m - 3/8" (995.815)		G 3/8" (f)	G 3/8" (f)	23,1 kg	23,6 kg
	8433.354	8423.354	15 m - 3/8" (995.915)		G 3/8" (f)	G 3/8" (f)	23,1 kg	23,6 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"
	max. length	12 m	15 m

s. 430 ABS 400 bar	9434.350	-	without hose *		G 3/8" (f)	G 1/2" (f)	12,5 kg	-
	9432.353	-	10 m - 3/8" (995.810)		G 3/8" (f)	G 3/8" (f)	18,4 kg	-
	9432.354	-	15 m - 3/8" (995.815)		G 3/8" (f)	G 3/8" (f)	20,8 kg	-

* Hose reel capacity	inner hose Ø	3/8"	1/2"
	max. length	25 m	25 m

s. 530 400 bar	8534.350	8524.350	without hose *		G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8532.352	8522.352	25 m - 3/8" (995.825)		G 3/8" (f)	G 3/8" (f)	31,8 kg	32,8 kg
	8533.352	8523.352	25 m - 3/8" (995.925)		G 3/8" (f)	G 3/8" (f)	31,8 kg	32,8 kg

s. 530 700 bar	8534.550	-	without hose *		G 3/8" (f)	G 3/8" (f)	21,0 kg	-
--------------------------	-----------------	---	----------------	--	------------	------------	---------	---

* Hose reel capacity	inner hose Ø	3/8"	1/2"
	max. length	25 m	25 m

s. 540 400 bar	8544.350	8554.350	without hose *		G 3/8" (f)	G 1/2" (f)	28,0 kg	33,5 kg
--------------------------	-----------------	-----------------	----------------	--	------------	------------	---------	---------

s. 540 700 bar	8544.550	-	without hose *		G 3/8" (f)	G 3/8" (f)	28,5 kg	-
--------------------------	-----------------	---	----------------	--	------------	------------	---------	---

* Hose reel capacity	inner hose Ø	3/8"	1/2"
	max. length	30 m	30 m

s. 560 400 bar	8564.350	-	without hose *		G 3/8" (f)	G 3/8" (f)	48,0 kg	-
--------------------------	-----------------	---	----------------	--	------------	------------	---------	---

* Hose reel capacity	inner hose Ø	3/8"	1/2"
	max. length	60 m	60 m

Hygienic hose
 Black rubber hose



Type of fluid
HOT WATER


Pressure
**100-200
400 bar**

Material
AISI 316 S. STEEL

WITH SPRING



FIXED*



- with hose, see page 139
- without hose, max. 130 °C



* can be rendered swivelling by using the special bracket, see page 81.


In accordance with directive



The hose reels in AISI 316 stainless steel can also be used for the following fluids:

OIL AND SIMILAR GREASE DIESEL ADBLUE®

Seals	Swivel joint	Central pin
Viton® - Teflon®	AISI 316 s. steel	AISI 316 s. steel
		

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
			430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
			530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
			540	300	218	227	268	165	535	510	572	315		660 x 390 x 690
			560	488	399	238	272	348	535	510	578	315		670 x 610 x 760

(W: width - D: depth - H: height)

See specific catalogue





	P/N	Hose supplied	Connection		Weight
			inlet	outlet	
s. 430 100 bar	8435.200	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg
s. 430 200 bar	8435.300	without hose **	G 3/8" (f)	G 1/2" (f)	16,0 kg
s. 430 400 bar	8435.350	without hose **	G 3/8" (f)	G 1/2" (f)	16,0 kg
* Hose reel capacity		inner hose Ø	5/16"	3/8"	1/2"
		max. length	20 m	20 m	16 m
** Hose reel capacity		inner hose Ø	5/16"	3/8"	
		max. length	12 m	15 m	
s. 530 100 bar	8535.200	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg
s. 530 200 bar	8535.300	without hose **	G 3/8" (f)	G 1/2" (f)	21,0 kg
s. 530 400 bar	8535.350	without hose **	G 3/8" (f)	G 1/2" (f)	21,0 kg
* Hose reel capacity		inner hose Ø	3/8"	1/2"	5/8"
		max. length	25 m	25 m	22 m
** Hose reel capacity		inner hose Ø	3/8"	1/2"	
		max. length	25 m	25 m	
s. 540 100 bar	8545.200	without hose *	G 1" (f)	G 1" (f)	28,0 kg
	8545.205	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg
* Hose reel capacity		inner hose Ø	5/8"	3/4"	1"
		max. length	20 m	22 m	15 m
** Hose reel capacity		inner hose Ø	3/8"	1/2"	5/8"
		max. length	32 m	33 m	36 m
s. 560 100 bar	8565.200	without hose *	G 1" (f)	G 1" (f)	48,5 kg
	8565.206	without hose **	G 1/2" (f)	G 1/2" (m)	47,5 kg
* Hose reel capacity		inner hose Ø	5/8"	3/4"	1"
		max. length	50 m	40 m	30 m
** Hose reel capacity		inner hose Ø	3/8"	1/2"	5/8"
		max. length	60 m	60 m	60 m





Type of fluid
**OIL AND
SIMILAR**


Pressure
**50-100
150 bar**

Material
**- PAINTED STEEL
- ABS**


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 80 °C



In accordance with directive



for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	polyurethane	galvanized steel	galvanized steel

Overall dimensions FIXED (mm)											Series		A		B		C		D		E		F		G		H		I		Packaging (mm) W x D x H	
											330		186	140	196	226	98	390	350	365	155			510 x 260 x 520								
390		186	140	196	226	98	410	390	410	155	580 x 280 x 590																					
430		186	140	197	226	97	450	415	456	264	580 x 280 x 590																					
430 ABS		186	140	197	226	110	450	425	461	259	580 x 280 x 590																					
530		203	153	221	258	104	535	510	558	315	650 x 290 x 700																					
540		300	218	227	268	165	535	510	572	315	660 x 390 x 690																					
560		488	399	238	272	348	535	510	578	315	670 x 610 x 760																					



		P/N		Hose supplied	Connection		Weight	
		fixed	swivelling		inlet	outlet	fixed	swivelling
s. 330 150 bar	8330.400	-	without hose *		G 1/2" (f)	G 3/8"(f) G 1/2"(f)	11,2 kg	-
	8330.402	-	12 m - 3/8" (995.312)		G 1/2" (f)	G 1/2" (m)	15,0 kg	-
* Hose reel capacity		inner hose ø max. length	1/4" 12 m	5/16" 12 m	3/8" 12 m	1/2" 8 m		
s. 390 150 bar	8390.400	8380.400	without hose *		G 1/2" (f)	G 3/8"(f) G 1/2"(f)	13,0 kg	13,5 kg
	8390.401	8380.401	12 m - 3/8" (995.312)		G 1/2" (f)	G 1/2" (m)	16,8 kg	17,3 kg
	8390.402	8380.402	17 m - 3/8" (995.317)		G 1/2" (f)	G 1/2" (m)	18,3 kg	18,8 kg
* Hose reel capacity		inner hose ø max. length	1/4" 15 m	5/16" 16 m	3/8" 17 m	1/2" 12 m		
s. 430 150 bar	8430.400	8420.400	without hose *		G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8430.401	8420.401	10 m - 1/2" (996.310)		G 1/2" (f)	G 1/2" (m)	20,5 kg	21,0 kg
	8430.402	8420.402	15 m - 1/2" (996.315)		G 1/2" (f)	G 1/2" (m)	12,5 kg	13,0 kg
	8430.450	-	without hose **		G 1" (f)	G 3/4" (f)	16,8 kg	-
s. 430 for suction	8430.400/AS	-	without hose *		G 1/2" (f)	G 1/2" (f)	16,0 kg	-
	8430.401/AS	8420.401/AS	10 m - 1/2" (996.310)		G 1/2" (f)	G 1/2" (m)	20,5 kg	21,0 kg
	8430.415/AS	-	without hose **		G 1/2" (f)	G 1/2" (m)	16,0 kg	-
	8430.452/AS	-	8 m - 3/4" (997.3308)		G 1" (f)	G 3/4" (m)	22,0 kg	-
s. 430 100 bar	8430.415	-	without hose **		G 1/2" (f)	G 1/2" (m)	16,0 kg	-
	8430.416	-	10 m - 5/8" (999.3310)		G 3/4" (f)	G 3/4" (m)	21,5 kg	-
	8430.417	-	8 m - 3/4" (997.3308)		G 3/4" (f)	G 3/4" (m)	22,0 kg	-
s. 430 ABS 150 bar	9430.400	-	without hose *		G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9430.401	-	10 m - 1/2" (996.310)		G 1/2" (f)	G 1/2" (m)	17,0 kg	-
	9430.402	-	15 m - 1/2" (996.315)		G 1/2" (f)	G 1/2" (m)	19,0 kg	-
s. 430 ABS for suction	9430.400/AS	-	without hose *		G 1/2" (f)	G 1/2" (f)	12,5 kg	-
s. 430 ABS 100 bar	9430.415	-	without hose **		G 1/2" (f)	G 1/2" (m)	12,5 kg	-
	9430.416	-	10 m - 5/8" (999.3310)		G 3/4" (f)	G 3/4" (m)	17,0 kg	-
	9430.417	-	8 m - 3/4" (997.3308)		G 3/4" (f)	G 3/4" (m)	17,5 kg	-
Hose reel capacity		inner hose ø max. length	* 5/16" 20 m	3/8" 20 m	1/2" 16 m	** 5/8" 14 m	3/4" 8 m	
s. 530 150 bar	8530.400	8520.400	without hose *		G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.401	8520.401	20 m - 1/2" (996.320)		G 1/2" (f)	G 1/2" (m)	29,2 kg	30,2 kg
	8530.402	8520.402	25 m - 1/2" (996.325)		G 1/2" (f)	G 1/2" (m)	31,1 kg	32,1 kg
s. 530 100 bar	8530.415	-	without hose **		G 1" (f)	G 1" (f)	21,0 kg	-
	8530.416	-	12 m - 3/4" (997.3312)		G 1" (f)	G 3/4" (m)	28,8 kg	-
Hose reel capacity		inner hose ø max. length	* 3/8" 25 m	1/2" 25 m	5/8" 22 m	** 3/4" 12 m	1" 8 m	
s. 540 150 bar	8540.400	8550.400	without hose *		G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8540.405	8550.405	without hose **		G 1/2" (f)	G 1/2" (f)	28,0 kg	33,5 kg
	8540.406	8550.406	30 m - 1/2" (996.330)		G 1/2" (f)	G 1/2" (m)	40,3 kg	45,8 kg
s. 540 100 bar	8540.411	8550.411	15 m - 3/4" (997.3315)		G 1" (f)	G 3/4" (m)	37,6 kg	43,1 kg
	8540.412	8550.412	20 m - 3/4" (997.3320)		G 1" (f)	G 3/4" (m)	40,2 kg	45,7 kg
s. 540 50 bar	8540.413	8550.413	15 m - 1" (998.3315)		G 1" (f)	G 1" (m)	42,6 kg	48,1 kg
	8540.414	-	10 m - 1" (998.3310)		G 1" (f)	G 1" (m)	38,2 kg	-
Hose reel capacity		inner hose ø max. length	* 3/4" 22 m	1" 15 m	** 3/8" 30 m	1/2" 30 m	5/8" 30 m	
s. 560 150 bar	8560.400	-	without hose *		G 1" (f)	G 1" (f)	48,0 kg	-
* Hose reel capacity		inner hose ø max. length	5/8" 50 m	3/4" 40 m	1" 30 m			



Prepared with outlet connection for Ø 3/4" hoses



Type of fluid
**OIL AND
SIMILAR**


Pressure
150 bar

Material
**- AISI 304 S. STEEL
- ABS**


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Seals	Swivel joint	Central pin
Viton®	AISI 304 s. steel	AISI 304 s. steel
		

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
				390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
				430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
				430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
				530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
				540	300	218	227	268	165	535	510	572	315		660 x 390 x 690

Overall dimensions SWIVELLING (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
				390	184	146	106	144	98	410	390	482	155		580 x 280 x 590
				430	208	162	118	164	97	450	415	540	264		580 x 280 x 590
				530	228	182	154	200	104	535	510	642	315		650 x 290 x 700
				540	300	218	227	268	165	535	510	700	315		660 x 390 x 690

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 390	8392.200	8382.200	without hose *	G 1/2" (f)	G 3/8"(f) G 1/2"(f)	13,0 kg	13,5 kg
---------------	-----------------	-----------------	----------------	------------	------------------------	---------	---------

* Hose reel capacity	inner hose Ø	1/4"	5/16"	3/8"	1/2"
	max. length	15 m	16 m	17 m	12 m

s. 430	8434.200	8424.200	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8434.250	-	without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-

Hose reel capacity	inner hose Ø	* 5/16"	3/8"	1/2"	** 5/8"	3/4"
	max. length	20 m	20 m	16 m	14 m	8 m

s. 430 ABS	9434.200	-	without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9432.401	-	10 m - 1/2" (996.310)	G 1/2" (f)	G 1/2" (m)	16,9 kg	-
	9432.402	-	15 m - 1/2" (996.315)	G 1/2" (f)	G 1/2" (m)	20,0 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 530	8534.200	8524.200	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8534.250	-	without hose **	G 1" (f)	G 1" (f)	22,5 kg	-

Hose reel capacity	inner hose Ø	* 3/8"	1/2"	5/8"	** 3/4"	1"
	max. length	25 m	25 m	22 m	12 m	8 m

s. 540	8544.200	8554.200	without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8544.205	8554.205	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg	34,0 kg

Hose reel capacity	inner hose Ø	* 3/4"	1"	** 3/8"	1/2"	5/8"
	max. length	22 m	15 m	30 m	30 m	30 m



Type of fluid
GREASE

Pressure
400-600 bar

Material
- PAINTED STEEL
- ABS


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 80 °C



In accordance with directive



for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	polyurethane	galvanized steel	galvanized steel

Overall dimensions FIXED (mm)					Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
					330	186	140	196	226	98	390	350	365	155		510 x 260 x 520
					390	186	140	196	226	98	410	390	410	155		580 x 280 x 590
					430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
					430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590
					530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
					540	300	218	227	268	165	535	510	572	315		660 x 390 x 690

Overall dimensions SWIVELLING (mm)					Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
					390	184	146	106	144	98	410	390	482	155		580 x 280 x 590
					430	208	162	118	164	97	450	415	540	264		580 x 280 x 590
					530	228	182	154	200	104	535	510	642	315		650 x 290 x 700
					540	300	218	227	268	165	535	510	700	315		660 x 390 x 690

(W: width - D: depth - H: height)



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 330 600 bar	8330.500	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
s. 330 400 bar	8330.501	-	12 m - 1/4" (993.511)	G 3/8" (f)	G 1/4" (m)	15,2 kg	-

* Hose reel capacity	inner hose Ø max. length	1/4" 12 m	5/16" 12 m	3/8" 12 m	1/2" 8 m
----------------------	-----------------------------	--------------	---------------	--------------	-------------



s. 390 600 bar	8390.500	8380.500	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
s. 390 400 bar	8390.501	8380.501	12 m - 1/4" (993.511)	G 3/8" (f)	G 1/4" (m)	17,0 kg	17,5 kg
	8390.502	8380.502	16 m - 1/4" (993.516)	G 3/8" (f)	G 1/4" (m)	18,0 kg	18,5 kg

* Hose reel capacity	inner hose Ø max. length	1/4" 16 m	5/16" 16 m	3/8" 17 m	1/2" 12 m
----------------------	-----------------------------	--------------	---------------	--------------	--------------



s. 430 600 bar	8430.500	8420.500	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
s. 430 400 bar	8430.501	8420.501	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	20,0 kg	20,5 kg
	8430.502	8420.502	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	21,7 kg	22,2 kg
	8430.505	8420.505	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	20,8 kg	21,3 kg
	8430.506	8420.506	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	22,7 kg	23,2 kg

* Hose reel capacity	inner hose Ø max. length	5/16" 12 m	3/8" 15 m
----------------------	-----------------------------	---------------	--------------



s. 430 ABS 600 bar	9430.500	-	without hose *	G 3/8" (f)	G 1/2" (f)	12,5 kg	-
s. 430 ABS 400 bar	9430.501	-	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	16,5 kg	-
	9430.502	-	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	18,2 kg	-
	9430.505	-	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	17,3 kg	-
	9430.506	-	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	19,2 kg	-

* Hose reel capacity	inner hose Ø max. length	5/16" 12 m	3/8" 15 m
----------------------	-----------------------------	---------------	--------------



s. 530 600 bar	8530.500	8520.500	without hose *	G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
s. 530 400 bar	8530.501	8520.501	20 m - 3/8" (995.720)	G 3/8" (f)	G 1/4" (m)	29,6 kg	30,6 kg
	8530.502	8520.502	25 m - 3/8" (995.725)	G 3/8" (f)	G 1/4" (m)	31,6 kg	32,6 kg

* Hose reel capacity	inner hose Ø max. length	3/8" 25 m	1/2" 25 m
----------------------	-----------------------------	--------------	--------------



s. 540 600 bar	8540.500	8550.500	without hose *	G 3/8" (f)	G 1/2" (f)	28,0 kg	33,5 kg
s. 540 400 bar	8540.501	8550.501	30 m - 3/8" (995.730)	G 3/8" (f)	G 1/4" (m)	41,0 kg	46,5 kg

* Hose reel capacity	inner hose Ø max. length	3/8" 30 m	1/2" 30 m	5/8" 30 m
----------------------	-----------------------------	--------------	--------------	--------------



Type of fluid
GREASE


Pressure
400-600 bar

Material
- AISI 304 S. STEEL
- ABS


WITH SPRING




FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 80 °C



In accordance with directive




for ABS versions


* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

ABS

Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	polyurethane	galvanized steel	AISI 304 s. steel
				

Overall dimensions FIXED (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
				390	186	140	196	226	98	410	390	410	155	 580 x 280 x 590
				430	186	140	197	226	97	450	415	456	264	580 x 280 x 590
				430 ABS	186	140	197	226	110	450	425	461	259	580 x 280 x 590
				530	203	153	221	258	104	535	510	558	315	650 x 290 x 700

Overall dimensions SWIVELLING (mm)										Series		A		B		C		D		E		F		G		H		I		Packaging (mm) W x D x H			
										390		184		146		106		144		98		410		390		482		155				580 x 280 x 590	
										430		208		162		118		164		97		450		415		540		264				580 x 280 x 590	
										530		228		182		154		200		104		535		510		642		315				650 x 290 x 700	
(W: width - D: depth - H: height)																																	

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

s. 390 600 bar	8392.500	8382.500	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
--------------------------	-----------------	-----------------	----------------	------------	------------	---------	---------

* Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"
	max. length	15 m	16 m	17 m	12 m

s. 430 600 bar	8432.500	8422.500	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
--------------------------	-----------------	-----------------	----------------	------------	------------	---------	---------

* Hose reel capacity	inner hose ø	5/16"	3/8"
	max. length	12 m	15 m

s. 430 ABS 600 bar	9432.500	-	without hose *	G 3/8" (f)	G 1/2" (f)	12,5 kg	-
s. 430 ABS 400 bar	9432.501	-	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	16,5 kg	-
	9432.502	-	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	18,2 kg	-
	9432.505	-	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	17,3 kg	-
	9432.506	-	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	19,2 kg	-

* Hose reel capacity	inner hose ø	5/16"	3/8"
	max. length	12 m	15 m

s. 530 600 bar	8532.500	8522.500	without hose *	G 3/8" (f)	G 1/2" (m)	21,0 kg	22,0 kg
--------------------------	-----------------	-----------------	----------------	------------	------------	---------	---------

* Hose reel capacity	inner hose ø	3/8"	1/2"
	max. length	25 m	25 m



Type of fluid
DIESEL


Pressure
10-20 bar

Material
- PAINTED STEEL
- ABS

WITH SPRING



FIXED*



- with hose, see page 139
- without hose, max. 100 °C

In accordance with directive




for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses	Connections	Seals	Swivel joint	Central pin
black antistatic rubber	galvanized steel	Viton®	brass	galvanized steel

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H		
	430	186	140	197	226	97	450	415	456	264		580 x 280 x 590			
	430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590			
	530	203	153	221	258	104	535	510	558	315		650 x 290 x 700			
	540	300	218	227	268	165	535	510	572	315		660 x 390 x 690			
	560	488	399	238	272	348	535	510	578	315		670 x 610 x 760			
														(W: width - D: depth - H: height)	

(W: width - D: depth - H: height)



	P/N	Hose supplied	Connection		Weight
			inlet	outlet	
s. 430 20 bar	8430.150	without hose *	G 1" (f)	G 3/4" (f)	17,0 kg
	8430.600	without hose *	G 1/2" (f)	G 1/2" (m)	16,0 kg
s. 430 10 bar	8430.601	10 m - 5/8" (999.810)	G 3/4" (f)	G 3/4" (m)	20,4 kg
	8430.602	8 m - 3/4" (998.808)	G 3/4" (f)	G 3/4" (m)	22,5 kg
* Hose reel capacity		inner hose Ø max. length	1/2" 16 m	5/8" 14 m	3/4" 8 m
s. 430 ABS 20 bar	9430.600	without hose *	G 1/2" (f)	G 1/2" (m)	12,5 kg
s. 430 ABS 10 bar	9430.601	10 m - 5/8" (999.810)	G 3/4" (f)	G 3/4" (m)	16,9 kg
	9430.602	8 m - 3/4" (997.808)	G 3/4" (f)	G 3/4" (m)	19,0 kg
* Hose reel capacity		inner hose Ø max. length	1/2" 16 m	5/8" 14 m	3/4" 8 m
s. 530 20 bar	8530.150	without hose *	G 1" (f)	G 1" (f)	21,0 kg
s. 530 10 bar	8530.603	12 m - 3/4" (997.812)	G 1" (f)	G 3/4" (m)	26,6 kg
	8530.604	8 m - 1" (998.808)	G 1" (f)	G 1" (m)	28,0 kg
* Hose reel capacity		inner hose Ø max. length	5/8" 22 m	3/4" 12 m	1" 8 m
s. 540 20 bar	8540.100	without hose *	G 1" (f)	G 1" (f)	28,0 kg
s. 540 10 bar	8540.601	15 m - 3/4" (997.815)	G 1" (f)	G 3/4" (m)	35,2 kg
	8540.602	20 m - 3/4" (997.820)	G 1" (f)	G 3/4" (m)	37,9 kg
	8540.603	15 m - 1" (998.815)	G 1" (f)	G 1" (m)	39,3 kg
* Hose reel capacity		inner hose Ø max. length	3/4" 22 m	1" 15 m	
s. 560 20 bar	8560.100	without hose *	G 1" (f)	G 1" (f)	48,0 kg
s. 560 10 bar	8560.603	40 m - 3/4" (997.840)	G 1" (f)	G 3/4" (m)	66,4 kg
	8560.604	20 m - 1" (998.820)	G 1" (f)	G 1" (m)	62,6 kg
	8560.605	30 m - 1" (998.830)	G 1" (f)	G 1" (m)	70,4 kg
* Hose reel capacity		inner hose Ø max. length	3/4" 40 m	1" 30 m	



Type of fluid
DIESEL


Pressure
10-20 bar

Material
AISI 304 S. STEEL

WITH SPRING



FIXED*



- with hose, see page 139
- without hose, max. 100 °C






In accordance with directive




* can be rendered swivelling by using the special bracket, see page 81.

Hoses	Connections	Seals	Swivel joint	Central pin
black antistatic rubber	galvanized steel	Viton®	brass	AISI 304 s. steel
				

Overall dimensions (mm)											Series						
			530	540	560	A	B	C	D	E	F	G	H	I			
			203	300	488	153	218	399	221	268	272	258	104	535	510	558	315
											Packaging (mm) W x D x H						
												650 x 290 x 700					
												660 x 390 x 690					
												670 x 610 x 760					

(W: width - D: depth - H: height)





P/N	Hose supplied	Connection		Weight
		inlet	outlet	

s. 530 20 bar	8532.150	without hose *	G 1" (f)	G 1" (f)	21,0 kg
-------------------------	-----------------	----------------	----------	----------	---------

* Hose reel capacity	inner hose ø	5/8"	3/4"	1"
	max. length	22 m	12 m	8 m

s. 540 20 bar	8542.100	without hose *	G 1" (f)	G 1" (f)	28,0 kg
s. 540 10 bar	8542.601	15 m - 3/4" (997.815)	G 1" (f)	G 3/4" (m)	35,2 kg
	8542.602	20 m - 3/4" (997.820)	G 1" (f)	G 3/4" (m)	37,9 kg
	8542.603	15 m - 1" (998.815)	G 1" (f)	G 1" (m)	39,3 kg

* Hose reel capacity	inner hose ø	3/4"	1"
	max. length	22 m	15 m

s. 560 20 bar	8562.100	without hose *	G 1" (f)	G 1" (f)	48,0 kg
s. 560 10 bar	8562.603	40 m - 3/4" (997.840)	G 1" (f)	G 3/4" (m)	66,4 kg
	8562.604	20 m - 1" (998.820)	G 1" (f)	G 1" (m)	62,6 kg
	8562.605	30 m - 1" (998.830)	G 1" (f)	G 1" (m)	70,4 kg

* Hose reel capacity	inner hose ø	3/4"	1"
	max. length	40 m	30 m



Type of fluid
AdBlue®


Pressure
10-100 bar

Material
- **PAINTED STEEL**
- **AISI 304 S. STEEL**
- **ABS**


WITH SPRING



FIXED*



- with hose, see page 139
- without hose, max. 130 °C



In accordance with directive




for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

Painted
ABS

Hoses	Connections	Seals	Swivel joint	Central pin
Antistatic EPDM	AISI 304 stainless steel	Viton®	AISI 304 stainless steel AISI 316 stainless steel	AISI 304 stainless steel AISI 316 stainless steel

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
	436 painted	337	302	160	203	150	450	415	456	264		580 x 280 x 590	
	436 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590	
	437 s. steel	186	140	197	226	97	450	415	456	264		580 x 280 x 590	
	437 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590	
	537	203	153	221	258	104	535	510	558	315		650 x 290 x 700	
(W: width - D: depth - H: height)													

(W: width - D: depth - H: height)

See specific catalogue





P/N	Central pin swivel joint	Hose supplied	Connection		Weight
			inlet	outlet	

PAINTED STEEL

s. 436 painted 100 bar	8436.200	AISI 316 stainless steel	without hose *	G 1" (f)	G 3/4" (f)	20,0 kg
	8436.250	AISI 304 stainless steel	without hose *	G 1" (f)	G 3/4" (f)	22,0 kg
s. 436 painted 10 bar	8436.251	AISI 304 stainless steel	10 m - 19 x 27 mm (987.210)	G 3/4" (f)	G 3/4" (m)	29,4 kg
	8436.252	AISI 304 stainless steel	15 m - 19 x 27 mm (987.215)	G 3/4" (f)	G 3/4" (m)	32,4 kg

* Hose reel capacity	inner hose Ø	1/2"	5/8"	3/4"
	max. length	16 m	14 m	8 m

s. 436 ABS 100 bar	9436.200	AISI 304 stainless steel	without hose *	G 1/2" (f)	G 1/2" (m)	15,8 kg
s. 436 ABS 10 bar	9436.201	AISI 304 stainless steel	8 m - 19 x 27 mm (987.208)	G 3/4" (f)	G 3/4" (m)	20,7 kg

* Hose reel capacity	inner hose Ø	1/2"	5/8"	3/4"
	max. length	16 m	14 m	8 m

AISI 304 STAINLESS STEEL

s. 437 s. steel 100 bar	8434.250	AISI 304 stainless steel	without hose *	G 1" (f)	G 3/4" (f)	17,0 kg
-------------------------------	----------	-----------------------------	----------------	----------	------------	---------

* Hose reel capacity	inner hose Ø	1/2"	5/8"	3/4"
	max. length	16 m	14 m	8 m

s. 437 ABS 100 bar	9437.200	AISI 304 stainless steel	without hose *	G 1/2" (f)	G 1/2" (m)	15,8 kg
s. 437 ABS 10 bar	9437.201	AISI 304 stainless steel	8 m - 19 x 27 mm (987.208)	G 3/4" (f)	G 3/4" (m)	20,7 kg

* Hose reel capacity	inner hose Ø	1/2"	5/8"	3/4"
	max. length	16 m	14 m	8 m

s. 537 s. steel 100 bar	8537.200	AISI 316 stainless steel	without hose *	G 1" (f)	G 1" (f)	22,5 kg
	8534.250	AISI 304 stainless steel	without hose *	G 1" (f)	G 1" (f)	22,5 kg
s. 537 s. steel 10 bar	8537.251	AISI 304 stainless steel	10 m - 19 x 27 mm (987.210)	G 3/4" (f)	G 3/4" (m)	27,0 kg
	8537.252	AISI 304 stainless steel	15 m - 19 x 27 mm (987.215)	G 3/4" (f)	G 3/4" (m)	31,0 kg

* Hose reel capacity	inner hose Ø	5/8"	3/4"	1"
	max. length	22 m	12 m	8 m

Prepared with outlet connection for Ø 3/4" hoses



Type of fluid
LPG-METHANE


Pressure
20 bar

Material
PAINTED STEEL

WITH SPRING



FIXED*



In accordance with directive




* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS

S. 330 - 390

Hoses	Connections	Seals	Swivel joint	Central pin
PVC/NBR orange rubber EN ISO 3821	brass	Viton®	brass	galvanized steel
				

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	330	186	140	196	226	98	390	350	365	155		510 x 260 x 520		
	390	186	140	196	226	98	410	390	410	155		580 x 280 x 590		
	430	186	140	197	226	97	450	415	456	264		580 x 280 x 590		
	530	203	153	221	258	104	535	510	558	315		650 x 290 x 700		
	540	300	218	227	268	165	535	510	572	315		660 x 390 x 690		
(W: width - D: depth - H: height)														

(W: width - D: depth - H: height)



P/N	Hose supplied	Connection		Weight
		inlet	outlet	
s. 330	8330.800	without hose *		12,5 kg
	8330.801	8 m - 8 x 15 mm (974.1008)	G 3/8" (f) LH	14,5 kg
	8330.802	10 m - 10 x 17 mm (975.1010)	G 3/8" (f) LH	15,3 kg
* Hose reel capacity		inner hose Ø max. length	1/4" 20 m 5/16" 20 m 3/8" 18 m 1/2" 15 m	
s. 390	8390.800	without hose *		13,5 kg
	8390.801	15 m - 8 x 15 mm (974.1015)	G 3/8" (f) LH	16,6 kg
	8390.802	15 m - 10 x 17 mm (975.1015)	G 3/8" (f) LH	17,3 kg
* Hose reel capacity		inner hose Ø max. length	1/4" 20 m 5/16" 20 m 3/8" 18 m 1/2" 15 m	
s. 430	8430.800	without hose *		18,5 kg
	8430.802	20 m - 8 x 15 mm (974.1020)	G 3/8" (f) LH	22,3 kg
	8430.804	18 m - 10 x 17 mm (975.1018)	G 3/8" (f) LH	23,0 kg
* Hose reel capacity		inner hose Ø max. length	5/16" 20 m 3/8" 20 m 1/2" 16 m 5/8" 14 m	
s. 530	8530.800	without hose *		21,0 kg
	8530.802	28 m - 8 x 15 mm (974.1028)	G 3/8" (f) LH	26,3 kg
	8530.804	27 m - 10 x 17 mm (975.1027)	G 3/8" (f) LH	28,0 kg
* Hose reel capacity		inner hose Ø max. length	3/8" 25 m 1/2" 25 m 5/8" 22 m	
s. 540	8540.800	without hose *		28,0 kg
	8540.802	30 m - 10 x 17 mm (975.1030)	G 3/8" (f) LH	35,0 kg
* Hose reel capacity		inner hose Ø max. length	3/8" 30 m 1/2" 30 m 5/8" 30 m	

LH (Left hand): counter-clockwise turning direction



Hose reel
WELDING

Pressure
20 bar

Material
PAINTED STEEL

WITH SPRING



FIXED*



In accordance with directive



* can be rendered swivelling by using the special bracket, see page 81.

Hoses	Connections	Seals	Swivel joint	Central pin
SBR/EPDM for oxy-acetylene EN ISO 3821	brass	Viton®	brass	galvanized steel

Overall dimensions (mm)				Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
				430	186	140	197	226	97	450	415	456	264	580 x 280 x 590
				530	203	153	221	258	104	535	510	558	315	650 x 290 x 700
				540	300	218	227	268	165	535	510	572	315	660 x 390 x 690

(W: width - D: depth - H: height)



P/N	Hose supplied	Connection		Weight
		inlet	outlet	
s. 430	8430.700	without hose *		18,5 kg
	8430.701	13 m - 2 x 6 mm - (2 x 1/4") (973.913)	G 3/8" (f)	23,7 kg
	8430.702	12 m - 2 x 8 mm - (2 x 5/16") (974.912)	G 3/8" (f)	23,4 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 13 m 2 x 5/16" 12 m 2 x 3/8" 10 m	
s. 530	8530.700	without hose *		23,2 kg
	8530.701	17 m - 2 x 6 mm - (2 x 1/4") (973.917)	G 3/8" (f)	29,7 kg
	8530.702	20 m - 2 x 6 mm - (2 x 1/4") (973.920)	G 3/8" (f)	30,9 kg
	8530.703	15 m - 2 x 8 mm - (2 x 5/16") (974.915)	G 3/8" (f)	29,4 kg
	8530.704	20 m - 2 x 8 mm - (2 x 5/16") (974.920)	G 3/8" (f)	31,7 kg
	8530.705	15 m - 2 x 9 mm - (2 x 3/8") (975.915)	G 3/8" (f)	31,5 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 22 m 2 x 5/16" 20 m 2 x 3/8" 15 m	
s. 540	8540.700	without hose *		30,0 kg
	8540.701	25 m - 2 x 6 mm (2 x 1/4") (973.925)	G 3/8" (f)	38,8 kg
	8540.702	30 m - 2 x 6 mm (2x1/4") (973.930)	G 3/8" (f)	39,2 kg
	8540.704	25 m - 2 x 8 mm (2 x 5/16") (974.925)	G 3/8" (f)	40,2 kg
	8540.705	30 m - 2 x 8 mm (2 x 5/16") (974.930)	G 3/8" (f)	42,2 kg
	8540.707	20 m - 2 x 9 mm (2 x 3/8") (975.920)	G 3/8" (f)	40,0 kg
	8540.709	27 m - 2 x 9 mm (2 x 3/8") (975.927)	G 3/8" (f)	42,6 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m 2 x 5/16" 35 m 2 x 3/8" 27 m	



Hose reel
**DOUBLE INLET AND
DOUBLE OUTLET**

Pressure
**20-200
400-700 bar**

Material
**PAINTED
STEEL**

WITH SPRING



FIXED*




In accordance with directive



* can be rendered swivelling by using the special bracket, see page 81.

	Seals	Swivel joint	Central pin
AIR-WATER 20 bar	Viton®	brass	galvanized steel
OIL-WATER 200 bar	Viton®	AISI 304 s. steel	galvanized steel
OIL-PAINTS 200 bar	polyurethane	galvanized steel	galvanized steel
OIL 400 bar	polyurethane	galvanized steel	galvanized steel
OIL-WATER 700 bar	Viton® - Teflon®	AISI 304 s. steel	galvanized steel
			

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
			430	186	140	197	226	97	450	415	456	264		580 x 280 x 590
			530	203	153	221	258	104	535	510	558	315		650 x 290 x 700
			540	300	218	227	268	165	535	510	572	315		660 x 390 x 690

(W: width - D: depth - H: height)

Twin hose reels can be used for all applications that need
to **simultaneously supply two fluids** or to **recirculate a single fluid**.



s. 430



s. 530



s. 540

P/N	Hose supplied	Connection		Weight
		inlet	outlet	

AIR-WATER 20 bar

s. 430	8430.1000	without hose *			G 1/2" (f)	G 3/8" (m)	18,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 13 m	2 x 5/16" 12 m	2 x 3/8" 10 m		
s. 530	8530.1000	without hose *			G 1/2" (f)	G 3/8" (m)	25,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 22 m	2 x 5/16" 20 m	2 x 3/8" 15 m		
s. 540	8540.1000	without hose *			G 1/2" (f)	G 3/8" (m)	30,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m	2 x 5/16" 35 m	2 x 3/8" 25 m		

OIL-WATER 200 bar

s. 430	8430.3000	without hose *			G 3/8" (f)	G 3/8" (m)	18,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 13 m	2 x 5/16" 12 m	2 x 3/8" 10 m		
s. 530	8530.3000	without hose *			G 3/8" (f)	G 3/8" (m)	25,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 22 m	2 x 5/16" 20 m	2 x 3/8" 15 m		
s. 540	8540.3000	without hose *			G 3/8" (f)	G 3/8" (m)	30,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m	2 x 5/16" 35 m	2 x 3/8" 27 m		

OIL-PAINTS 200 bar

s. 430	8430.4000	without hose *			G 1/2" (f)	G 3/8" (m)	18,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 13 m	2 x 5/16" 12 m	2 x 3/8" 10 m		
s. 530	8530.4000	without hose *			G 1/2" (f)	G 3/8" (m)	25,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 22 m	2 x 5/16" 20 m	2 x 3/8" 15 m		
s. 540	8540.4000	without hose *			G 1/2" (f)	G 3/8" (m)	30,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m	2 x 5/16" 35 m	2 x 3/8" 27 m		

OIL 400 bar

s. 430	8430.5000	without hose *			G 3/8" (f)	G 3/8" (m)	18,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 5/16" 12 m	2 x 3/8" 10 m			
s. 530	8530.5000	without hose *			G 3/8" (f)	G 3/8" (m)	25,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 3/8" 15 m	2 x 5/16" 20 m			
s. 540	8540.5000	without hose *			G 3/8" (f)	G 3/8" (m)	30,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m	2 x 5/16" 35 m	2 x 3/8" 27 m		

OIL-WATER 700 bar

s. 430	8430.5500	without hose *			G 3/8" (f)	G 3/8" (m)	18,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 5/16" 12 m	2 x 3/8" 10 m			
s. 530	8530.5500	without hose *			G 3/8" (f)	G 3/8" (m)	25,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 5/16" 20 m	2 x 3/8" 15 m			
s. 540	8540.5500	without hose *			G 3/8" (f)	G 3/8" (m)	30,0 kg
* Hose reel capacity		inner hose Ø max. length	2 x 1/4" 37 m	2 x 5/16" 35 m	2 x 3/8" 27 m		




**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED **ENCLOSED HOSE REELS**




EXAMPLES OF **USE**



GREASING EXCAVATORS ON ASSEMBLY LINES

IN-SHOP MAINTENANCE OPERATIONS



AUTOMOTIVE

LUBE TRUCKS
AND INDUSTRIAL
VEHICLES

MINING
INDUSTRY

BUILDING
AND ROAD
CONSTRUCTION

RAILWAY
TRANSPORT

...and much more



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED **ENCLOSED HOSE REELS**



STRENGTH POINTS

- Repeated spring stress-tests guarantees decades of life and efficiency.
- All models comply with the ATEX directive for use in environments with potentially explosive atmospheres.
- Hose guide with rollers on 4 sides, horizontal and vertical, standard on all models, designed to extend average hose life.
- Hose stop available for all standard models, even those supplied without hose.
- The spring force is both constant and adjustable. Thus use can be fine-tuned to the specific needs of each application.
- All sliding parts, such as bushing and the rack, are made of special technopolymers tested for long-term use.

TECHNICAL CHARACTERISTICS

Visit our
website



FIXING BRACKET

Has 4 slotted holes for safe, easy installation.

PAWL

Easy to remove for maintenance or when the work requires free sliding.

STOP RACK

Makes it possible to lock the hose around every 0,5 m.

SPRING

Tested to withstand over 20000 work cycles.

HOSE GUIDE

SWIVEL JOINT


Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.

DRUM SUPPORT BUSHING

Made of self-lubricating technopolymer with excellent corrosion resistance.

CENTRAL PIN

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.





Hose reel
ENCLOSED


Pressure
**20-150
400-600 bar**

Material
**- PAINTED STEEL
- ABS**


WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose:
with brass swivel joint
max. 100 °C
with galvanized steel
swivel joint max. 80 °C



In accordance with directive

CE II 2 GD

CE II 3 GD

for ABS and enclosed
models 20 bar

* can be rendered swivelling by using the
special bracket, see page 81.

Enclosed hose reels are used for the following fluids:

	Hoses	Connections	Seals	Swivel joint	Central pin
AIR-WATER 20 bar	black rubber	galvanized steel	Viton®	brass	galvanized steel
OIL AND SIMILAR 150 bar	black rubber	galvanized steel	polyurethane	galvanized steel	galvanized steel
FOR SUCTION OF OIL AND SIMILAR	black rubber	galvanized steel	Viton®	brass	galvanized steel
GREASE 400-600 bar	black rubber	galvanized steel	polyurethane	galvanized steel	galvanized steel

COVER COLOURS

Painted

Overall dimensions (mm)		Series 450	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
	FIXED	217	177	180	236	217	140	485	495	485		620 x 290 x 620
	SWIVEL.	208	162	118	164	208	140	485	575	485		620 x 290 x 620

(W: width - D: depth - H: height)



P/N		Hose supplied	Connection		Weight	
fixed	swivelling		inlet	outlet	fixed	swivelling

AIR-WATER 20 bar

s. 450	8450.100	8440.100	without hose *	G 1/2" (f)	G 1/2" (f)	22,2 kg	23,0 kg
	8450.101	8440.101	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	24,7 kg	25,5 kg
	8450.102	8440.102	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	25,4 kg	26,2 kg
	8450.103	8440.103	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	25,2 kg	26,0 kg
	8450.104	8440.104	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	26,1 kg	26,9 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 450 ABS drum	9450.100	-	without hose *	G 1/2" (f)	G 1/2" (f)	19,5 kg	-
	9450.101	-	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	22,0 kg	-
	9450.102	-	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	22,7 kg	-
	9450.103	-	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	22,5 kg	-
	9450.104	-	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	23,4 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

OIL AND SIMILAR 150 bar

s. 450	8450.400	8440.400	without hose *	G 1/2" (f)	G 1/2" (f)	22,2 kg	23,0 kg
	8450.401	8440.401	10 m - 1/2" (996.310)	G 1/2" (f)	G 1/2" (m)	26,4 kg	27,2 kg
	8450.402	8440.402	15 m - 1/2" (996.315)	G 1/2" (f)	G 1/2" (m)	28,4 kg	29,2 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

s. 450 ABS drum	9450.400	-	without hose *	G 1/2" (f)	G 1/2" (f)	19,5 kg	-
	9450.401	-	10 m - 1/2" (996.310)	G 1/2" (f)	G 1/2" (m)	23,7 kg	-
	9450.402	-	15 m - 1/2" (996.315)	G 1/2" (f)	G 1/2" (m)	25,7 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m

FOR SUCTION OF OIL AND SIMILAR

s. 450 for suction	8450.401/AS	8440.401/AS	10 m - 1/2" (996.310)	G 1/2" (f)	G 1/2" (m)	27,0 kg	27,8 kg
-----------------------	-------------	-------------	-----------------------	------------	------------	---------	---------

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	10 m	10 m	10 m

GREASE 400-600 bar

s. 450 600 bar	8450.500	8440.500	without hose *	G 3/8" (f)	G 1/2" (f)	22,2 kg	23,0 kg
s. 450 400 bar	8450.501	8440.501	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	25,9 kg	26,7 kg
	8450.502	8440.502	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	27,6 kg	28,4 kg
	8450.505	8440.505	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	26,8 kg	27,6 kg
	8450.506	8440.506	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	28,6 kg	29,4 kg

* Hose reel capacity	inner hose Ø	5/16"	3/8"
	max. length	12 m	15 m

s. 450 ABS drum 600 bar	9450.500	-	without hose *	G 3/8" (f)	G 1/2" (f)	19,5 kg	-
s. 450 ABS drum 400 bar	9450.501	-	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	23,2 kg	-
	9450.502	-	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	24,9 kg	-
	9450.505	-	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	24,1 kg	-
	9450.506	-	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	25,9 kg	-

* Hose reel capacity	inner hose Ø	5/16"	3/8"	1/2"
	max. length	20 m	20 m	16 m




**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED HOSE REELS WITH POLYURETHANE HOSE




EXAMPLES OF **USE**



RESTORE OPERATING PRESSURE IN SERVICE STATIONS

**POWERING PNEUMATIC EQUIPMENT
AT MANUFACTURING SITES**



AUTOMOTIVE

CLEANING

SHIPPING AND
OFFSHORE

MANUFACTUR-
ING INDUSTRY

BUILDING
AND ROAD
CONSTRUCTION

...and much more



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED HOSE REELS WITH POLYURETHANE HOSE

✓ STRENGTH POINTS

- Repeated spring stress-tests guarantees decades of life and efficiency.
- All models comply with the ATEX directive for use in environments with potentially explosive atmospheres.
- Hose stop available for all standard models, even those supplied without hose.
- The spring force is both constant and adjustable. Thus use can be fine-tuned to the specific needs of each application.
- All sliding parts, such as bushing and the rack, are made of special technopolymers tested for long-term use.
- Light, resistant polyurethane hose with metal spiral tips to safeguard durability and integrity.

TECHNICAL CHARACTERISTICS

Visit our
website



FIXING BRACKET

Has 4 slotted holes for safe, easy installation.

PAWL

Easy to remove for maintenance or when the work requires free sliding.

STOP RACK

Makes it possible to lock the hose around every 0,5 m.

SPRING

Tested to withstand over 20000 work cycles.

MULTI POSITION ARMS

Hose outlet position can be changed manually by modifying the installation of the arms.

HOSE GUIDE

Designed with ample width and roller arrangement to reduce wear on the hose.

DRUM SUPPORT BUSHING

Made of self-lubricating technopolymer with excellent wear and corrosion resistance.

CENTRAL PIN

Designed to minimise load losses.

SWIVEL JOINT

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.



Type of fluid
AIR-WATER


Pressure
20 bar

Material
- PAINTED STEEL
- ABS

WITH SPRING



FIXED*



Max. temperature 70 °C



In accordance with directive



* can be rendered swivelling
(except for s. 250) by using the
special bracket, see page 81.

	Hoses	Connections	Seals	Swivel joint	Central pin
S. 250	Atoxic polyurethane	brass	Viton®	Delrin® - brass	Delrin®
S. 290-330-390				brass	nylon PA6
S. 430				brass	galvanized steel

DRUM COLOURS

Painted    

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
			250	186	140	196	225	90	-	255	282	110	 330 x 200 x 300
			290	186	140	196	226	98	330	300	339	135	470 x 260 x 490
			330	186	140	196	226	98	390	350	365	155	510 x 260 x 520
			390	186	140	196	226	98	410	390	410	155	580 x 280 x 590
			430	186	140	197	226	97	450	415	456	264	580 x 280 x 590
													(W: width - D: depth - H: height)



P/N	Hose supplied	Connection		Weight
		inlet	outlet	

s. 250 ABS	HOSE REEL FOR SERVICE COLUMNS WITH STEEL BRACKET AND ABS DRUM				
	92438.101	12 m - 8 x 12 mm (971.112)	G 3/8" (m)	G 1/4" (m)	7,6 kg
	92438.102	10 m - 10 x 14,5 mm (972.110)	G 3/8" (m)	G 3/8" (m)	7,8 kg

Hose guide available as accessory, see page 83

s. 290	8288.100	without hose *	G 3/8" (m)	G 3/8" (f)	9,5 kg
	8288.102	13 m - 10 x 14,5 mm (972.113)	G 3/8" (m)	G 3/8" (m)	11,3 kg
	8288.103	15 m - 8 x 12 mm (971.115)	G 3/8" (m)	G 1/4" (m)	11,0 kg
	8288.104	10 m - 6 x 10 mm (971.010)	G 3/8" (m)	G 1/4" (m)	10,5 kg
	8288.105	15 m - 6 x 10 mm (971.015)	G 3/8" (m)	G 1/4" (m)	10,9 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5
	max. length	16 m	14 m

s. 330	8328.100	without hose *	G 3/8" (m)	G 3/8" (f)	10,1 kg
	8328.102	15 m - 10 x 14,5 mm (972.115)	G 3/8" (m)	G 3/8" (m)	12,1 kg
	8328.103	18 m - 8 x 12 mm (971.118)	G 3/8" (m)	G 1/4" (m)	11,8 kg
	8328.104	8 m - 13 x 19 mm (976.108)	G 1/2" (m)	G 1/2" (m)	12,0 kg
	8328.105	12 m - 13 x 19 mm (976.112)	G 1/2" (m)	G 1/2" (m)	15,9 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5	13 x 19
	max. length	18 m	16 m	12 m

s. 390	8378.100	without hose *	G 3/8" (m)	G 3/8" (f)	13,5 kg
	8378.102	20 m - 10 x 14,5 mm (972.120)	G 3/8" (m)	G 3/8" (m)	18,2 kg
	8378.103	20 m - 8 x 12 mm (971.120)	G 3/8" (m)	G 1/4" (m)	15,4 kg
	8378.104	10 m - 13 x 19 mm (976.110)	G 1/2" (m)	G 1/2" (m)	16,6 kg
	8378.105	15 m - 13 x 19 mm (976.114)	G 1/2" (m)	G 1/2" (m)	17,0 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5	13 x 19
	max. length	18 m	16 m	12 m

s. 430	8430.100	without hose *	G 1/2" (f)	G 1/2" (f)	15,2 kg
	8438.101	10 m - 13 x 19 mm (976.111)	G 1/2" (f)	G 1/2" (m)	18,3 kg
	8438.102	15 m - 13 x 19 mm (976.115)	G 1/2" (f)	G 1/2" (m)	18,9 kg

* Hose reel capacity	inner hose Ø	10 x 14,5	13 x 19	16 x 27
	max. length	20 m	16 m	14 m



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED HOSE REELS WITH TECHNOPOLYMER COVER AND POLYURETHANE HOSE




STRENGTH POINTS

- Comes standard with polyurethane hose that can be used with aqueous or detergent solutions at up to 70 °C.
- Hose guide with rollers, horizontal and vertical, on 4 sides, designed to extend average hose life, as standard on all models.
- The hose reel comes with a 1,5 m section of hose for connection to the fixed system.
- The standard swivelling bracket, with slotted fixing holes, has special seals that act as a clutch. The bracket can also be locked in the upright position or rotated 90°.
- An optional rewind clutch is available, useful to protect against accidental, uncontrolled rewinding of the hose.
- An optional bayonet bracket, which lets you quickly move the hose reel around the various workstations, is also available.

TECHNICAL CHARACTERISTICS

Visit our
website



PAWL

Easy to remove for maintenance or when the work requires free sliding.

REWINDING CLUTCH

Optional: lets you rewind the drum at a safe speed.

SPRING

Tested to withstand over 20000 work cycles.

SIDE CLUTCH

HOSE GUIDE

HOSE

Fit with hose stop and metal spiral tips to reinforce the hose structure.

CONNECTIONS AND CENTRAL PIN

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.

STOP RACK

Makes it possible to lock the hose every 0,5 m.

FIXING BRACKET

Can be rotated up to 90° per side and has 2 slotted holes for safe, easy installation.

ENTRY JOINT

Can be oriented in 8 different positions, evenly spaced by 45°, to facilitate connection to the fixed system.

BAYONET BRACKET

Lets you quickly move the hose reel around the various workstations.




Type of fluid
AIR-WATER


Pressure
20 bar

Material
TECHNOPOLYMER

WITH SPRING



SWIVELLING



Max. temperature 70 °C



COVER COLOURS


ABS s. 260

Polypropylene s. 280




Hoses	Connections	Seals	Swivel joint	Central pin
Atoxic polyurethane	brass	Viton®	brass	galvanized steel
			Delrin®	Delrin®

Overall dimensions (mm) with bayonet hooking s. 260




Packaging (mm)
W 470 x D 260 x H 490

Overall dimensions (mm) with bayonet hooking s. 280




Packaging (mm)
W 470 x D 260 x H 490

Overall dimensions (mm) without bayonet hooking s. 260



Packaging (mm)
W 470 x D 260 x H 490

Overall dimensions (mm) without bayonet hooking s. 280



Packaging (mm)
L 470 x P 260 x H 490

(W: width - D: depth - H: height)



P/N	Hose supplied	Connection		Weight
		inlet	outlet	

WITH SWIVELLING WALL MOUNTED BRACKET WITH BAYONET HOOKING

s. 260	89010	11 m - 8 x 12 mm (971.111)	G 1/4" (m)	G 1/4" (m)	6,5 kg
	89011	11 m - 6 x 10 mm (971.011)	G 1/4" (m)	G 1/4" (m)	7,3 kg

WITH SWIVELLING WALL MOUNTED BRACKET

s. 260	89109	11 m - 8 x 12 mm (971.111)	G 1/4" (m)	G 1/4" (m)	5,8 kg
	89110	11 m - 6 x 10 mm (971.011)	G 1/4" (m)	G 1/4" (m)	5,6 kg

WITH SWIVELLING WALL MOUNTED BRACKET

s. 280	92808.101	10 m - 8 x 12 mm (971.110)	G 3/8" (m)	G 1/4" (m)	8,2 kg
	92808.102	14 m - 8 x 12 mm (971.114)	G 3/8" (m)	G 1/4" (m)	8,5 kg
	92808.105	8+1 m - 10 x 14,5 mm (972.109)	G 3/8" (m)	G 3/8" (m)	8,6 kg

WITH SWIVELLING WALL MOUNTED BRACKET AND SPEED CONTROL

s. 280	92848.101	10 m - 8 x 12 mm (971.110)	G 3/8" (m)	G 1/4" (m)	9,0 kg
	92848.102	14 m - 8 x 12 mm (971.114)	G 3/8" (m)	G 1/4" (m)	9,3 kg
	92848.105	8+1 m - 10 x 14,5 mm (972.109)	G 3/8" (m)	G 3/8" (m)	9,4 kg

WITH SWIVELLING WALL MOUNTED BRACKET WITH BAYONET HOOKING

s. 280	92818.101	10 m - 8 x 12 mm (971.110)	G 3/8" (m)	G 1/4" (m)	8,8 kg
	92818.102	14 m - 8 x 12 mm (971.114)	G 3/8" (m)	G 1/4" (m)	9,1 kg
	92818.105	8+1 m - 10 x 14,5 mm (972.109)	G 3/8" (m)	G 3/8" (m)	9,2 kg

WITH SWIVELLING WALL MOUNTED BRACKET WITH BAYONET AND SPEED CONTROL

s. 280	92858.101	10 m - 8 x 12 mm (971.110)	G 3/8" (m)	G 1/4" (m)	9,6 kg
	92858.102	14 m - 8 x 12 mm (971.114)	G 3/8" (m)	G 1/4" (m)	9,9 kg
	92858.105	8+1 m - 10 x 14,5 mm (972.109)	G 3/8" (m)	G 3/8" (m)	10,0 kg



ADVANCED FLUID
MANAGEMENT SOLUTIONS

SPRING OPERATED HOSE REELS IN STEEL WITH POLYURETHANE HOSE



STRENGTH POINTS

- Comes standard with polyurethane hose that can be used with aqueous or detergent solutions at up to 70 °C.
- In the versions with stainless steel cover, the hose fittings, spiral protections and swivel joint are supplied as standard in AISI 304 stainless steel.
- All models comply with the ATEX directive for use in environments with potentially explosive atmospheres.
- Hose guide with rollers, horizontal and vertical, on 4 sides, designed to extend average hose life, as standard on all models.
- The hose reel comes with a 1,5 m section of hose for connection to the fixed system.
- The standard swivelling bracket, with slotted fixing holes, has special seals that act as a clutch. The bracket can also be locked in the upright position or rotated 90°.

TECHNICAL CHARACTERISTICS

Visit our
website




SPRING

Tested to withstand over 20000 work cycles.

PAWL

ENTRY SWIVEL JOINT

Can be oriented in 8 different positions, evenly spaced by 45°, to facilitate connection to the fixed system.



BAYONET BRACKET

Lets you quickly move the hose reel around the various workstations.

HOSE GUIDE

HOSE

Fit with hose stop and metal spiral tips to reinforce the hose structure.

CENTRAL PIN


Designed to minimise load losses.

STOP RACK

Makes it possible to lock the hose around every 0,5 m.

FIXING BRACKET

Can be rotated up to 90° per side and has 2 slotted holes for safe, easy installation.






Type of fluid
AIR-WATER

Pressure
20 bar

Material
- PAINTED STEEL
- AISI 304 S. STEEL

WITH SPRING




In accordance with directive



COVER COLOURS

Painted

	Hoses	Connections	Seals	Swivel joint	Central pin
Painted steel	Atoxic polyurethane	brass	Viton®	Delrin® - brass	Delrin®
AISI 304 stainless steel	Atoxic polyurethane	AISI 304 stainless steel	Viton®	Delrin® - AISI 304 stainless steel	Delrin®
					

Overall dimensions (mm)											Series	A	B	C	D	E	F	G	H	I	L	M	N	Packaging (mm) W x D x H
											250	40	319	210	130	20	20	173	124	62	281	338	230	 370 x 200 x 370
											300	40	319	210	130	20	20	173	124	62	333	416	308	 385 x 200 x 415

(W: width - D: depth - H: height)



P/N	Hose supplied	Connection		Weight
		inlet	outlet	

PAINTED STEEL

s. 250	92608.101	12 m - 8 x 12 mm (971.112)	G 3/8" (m)	G 1/4" (m)	7,0 kg
	92608.102	10 m - 10 x 14,5 mm (972.110)	G 3/8" (m)	G 3/8" (m)	7,3 kg

s. 300	93108.102	12 m - 8 x 12 mm (971.112)	G 3/8" (m)	G 1/4" (m)	8,6 kg
	93108.103	15 m - 8 x 12 mm (971.116)	G 3/8" (m)	G 1/4" (m)	8,8 kg
	93108.104	20 m - 8 x 12 mm (971.121)	G 3/8" (m)	G 1/4" (m)	9,0 kg
	93108.105	12 m - 10 x 14,5 mm (972.112)	G 3/8" (m)	G 3/8" (m)	8,9 kg
	93108.106	15 m - 10 x 14,5 mm (972.116)	G 3/8" (m)	G 3/8" (m)	9,3 kg

AISI 304 STAINLESS STEEL

s. 250	92708.101	12 m - 8 x 12 mm (981.112)	G 3/8" (m)	G 1/4" (m)	7,0 kg
	92708.102	10 m - 10 x 14,5 mm (982.110)	G 3/8" (m)	G 3/8" (m)	7,3 kg

s. 300	93208.102	12 m - 8 x 12 mm (981.112)	G 3/8" (m)	G 1/4" (m)	8,6 kg
	93208.103	15 m - 8 x 12 mm (981.116)	G 3/8" (m)	G 1/4" (m)	8,8 kg
	93208.104	20 m - 8 x 12 mm (981.121)	G 3/8" (m)	G 1/4" (m)	9,0 kg
	93208.105	12 m - 10 x 14,5 mm (982.112)	G 3/8" (m)	G 3/8" (m)	8,9 kg
	93208.106	15 m - 10 x 14,5 mm (982.116)	G 3/8" (m)	G 3/8" (m)	9,3 kg



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

Automatic rewinding





Discover the RAASM rewinding brake
for spring-loaded hose reels...
Contact our offices!



ACCESSORIES - AUTOMATIC HOSE GUIDE IN PAINTED STEEL

The new automatic hose guide guarantees correct arrangement of the hose on the drum, thus preventing haphazard rewinding.

✓ STRENGTH POINTS

- Designed to move independently while rewinding the hose.
- Equipped with rollers, horizontal and vertical, that can be adjusted to the hose being used.
- Easy to assemble on both new hose reels and on equipment already in use.



⚠ The hose reel equipped with automatic hose guide is not suitable for installation in potentially explosive atmosphere.

P/N 77/44312

Automatic hose guide in painted steel for hose reel s. 430, hoses up to 1/2".

P/N 77/45312

Automatic hose guide in painted steel for hose reel s. 530, hoses up to 1/2".

P/N 77/45401

Automatic hose guide in painted steel for hose reel s. 540, hoses from 3/4" to 1".

P/N 77/45412



Automatic hose guide in painted steel for hose reel s. 540, hoses up to 1/2".

P/N 77/45601

Automatic hose guide in painted steel for hose reel s. 560, hoses from 3/4" to 1".

P/N 77/45612

Automatic hose guide in painted steel for hose reel s. 560, hoses up to 1/2".



Series	A	B	C	D	E	F
430	314	283	134	377	209	172
530	371	341	136	448	223	187
540	371	341	136	448	288	252
560	371	341	136	448	472	436



ACCESSORIES - AUTOMATIC HOSE GUIDE IN AISI 316 STAINLESS STEEL

The new automatic hose guide guarantees correct arrangement of the hose on the drum, thus preventing haphazard rewinding.

✓ STRENGTH POINTS

- Designed to move independently while rewinding the hose.
- Equipped with rollers, horizontal and vertical, that can be adjusted to the hose being used.
- Easy to assemble on both new hose reels and on equipment already in use.



⚠ The hose reel equipped with automatic hose guide is not suitable for installation in potentially explosive atmosphere.

P/N 79/44312

Automatic hose guide in AISI 316 stainless steel for hose reel s. 430, hoses up to 1/2".

P/N 79/45312

Automatic hose guide in AISI 316 stainless steel for hose reel s. 530, hoses up to 1/2".

P/N 79/45401

Automatic hose guide in AISI 316 stainless steel for hose reel s. 540, hoses from 3/4" to 1".

P/N 79/45412



Automatic hose guide in AISI 316 stainless steel for hose reel s. 540, hoses up to 1/2".

P/N 79/45601

Automatic hose guide in AISI 316 stainless steel for hose reel s. 560, hoses from 3/4" to 1".

P/N 79/45612

Automatic hose guide in AISI 316 stainless steel for hose reel s. 560, hoses up to 1/2".




Series	A	B	C	D	E	F
430	314	283	134	377	209	172
530	371	341	136	448	223	187
540	371	341	136	448	288	252
560	371	341	136	448	472	436



ACCESSORIES FOR SPRING OPERATED HOSE REEL

A **quick coupling support**, which facilitates coupling of individual hose reels and optimises installation in series, i.e. several hose reels set side-by-side, is available upon request.



P/N 843001



P/N 843002

P/N 843001


Fixed support in steel

for fixed painted steel hose reels
series 290 - 330 - 390 - 430.

P/N 843002

Fixed support in AISI 304 stainless steel

for fixed hose reels in AISI 304 stainless steel
series 290 - 330 - 390 - 430.




P/N 845001

P/N 845001

Fixed support in steel

for fixed enclosed painted steel hose reels
series 450.



P/N 853001



P/N 853002

P/N 853001


Fixed support in steel

for fixed painted steel hose reels
series 530.

P/N 853002

Fixed support in AISI 304 stainless steel

for fixed hose reels in AISI 304 stainless steel
series 530.



P/N 854001



P/N 854002

P/N 854001


Fixed support in steel

for fixed painted steel hose reels
series 540.

P/N 854002

Fixed support in AISI 304 stainless steel

for fixed hose reels in AISI 304 stainless steel
series 540.



P/N 856001



P/N 856002

P/N 856001


Fixed support in steel

for fixed painted steel hose reels
series 560.


P/N 856002

Fixed support in AISI 304 stainless steel

for fixed hose reels in AISI 304 stainless steel
series 560.



A swivelling bracket with quick coupling is available upon request to facilitate hose reel installation in various positions - turned 40° to the right or left, or in the fixed 0° position - by locking it with two screws.



P/N 843005



P/N 843006
P/N 843007



P/N 845005



P/N 853005



P/N 853006
P/N 853007



P/N 854005
P/N 856005



P/N 854006
P/N 854007
P/N 856007

P/N 843005


Swivelling bracket in steel
for fixed hose reels in painted steel
series 290 - 330 - 390 - 430.

P/N 843006

Swivelling bracket in AISI 304 stainless steel
for fixed hose reels in AISI 304 stainless steel
series 290 - 330 - 390 - 430.


P/N 843007

Swivelling bracket in AISI 316 stainless steel
for fixed hose reels in AISI 316 stainless steel
series 290 - 330 - 390 - 430.



P/N 845005

Swivelling bracket in steel
for fixed enclosed painted steel hose reels,
series 450.



P/N 853005


Swivelling bracket in steel
for fixed hose reels in painted steel series 530.

P/N 853006

Swivelling bracket in AISI 304 stainless steel
for fixed hose reels in AISI 304 stainless steel series 530.

P/N 853007

Swivelling bracket in AISI 316 stainless steel
for fixed hose reels in AISI 316 stainless steel series 530.



P/N 854005

Swivelling bracket in steel
for fixed hose reels in painted steel series 540.

P/N 856005

Swivelling bracket in steel
for fixed hose reels in painted steel series 560.

P/N 854006

Swivelling bracket in AISI 304 stainless steel
for fixed hose reels in stainless steel and
AISI 304 stainless steel series 540.


P/N 854007

Swivelling bracket in AISI 316 stainless steel
for fixed hose reels in AISI 316 stainless steel
series 540.


P/N 856007

Swivelling bracket in AISI 316 stainless steel
for fixed hose reels in AISI 316 stainless steel
series 560.

**OVERALL
DIMENSIONS
for series 540**



**OVERALL
DIMENSIONS
for series 560**











ACCESSORIES FOR FIXED ENCLOSED PAINTED STEEL HOSE REELS


BRACKETS FOR BEAM MOUNTING

This special bracket is used to install 1, 2 or 3 hose reels (s. 390 and 430) on HEA ceiling beams. It can be installed and used in two different positions, turned 90° as shown in the figure to the side.




P/N 843011

Bracket for installing 1 hose reel
s. 390 or 430 on HEA beam.




P/N 843012

Bracket for installing 2 hose reels
s. 390 or 430 on HEA beam.



P/N 843013

Bracket for installing 3 hose reels
s. 390 or 430 on HEA beam.




P/N 89003**Bayonet bracket - for enclosed hose reels s. 260 - 280:**

lets you easily move cable reel and hose reel around the various workstations.

P/N 89002**Wall support for bayonet hooking - for hose reels s. 250 - 300****P/N 89001****Wall support with bayonet hooking - for enclosed hose reels s. 260 - 280**

Installing several supports (see drawing) at the points of use lets you easily move the hose reel around the various workstations.

**P/N 89003****P/N 89002****P/N 89001****P/N 89005****Hose guide with 4 opposing rollers**

for application on service columns - for hose reels s. 250.

**P/N 88630**

Modular drip tray. Equipped with hook to secure the gun and removable drip tray. Applied under the hose reel, it is a practical housing for the dispensing gun. Essential for a clean, tidy workplace.

**P/N 88650**

Protective rack side cover in ABS - for hose reel s. 430.

P/N 88651


Protective rack side cover in ABS - for hose reel s. 530 - 540 - 560.



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**


MANUAL HOSE REELS





PESTICIDE TREATMENTS IN AGRICULTURE

PNEUMATIC DEMOLITION IN BUILDING



EXAMPLES OF **USE**

CLEANING

AGRICULTURE

SHIPPING AND
OFFSHORE

AERONAUTICS

BUILDING
AND ROAD
CONSTRUCTION

...and much more



ADVANCED FLUID
MANAGEMENT SOLUTIONS

MANUAL

HOSE REELS SERIES 430-530 540-560



STRENGTH POINTS

- Standard safety system which prevents the handle from being turned during unwinding, prevents accidental injury or property damage.
- Available in AISI 304 or AISI 316 stainless steel for particularly aggressive environments.
- Optimised winding capacity. The absence of springs maximises use of drum space.
- Available for standard models: adjustable clutch that lets you regulate the speed of drum rotation when unwinding the hose. If necessary, it also serves as brake.
- All models in this series comply with the ATEX directive for use in environments with potentially explosive atmospheres.
- The optional rotation lock is recommended for use in vibration-prone environments (trucks, industrial machines, etc.).

TECHNICAL CHARACTERISTICS

Visit our
website



DRUM SUPPORT BUSHING

Made of self-lubricating
technopolymer with excellent
wear and corrosion resistance.

ADJUSTABLE CLUTCH

SAFETY SYSTEM

CENTRAL PIN

Designed to minimise load losses.
Available in different materials
to ensure maximum chemical
compatibility with a wide
range of fluids.


ROTATION LOCK

SWIVEL JOINT

Designed to minimise load
losses. Available in different
materials to ensure maximum
chemical compatibility with a
wide range of fluids.

FIXING BRACKET

Has 4 slotted holes for safe,
easy installation.





**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

MANUAL

HOSE REELS SERIES 500



STRENGTH POINTS

- Standard safety system which prevents the handle from being turned during unwinding, prevents accidental injury or property damage.
- Optimised winding capacity. The absence of a spring and double 1/2" and 1" connections available in the catalogue maximises use of drum space.
- Available for standard models: rotation lock for use in vibration-prone environments (trucks, industrial machines, etc.).
- Available for standard models: adjustable clutch that lets you regulate the speed of drum rotation when unwinding the hose.
- Sturdy structure, epoxy powder-painted - minimum thickness: 80 µm.
- Hose guide with rollers, horizontal and vertical, on 4 sides, designed to extend average hose life, comes standard on all models.

TECHNICAL CHARACTERISTICS

Visit our
website



SWIVEL JOINT

Designed to minimise load losses. Available in different materials to ensure maximum chemical compatibility with a wide range of fluids.

BRAKE DISC

In stainless steel.

HOSE GUIDE

ADJUSTABLE CLUTCH

ROTATION LOCK

SAFETY SYSTEM



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

MANUAL HOSE REELS SERIES 700



STRENGTH POINTS

- These hose reels are designed so that the rewind handle can be positioned on the opposite side, with the possibility to optimize the workplace.
- During unwinding, a convenient housing has been added where you can safely stow the handle.
- Available for standard models: rotation lock for use in vibration-prone environments (trucks, industrial machines, etc.).
- All moving parts are secured and protected against accidental access from the outside.
- These are the only manual hose reels able to rewind hoses of up to 2" in diameter.
- Hose guide with rollers, horizontal and vertical, on 4 sides, designed to extend average hose life, available on all models.

TECHNICAL CHARACTERISTICS

Visit our
website




SWIVEL JOINT

Designed to minimise load losses.
Available in different materials to ensure
maximum chemical compatibility with a
wide range of fluids.

STANDARD POSITION

ALTERNATIVE POSITION




HOLES COVER

ADJUSTABLE CLUTCH

Made of POM, lets you regulate the speed
of drum rotation when unwinding the hose.

HANDLE

Lets you easily
wind up the hose
while controlling
its positioning
on the drum.



HANDLE MOVEMENT WITH CLUTCH

If required by use of the hose reel, the handle and clutch can be moved from
the **standard position** to an **alternative position** with a simple operation
indicated in the instruction manual.




Type of fluid
AIR-WATER

Pressure
20 bar

Material
**- PAINTED STEEL
- ABS**

MANUAL



In accordance with directive





for ABS versions and S. 700


Seals	Swivel joint	Central pin
Viton®	brass aluminum (s. 700)	galvanized steel

DRUM COLOURS

Painted					
ABS					

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	430	186	140	197	226	410	97	456	415	264		540 x 390 x 580		
	430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580		
	530	203	153	220	258	425	104	558	510	315		660 x 390 x 690		
	540	300	218	228	268	532	165	572	510	315		640 x 470 x 695		
	560	488	399	238	272	712	348	578	510	315		670 x 610 x 760		
													(W: width - D: depth - H: height)	

Overall dimensions s. 500 (mm)			Drum W											Packaging (mm) W x D x H	
	240	655	297	313	373	342	220	510	555	468	267		580 x 280 x 590		
	320	715	377	313	373	422	300	510	555	468	267		580 x 280 x 590		
	460	855	517	313	373	562	440	510	555	468	267		650 x 290 x 700		
	600	995	657	313	373	702	580	510	555	468	267		660 x 390 x 690		
(W: width - D: depth - H: height)															

Overall dimensions s. 700 (mm)			Drum W											Packaging (mm) W x D x H	
	270	542	200	300	570	422	260	700	760	659	365		580 x 280 x 590		
	410	542	340	440	710	562	398	700	760	659	365		580 x 280 x 590		
	550	542	480	580	850	702	538	700	760	659	365		650 x 290 x 700		
	690	542	620	720	990	842	680	700	760	659	365		660 x 390 x 690		
	(W: width - D: depth - H: height)														



		P/N	Drum external width (mm)	Connection					Weight
				inlet			outlet		
s. 430	74300.100	115	G 1/2" (f)			G 1/2" (f)			14,5 kg
	74300.150	115	G 1" (f)			G 3/4" (f)			15,5 kg
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m	
s. 430 ABS	74305.100	120	G 1/2" (f)			G 1/2" (f)			12,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m		
s. 530	75300.100	125	G 1/2" (f)			G 1/2" (f)			16,0 kg
	75300.150	125	G 1" (f)			G 1" (f)			17,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 38 m	1/2" 25 m	5/8" 20 m	3/4" 15 m	1" 7 m
s. 540	75400.100	190	G 1" (f)			G 1" (f)			18,3 kg
	75400.105	190	G 1/2" (f)			G 1/2" (f)			17,3 kg
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 48 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560	75600.100	368	G 1" (f)			G 1" (f)			36,0 kg
	75600.106	368	G 1/2" (f)			G 1/2" (f)			35,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 100 m	5/8" 90 m	3/4" 60 m	1" 30 m
s. 500	7522001.100	240	G 1" (f)			G 1" (f)			30,0 kg
	7522001.150	240	G 1/2" (f)			G 1/2" (f)			29,0 kg
	7532001.100	320	G 1" (f)			G 1" (f)			32,5 kg
	7532001.150	320	G 1/2" (f)			G 1/2" (f)			31,5 kg
	7552001.100	460	G 1" (f)			G 1" (f)			36,5 kg
	7552001.150	460	G 1/2" (f)			G 1/2" (f)			35,5 kg
	7562001.100	600	G 1" (f)			G 1" (f)			40,0 kg
	7562001.150	600	G 1/2" (f)			G 1/2" (f)			39,0 kg
Hose reel capacity		inner hose ø drum width 240 drum width 320 drum width 460 drum width 600	1/4" 130 m 200 m 300 m 400 m	3/8" 85 m 130 m 200 m 280 m	1/2" 65 m 100 m 150 m 220 m	3/4" 30 m 50 m 80 m 110 m	1" 20 m 30 m 50 m 70 m		
s. 700 *	7721001.100	270	G 2" (f)			G 2" (f)			88,1 kg
	7741001.100	410	G 2" (f)			G 2" (f)			94,6 kg
	7751001.100	550	G 2" (f)			G 2" (f)			103,0 kg
	7771001.100	690	G 2" (f)			G 2" (f)			119,0 kg
Hose reel capacity		inner hose ø drum width 270 drum width 410 drum width 550 drum width 690	3/8" 160 m 290 m 420 m 550 m	1/2" 110 m 180 m 280 m 350 m	3/4" 65 m 120 m 180 m 244 m	1" 30 m 60 m 100 m 134 m	1.1/4" 20 m 35 m 60 m 84 m	1.1/2" 15 m 30 m 50 m 75 m	2" 10 m 20 m 30 m 43 m

* Versions also available with passages and swivel joints in AISI 304-316 stainless steel




Type of fluid
AIR-WATER

Pressure
20 bar

Material
- AISI 304 S. STEEL
- ABS

MANUAL



without hose, max. 100 °C



In accordance with directive




for ABS versions

Seals	Swivel joint	Central pin
Viton®	brass	AISI 304 s. steel
		

DRUM COLOURS

ABS     

Overall dimensions (mm)		Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
		430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
		430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
		530	203	153	222	258	425	104	558	510	315		660 x 390 x 690
		540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
		560	488	399	238	272	712	348	578	510	315		670 x 610 x 760

(W: width - D: depth - H: height)



P/N		Drum external width (mm)	Connection						Weight	
			inlet			outlet				
s. 430	74320.100	115	G 1/2" (f)			G 1/2" (f)			14,5 kg	
	74320.150	115	G 1" (f)			G 3/4" (f)			15,5 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m		
s. 430 ABS	74325.100	120	G 1/2" (f)			G 1/2" (f)			12,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m			
s. 530	75320.100	125	G 1/2" (f)			G 1/2" (f)			16,0 kg	
	75320.150	125	G 1" (f)			G 1" (f)			17,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m	3/4" 15 m	1" 7 m	
s. 540	75420.100	190	G 1" (f)			G 1" (f)			18,5 kg	
	75420.105	190	G 1/2" (f)			G 1/2" (f)			17,3 kg	
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m	
s. 560	75620.100	368	G 1" (f)			G 1" (f)			36,0 kg	
	75620.106	368	G 1/2" (f)			G 1/2" (f)			35,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 100 m	5/8" 90 m	3/4" 60 m	1" 30 m	




Type of fluid
HOT WATER

Pressure
**100-200
400 bar**

Material
**- PAINTED STEEL
- ABS**

MANUAL



without hose, max. 130 °C



In accordance with directive



for ABS versions


DRUM COLOURS

Painted				
ABS				
S. 500				

Seals	Swivel joint	Central pin
Viton®	AISI 304 s. steel	galvanized steel

Overall dimensions (mm)											Series		Packaging (mm) W x D x H									
											430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
											430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
											530	203	153	220	258	425	104	558	510	315		660 x 390 x 690
											540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
											560	488	399	238	272	712	348	578	510	315		670 x 610 x 760

(W: width - D: depth - H: height)

Overall dimensions s. 500 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			240	655	297	313	373	342	220	510	555	468	267		580 x 280 x 590
			320	715	377	313	373	422	300	510	555	468	267		580 x 280 x 590
			460	855	517	313	373	562	440	510	555	468	267		650 x 290 x 700
			600	995	657	313	373	702	580	510	555	468	267		660 x 390 x 690
(W: width - D: depth - H: height)															

(W: width - D: depth - H: height)



	P/N	Drum external width (mm)	Connection					Weight
			inlet		outlet			
s. 430 100 bar	74300.200	115	G 1/2" (f)		G 1/2" (f)		14,5 kg	
	74300.250	115	G 1" (f)		G 3/4" (f)		15,5 kg	
s. 430 200 bar	74300.300	115	G 3/8" (f)		G 1/2" (f)		14,5 kg	
s. 430 400 bar	74300.350	115	G 3/8" (f)		G 1/2" (f)		14,5 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m
s. 430 ABS 100 bar	74305.200	120	G 1/2" (f)		G 1/2" (f)		12,0 kg	
s. 430 ABS 200 bar	74305.300	120	G 3/8" (f)		G 1/2" (f)		12,0 kg	
s. 430 ABS 400 bar	74305.350	120	G 3/8" (f)		G 1/2" (f)		12,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m		
s. 530 100 bar	75300.200	125	G 1/2" (f)		G 1/2" (f)		16,0 kg	
s. 530 200 bar	75300.300	125	G 3/8" (f)		G 1/2" (f)		16,0 kg	
s. 530 400 bar	75300.350	125	G 3/8" (f)		G 1/2" (f)		16,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m	
s. 540 100 bar	75400.200	190	G 1" (f)		G 1" (f)		18,3 kg	
	75400.205	190	G 1/2" (f)		G 1/2" (f)		17,3 kg	
s. 540 200 bar	75400.300	190	G 3/8" (f)		G 1/2" (f)		17,3 kg	
s. 540 400 bar	75400.350	190	G 3/8" (f)		G 1/2" (f)		17,3 kg	
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 48 m	5/8" 35 m	3/4" 25 m
s. 560 100 bar	75600.200	368	G 1" (f)		G 1" (f)		36,0 kg	
	75600.206	368	G 1/2" (f)		G 1/2" (f)		35,0 kg	
s. 560 200 bar	75600.300	368	G 3/8" (f)		G 1/2" (f)		35,0 kg	
s. 560 400 bar	75600.350	368	G 3/8" (f)		G 1/2" (f)		35,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 100 m	5/8" 90 m	3/4" 60 m
s. 500 100 bar	7522001.200	240	G 1" (f)		G 1" (f)		30,0 kg	
	7522001.250	240	G 1/2" (f)		G 1/2" (f)		29,0 kg	
	7532001.200	320	G 1" (f)		G 1" (f)		32,5 kg	
	7532001.250	320	G 1/2" (f)		G 1/2" (f)		31,5 kg	
	7552001.200	460	G 1" (f)		G 1" (f)		36,5 kg	
	7552001.250	460	G 1/2" (f)		G 1/2" (f)		35,5 kg	
	7562001.200	600	G 1" (f)		G 1" (f)		40,0 kg	
	7562001.250	600	G 1/2" (f)		G 1/2" (f)		39,0 kg	
s. 500 200 bar	7522001.300	240	G 3/8" (f)		G 1/2" (f)		29,0 kg	
	7532001.300	320	G 3/8" (f)		G 1/2" (f)		31,5 kg	
	7552001.300	460	G 3/8" (f)		G 1/2" (f)		35,5 kg	
	7562001.300	600	G 3/8" (f)		G 1/2" (f)		39,0 kg	
Hose reel capacity		inner hose ø	1/4" 130 m	3/8" 85 m	1/2" 65 m	3/4" 30 m	1" 20 m	
		drum width 240	130 m	130 m	100 m	50 m	30 m	
		drum width 320	200 m	200 m	150 m	80 m	50 m	
		drum width 460	300 m	200 m	150 m	80 m	50 m	
		drum width 600	400 m	280 m	220 m	110 m	70 m	



P/N AISI 304 stainless steel	P/N AISI 316 stainless steel	Drum width (mm)	Connection		Weight
			inlet	outlet	

s. 430 100 bar	74340.200	74350.200	115	G 1/2" (f)	G 1/2" (f)	14,5 kg
	74340.250	-	115	G 1" (f)	G 3/4" (f)	15,5 kg
s. 430 200 bar	74340.300	74350.300	115	G 3/8" (f)	G 1/2" (f)	14,5 kg
s. 430 400 bar	74340.350	74350.350	115	G 3/8" (f)	G 1/2" (f)	14,5 kg

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"
	max. length	52 m	35 m	25 m	17 m	15 m	8 m

s. 430 ABS 100 bar	74345.200	-	120	G 1/2" (f)	G 1/2" (f)	12,0 kg
s. 430 ABS 200 bar	74345.300	-	120	G 3/8" (f)	G 1/2" (f)	12,0 kg
s. 430 ABS 400 bar	74345.350	-	120	G 3/8" (f)	G 1/2" (f)	12,0 kg

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"
	max. length	52 m	35 m	25 m	17 m

s. 530 100 bar	75340.200	75350.200	115	G 1/2" (f)	G 1/2" (f)	16,0 kg
s. 530 200 bar	75340.300	75350.300	115	G 3/8" (f)	G 1/2" (f)	16,0 kg
s. 530 400 bar	75340.350	75350.350	115	G 3/8" (f)	G 1/2" (f)	16,0 kg

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"
	max. length	92 m	65 m	35 m	25 m	20 m

s. 540 100 bar	75440.200	75450.200	190	G 1" (f)	G 1" (f)	18,3 kg
	75440.205	75450.205	190	G 1/2" (f)	G 1/2" (f)	17,3 kg
s. 540 200 bar	75440.300	-	190	G 3/8" (f)	G 1/2" (f)	17,3 kg
s. 540 400 bar	75440.350	-	190	G 3/8" (f)	G 1/2" (f)	17,3 kg

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
	max. length	150 m	110 m	65 m	48 m	35 m	25 m	15 m

s. 560 100 bar	75640.200	75650.200	368	G 1" (f)	G 1" (f)	35,0 kg
	75640.206	75650.206	368	G 1/2" (f)	G 1/2" (f)	35,0 kg
s. 560 200 bar	75640.300	-	368	G 3/8" (f)	G 1/2" (f)	35,0 kg
s. 560 400 bar	75640.350	-	368	G 3/8" (f)	G 1/2" (f)	35,0 kg

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
	max. length	320 m	200 m	140 m	100 m	90 m	60 m	30 m

s. 700 70 bar	7724001.200	7725001.200	270	G 2" (f)	G 2" (f)	88,1 kg
	7744001.200	7745001.200	410	G 2" (f)	G 2" (f)	94,6 kg
	7754001.200	7755001.200	550	G 2" (f)	G 2" (f)	103,0 kg
	7774001.200	7775001.200	690	G 2" (f)	G 2" (f)	119,0 kg

Hose reel capacity	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
**OIL AND
SIMILAR**

Pressure
70-150 bar

Material
**- PAINTED STEEL
- ABS**

MANUAL



without hose, max. 80 °C

In accordance with directive





for ABS versions and S. 700


DRUM COLOURS

Painted     S. 500 - 700 
ABS     

Seals	Swivel joint	Central pin
polyurethane Viton® (s. 700)	galvanized steel	galvanized steel
		

Overall dimensions (mm)										Series		Packaging (mm) W x D x H									
										430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
										430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
										530	203	153	220	258	425	104	558	510	315		660 x 390 x 690
										540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
										560	488	399	238	272	712	348	578	510	315		670 x 610 x 760
										(W: width - D: depth - H: height)											

Overall dimensions s. 500 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			240	655	297	313	373	342	220	510	555	468	267		580 x 280 x 590
			320	715	377	313	373	422	300	510	555	468	267		580 x 280 x 590
			460	855	517	313	373	562	440	510	555	468	267		650 x 290 x 700
			600	995	657	313	373	702	580	510	555	468	267		660 x 390 x 690
(W: width - D: depth - H: height)															

Overall dimensions s. 700 (mm)			Drum W										Packaging (mm) W x D x H	
	270	542	200	300	570	422	260	700	760	659	365		580 x 280 x 590	
	410	542	340	440	710	562	398	700	760	659	365		580 x 280 x 590	
	550	542	480	580	850	702	538	700	760	659	365		650 x 290 x 700	
	690	542	620	720	990	842	680	700	760	659	365		660 x 390 x 690	
(W: width - D: depth - H: height)														



		P/N	Drum external width (mm)	Connection				Weight	
				inlet		outlet			
s. 430 150 bar	74300.400	115	G 1/2" (f)			G 1/2" (f)		14,5 kg	
	74300.450	115	G 1" (f)			G 3/4" (f)		14,5 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m	
s. 430 ABS 150 bar	74305.400	120	G 1/2" (f)			G 1/2" (f)		12,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m			
s. 530 150 bar	75300.400	125	G 1/2" (f)			G 1/2" (f)		16,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m		
s. 540 150 bar	75400.400	190	G 1" (f)			G 1" (f)		18,3 kg	
	75400.405	190	G 1/2" (f)			G 1/2" (f)		17,3 kg	
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560 150 bar	75600.400	368	G 1" (f)			G 1" (f)		36,0 kg	
	75600.406	368	G 1/2" (f)			G 1/2" (f)		35,0 kg	
Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 85 m	5/8" 90 m	3/4" 60 m	1" 30 m
s. 500 150 bar	7522001.400	240	G 1" (f)			G 1" (f)		30,0 kg	
	7522001.450	240	G 1/2" (f)			G 1/2" (f)		29,0 kg	
	7532001.400	320	G 1" (f)			G 1" (f)		32,5 kg	
	7532001.450	320	G 1/2" (f)			G 1/2" (f)		31,5 kg	
	7552001.400	460	G 1" (f)			G 1" (f)		36,5 kg	
	7552001.450	460	G 1/2" (f)			G 1/2" (f)		35,5 kg	
	7562001.400	600	G 1" (f)			G 1" (f)		40,0 kg	
	7562001.450	600	G 1/2" (f)			G 1/2" (f)		39,0 kg	
Hose reel capacity		inner hose ø	1/4"	3/8"	1/2"	3/4"	1"		
		drum width 240	130 m	85 m	65 m	30 m	20 m		
		drum width 320	200 m	130 m	100 m	50 m	30 m		
		drum width 460	300 m	200 m	150 m	80 m	50 m		
		drum width 600	400 m	280 m	220 m	110 m	70 m		
s. 700 70 bar	7721001.400	270	G 2" (f)			G 2" (f)		88,1 kg	
	7741001.400	410	G 2" (f)			G 2" (f)		94,6 kg	
	7751001.400	550	G 2" (f)			G 2" (f)		103,0 kg	
	7771001.400	690	G 2" (f)			G 2" (f)		119,0 kg	
Hose reel capacity		inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
		drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
		drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
		drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
		drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
**OIL AND
SIMILAR**

Pressure
150 bar

Material
**- AISI 304 S. STEEL
- ABS**

MANUAL



without hose, max. 130 °C



In accordance with directive




for ABS versions

DRUM COLOURS

ABS     

Seals	Swivel joint	Central pin
Viton®	AISI 304 s. steel	AISI 304 s. steel
		

Overall dimensions (mm)				Series										Packaging (mm) W x D x H	
				A	B	C	D	E	F	G	H	I			
				430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
				430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
				530	203	153	220	258	425	104	558	510	315		660 x 390 x 690
				540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
				560	488	399	238	272	712	348	578	510	315		670 x 610 x 760
														(W: width - D: depth - H: height)	

(W: width - D: depth - H: height)



P/N		Drum external width (mm)	Connection				Weight		
			inlet		outlet				
s. 430	74340.200	115	G 1/2" (f)		G 1/2" (f)		14,5 kg		
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m			
s. 430 ABS	74345.200	120	G 1/2" (f)		G 1/2" (f)		12,0 kg		
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m			
s. 530	75340.200	125	G 1/2" (f)		G 1/2" (f)		16,0 kg		
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m		
s. 540	75440.200	190	G 1" (f)		G 1" (f)		18,3 kg		
	75440.205	190	G 1/2" (f)		G 1/2" (f)		17,3 kg		
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560	75640.200	368	G 1" (f)		G 1" (f)		36,0 kg		
	75640.206	368	G 1/2" (f)		G 1/2" (f)		35,0 kg		
Hose reel capacity		inner hose ø max. length	1/4" 324 m	5/16" 200 m	3/8" 140 m	1/2" 85 m	5/8" 90 m	3/4" 60 m	1" 30 m




Type of fluid
GREASE

Pressure
600 bar

Material
- PAINTED STEEL
- ABS

MANUAL



without hose, max. 80 °C



In accordance with directive

CE  II 2 GD


CE  II 3 GD

for ABS versions

Seals	Swivel joint	Central pin
polyurethane	galvanized steel	galvanized steel
		

DRUM COLOURS

Painted    
ABS     

Overall dimensions (mm)											Series		A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
											430		186	140	197	226	410	97	456	415	264		540 x 390 x 580
											430 ABS		186	140	197	226	405	110	461	425	259		540 x 390 x 580
											530		203	153	220	258	425	104	558	510	315		660 x 390 x 690
											540		300	218	228	268	532	165	572	510	315		640 x 470 x 695
											560		488	399	238	272	712	348	578	510	315		670 x 610 x 760

(W: width - D: depth - H: height)



	P/N	Drum external width (mm)	Connection				Weight
			inlet		outlet		
s. 430	74300.500	115	G 3/8" (f)		G 1/2" (f)		14,5 kg
Hose reel capacity		inner hose ø1/4"max. length52 m	5/16"35 m	3/8"25 m	1/2"17 m	5/8"15 m	
s. 430 ABS	74305.500	120	G 3/8" (f)		G 1/2" (f)		12,0 kg
Hose reel capacity		inner hose ø1/4"max. length52 m	5/16"35 m	3/8"25 m	1/2"17 m	5/8"15 m	
s. 530	75300.500	125	G 3/8" (f)		G 1/2" (f)		16,0 kg
Hose reel capacity		inner hose ø1/4"max. length92 m	5/16"65 m	3/8"35 m	1/2"25 m	5/8"20 m	
s. 540	75400.500	190	G 3/8" (f)		G 1/2" (f)		17,3 kg
Hose reel capacity		inner hose ø1/4"max. length150 m	5/16"110 m	3/8"65 m	1/2"45 m	5/8"35 m	
s. 560	75600.500	368	G 3/8" (f)		G 1/2" (f)		35,0 kg
Hose reel capacity		inner hose ø1/4"max. length320 m	5/16"200 m	3/8"140 m	1/2"100 m	5/8"90 m	




Type of fluid
GREASE


Pressure
600 bar

Material
- AISI 304 S. STEEL
- ABS

MANUAL



without hose, max. 80 °C



In accordance with directive




for ABS versions

Seals	Swivel joint	Central pin
polyurethane	galvanized steel	AISI 304 s. steel

DRUM COLOURS

ABS     

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
			430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
			430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
			530	203	153	220	258	425	104	558	510	315		660 x 390 x 690
			540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
			560	488	399	238	272	712	348	578	510	315		670 x 610 x 760

(W: width - D: depth - H: height)



	P/N	Drum external width (mm)	Connection				Weight
			inlet		outlet		
s. 430	74320.500	115	G 3/8" (f)		G 1/2" (f)		14,5 kg
Hose reel capacity		inner hose ø1/4"52 m max. length	5/16"35 m	3/8"25 m	1/2"17 m	5/8"15 m	
s. 430 ABS	74325.500	120	G 3/8" (f)		G 1/2" (f)		12,0 kg
Hose reel capacity		inner hose ø1/4"52 m max. length	5/16"35 m	3/8"25 m	1/2"17 m	5/8"15 m	
s. 530	75320.500	125	G 3/8" (f)		G 1/2" (f)		16,0 kg
Hose reel capacity		inner hose ø1/4"92 m max. length	5/16"65 m	3/8"35 m	1/2"25 m	5/8"20 m	
s. 540	75420.500	190	G 3/8" (f)		G 1/2" (f)		17,3 kg
Hose reel capacity		inner hose ø1/4"150 m max. length	5/16"110 m	3/8"65 m	1/2"45 m	5/8"35 m	
s. 560	75620.500	368	G 3/8" (f)		G 1/2" (f)		35,0 kg
Hose reel capacity		inner hose ø1/4"320 m max. length	5/16"200 m	3/8"140 m	1/2"100 m	5/8"90 m	




Type of fluid
DIESEL

Pressure
20 bar

Material
- PAINTED STEEL
- ABS

MANUAL



without hose, max. 100 °C

In accordance with directive



for ABS versions and S. 700

Seals	Swivel joint	Central pin
Viton®	brass	galvanized steel
	aluminum (s. 700)	

DRUM COLOURS

Painted S. 500 - 700
ABS

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
			430	186	140	197	226	410	97	456	415	264		540 x 390 x 580
			430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580
			530	203	153	220	258	425	104	558	510	315		660 x 390 x 690
			540	300	218	228	268	532	165	572	510	315		640 x 470 x 695
			560	488	399	238	272	712	348	578	510	315		670 x 610 x 760

(W: width - D: depth - H: height)

Overall dimensions s. 500 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			240	655	297	313	373	342	220	510	555	468	267		580 x 280 x 590
			320	715	377	313	373	422	300	510	555	468	267		580 x 280 x 590
			460	855	517	313	373	562	440	510	555	468	267		650 x 290 x 700
			600	995	657	313	373	702	580	510	555	468	267		660 x 390 x 690

(W: width - D: depth - H: height)

Overall dimensions s. 700 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			270	542	200	300	570	422	260	700	760	659	365		580 x 280 x 590
			410	542	340	440	710	562	398	700	760	659	365		580 x 280 x 590
			550	542	480	580	850	702	538	700	760	659	365		650 x 290 x 700
			690	542	620	720	990	842	680	700	760	659	365		660 x 390 x 690

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

s. 430	74300.600	115	G 1/2" (f)	G 1/2" (m)	14,5 kg
--------	-----------	-----	------------	------------	---------

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"
	max. length	52 m	35 m	25 m	17 m	15 m	8 m

s. 430 ABS	74305.600	120	G 1/2" (f)	G 1/2" (m)	12,0 kg
---------------	-----------	-----	------------	------------	---------

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"
	max. length	52 m	35 m	25 m	17 m	15 m	8 m

s. 530	75300.150	125	G 1" (f)	G 1" (f)	16,0 kg
--------	-----------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
	max. length	92 m	65 m	35 m	25 m	20 m	15 m	7 m

s. 540	75400.100	190	G 1" (f)	G 1" (f)	18,3 kg
--------	-----------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
	max. length	150 m	110 m	65 m	45 m	35 m	25 m	15 m

s. 560	75600.100	368	G 1" (f)	G 1" (f)	36,0 kg
--------	-----------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
	max. length	324 m	200 m	140 m	100 m	90 m	60 m	30 m

s. 500	7522001.100	240	G 1" (f)	G 1" (f)	30,0 kg
	7532001.100	320	G 1" (f)	G 1" (f)	32,5 kg
	7552001.100	460	G 1" (f)	G 1" (f)	36,5 kg
	7562001.100	600	G 1" (f)	G 1" (f)	40,0 kg

Hose reel capacity	inner hose ø	1/4"	3/8"	1/2"	3/4"	1"
	drum width 240	130 m	85 m	65 m	30 m	20 m
	drum width 320	200 m	130 m	100 m	50 m	30 m
	drum width 460	300 m	200 m	150 m	80 m	50 m
	drum width 600	400 m	280 m	220 m	110 m	70 m

s. 700	7721001.100	270	G 2" (f)	G 2" (f)	88,1 kg
	7741001.100	410	G 2" (f)	G 2" (f)	94,6 kg
	7751001.100	550	G 2" (f)	G 2" (f)	103,2 kg
	7771001.100	690	G 2" (f)	G 2" (f)	119,0 kg

Hose reel capacity	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m

Prepared with outlet connection for ø 3/4" hoses




Type of fluid
DIESEL

Pressure
20 bar

Material
- AISI 304 S. STEEL
- ABS

MANUAL



without hose, max. 100 °C



In accordance with directive



for ABS versions

DRUM COLOURS

ABS     

Seals	Swivel joint	Central pin
Viton®	brass	AISI 304 s. steel
		

Overall dimensions (mm)											Packaging (mm) W x D x H	
Series	A	B	C	D	E	F	G	H	I			
430	186	140	197	226	410	97	456	415	264		540 x 390 x 580	
430 ABS	186	140	197	226	405	110	461	425	259		540 x 390 x 580	
530	203	153	220	258	425	104	558	510	315		660 x 390 x 690	
540	300	218	228	268	532	165	572	510	315		640 x 470 x 695	
560	488	399	238	272	712	348	578	510	315		670 x 610 x 760	

(W: width - D: depth - H: height)



	P/N	Drum external width (mm)	Connection						Weight
			inlet			outlet			
s. 430	74320.600	115	G 1/2" (f)			G 1/2" (m)			14,5 kg
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m	
s. 430 ABS	74325.600	120	G 1/2" (f)			G 1/2" (m)			12,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 52 m	5/16" 35 m	3/8" 25 m	1/2" 17 m	5/8" 15 m	3/4" 8 m	
s. 530	75320.150	125	G 1" (f)			G 1" (f)			16,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m	3/4" 15 m	1" 7 m
s. 540	75420.100	190	G 1" (f)			G 1" (f)			18,3 kg
Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560	75620.100	368	G 1" (f)			G 1" (f)			36,0 kg
Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 100 m	5/8" 90 m	3/4" 60 m	1" 30 m



Prepared with outlet connection for Ø 3/4" hoses




ADVANCED FLUID
MANAGEMENT SOLUTIONS

MANUAL TROLLEY-MOUNTED HOSE REELS




EXAMPLES OF **USE**



OFFSHORE FACILITIES CLEANING

HEALTHY AND FOOD ENVIRONMENTS WASHING OPERATIONS



MINING
INDUSTRY

AGRICULTURE

SHIPPING AND
OFFSHORE

MANUFACTUR-
ING INDUSTRY

AERONAUTICS

...and much more



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

MANUAL

TROLLEY-MOUNTED HOSE REELS




STRENGTH POINTS

- The trolley has been designed to meet specific parameters and prevent rollover during hose unwinding, achieved with the special brake and geometry of the floor stands.
- Super block trolley brake comes standard on all models, automatically locks the trolley only when stationary.
- Standard safety system which prevents the handle from being turned during unwinding, prevents accidental injury or property damage.
- Fold-in handle as standard reduces the overall dimensions of the hose reel and simultaneously increases safety.
- Standard hose guide to extend average hose life and facilitate unwinding.
- Adjustable clutch and rotation lock are standard, let you modulate rotation speed or completely lock the drum.

TECHNICAL CHARACTERISTICS

Visit our
website






Hose reel
**TROLLEY-
MOUNTED**

Pressure
**20-100
200-400 bar**

Material
PAINTED STEEL

MANUAL




- without hose:
with brass swivel joint
max. 100 °C
with steel swivel joint
max. 130 °C



	Trolley	Drum	Seals	Swivel joint	Central pin
AIR-WATER	galvanized steel	painted steel	Viton®	brass	galvanized steel
HOT WATER	galvanized steel	painted steel	Viton® - Teflon®	AISI 304 s. steel	galvanized steel
					

DRUM COLOURS

Painted

Overall dimensions (mm)		Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
		530	1050	210	104	350	464	510	463	205	675	 650 x 290 x 700
		540	1050	270	165	413	530	510	463	205	675	660 x 390 x 690
		560	1050	450	348	595	705	510	463	205	675	670 x 610 x 760
		(W: width - D: depth - H: height)										



s. 530



s. 540



s. 560

P/N		Hose supplied		Connection					Weight
				inlet		outlet			
AIR-WATER 20 bar									
s. 530	236530.100	without hose *		G 1/2" (f)		G 1/2" (f)			29,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	92 m	65 m	35 m	25 m	20 m	15 m	7 m
s. 540	236540.100	without hose *		G 1" (f)		G 1" (f)			34,0 kg
	236540.105	without hose *		G 1/2" (f)		G 1/2" (f)			33,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	150 m	110 m	65 m	45 m	35 m	25 m	15 m
s. 560	236560.100	without hose *		G 1" (f)		G 1" (f)			40,0 kg
	236560.105	without hose *		G 1/2" (f)		G 1/2" (f)			39,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	320 m	200 m	140 m	85 m	90 m	60 m	30 m
HOT WATER 100 bar									
s. 530	236530.200	without hose *		G 1/2" (f)		G 1/2" (f)			29,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	92 m	65 m	35 m	25 m	20 m	15 m	7 m
s. 540	236540.200	without hose *		G 1" (f)		G 1" (f)			34,0 kg
	236540.205	without hose *		G 1/2" (f)		G 1/2" (f)			33,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	150 m	110 m	65 m	45 m	35 m	25 m	15 m
s. 560	236560.200	without hose *		G 1" (f)		G 1" (f)			35,0 kg
	236560.205	without hose *		G 1/2" (f)		G 1/2" (f)			35,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
		max. length	320 m	200 m	140 m	85 m	90 m	60 m	30 m
HOT WATER 200 bar									
s. 530	236530.300	without hose *		G 3/8" (f)		G 1/2" (f)			29,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"			
		max. length	92 m	65 m	35 m	25 m			
s. 540	236540.300	without hose *		G 3/8" (f)		G 1/2" (f)			33,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"			
		max. length	150 m	110 m	65 m	45 m			
s. 560	236560.300	without hose *		G 3/8" (f)		G 1/2" (f)			40,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"	1/2"			
		max. length	320 m	200 m	140 m	85 m			
HOT WATER 400 bar									
s. 530	236530.350	without hose *		G 3/8" (f)		G 1/2" (f)			29,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"				
		max. length	92 m	65 m	35 m				
s. 540	236540.350	without hose *		G 3/8" (f)		G 1/2" (f)			33,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"				
		max. length	150 m	110 m	65 m				
s. 560	236560.350	without hose *		G 3/8" (f)		G 1/2" (f)			40,0 kg
* Hose reel capacity		inner hose Ø	1/4"	5/16"	3/8"				
		max. length	320 m	200 m	140 m				




Hose reel
**TROLLEY-
MOUNTED**

Pressure
**20-100
200-400 bar**

Material
**- AISI 304 S. STEEL
- AISI 316 S. STEEL**


MANUAL



- without hose:
with brass swivel joint
max. 100 °C
with steel swivel joint
max. 130 °C



	Trolley	Drum	Seals	Swivel joint	Central pin
AIR-WATER	AISI 304-316 stainless steel	AISI 304-316 stainless steel	Viton®	brass	AISI 304-316 stainless steel
HOT WATER			Viton® - Teflon®	AISI 304-316 s. steel	
					

Overall dimensions (mm)		Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
		530	1050	210	104	350	464	510	463	205	675		650 x 290 x 700
		540	1050	270	165	413	530	510	463	205	675		660 x 390 x 690
		560	1050	450	348	595	705	510	463	205	675		670 x 610 x 760

(W: width - D: depth - H: height)



s. 530



s. 540



s. 560

P/N AISI 304 stainless steel		P/N AISI 316 stainless steel	Hose supplied	Connection		Weight			
				inlet	outlet				
AIR-WATER 20 bar									
s. 530	246532.100	-	without hose *	G 1/2" (f)	G 1/2" (f)	29,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m	3/4" 15 m	1" 7 m
s. 540	246542.100	-	without hose *	G 1" (f)	G 1" (f)	34,0 kg			
	246542.105	-	without hose *	G 1/2" (f)	G 1/2" (f)	33,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560	246562.100	-	without hose *	G 1" (f)	G 1" (f)	40,0 kg			
	246562.105	-	without hose *	G 1/2" (f)	G 1/2" (f)	39,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 85 m	5/8" 90 m	3/4" 60 m	1" 30 m
HOT WATER 100 bar									
s. 530	246534.200	256535.200	without hose *	G 1/2" (f)	G 1/2" (f)	29,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m	5/8" 20 m	3/4" 15 m	1" 7 m
s. 540	246544.200	256545.200	without hose *	G 1" (f)	G 1" (f)	34,0 kg			
	246544.205	256545.205	without hose *	G 1/2" (f)	G 1/2" (f)	33,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m	5/8" 35 m	3/4" 25 m	1" 15 m
s. 560	246564.200	256565.200	without hose *	G 1" (f)	G 1" (f)	40,0 kg			
	246564.205	256565.205	without hose *	G 1/2" (f)	G 1/2" (f)	35,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 85 m	5/8" 90 m	3/4" 60 m	1" 30 m
HOT WATER 200 bar									
s. 530	246534.300	256535.300	without hose *	G 3/8" (f)	G 1/2" (f)	29,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m	1/2" 25 m			
s. 540	246544.300	256545.300	without hose *	G 3/8" (f)	G 1/2" (f)	33,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m	1/2" 45 m			
s. 560	246564.300	256565.300	without hose *	G 3/8" (f)	G 1/2" (f)	40,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m	1/2" 85 m			
HOT WATER 400 bar									
s. 530	246534.350	256535.350	without hose *	G 3/8" (f)	G 1/2" (f)	29,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 92 m	5/16" 65 m	3/8" 35 m				
s. 540	246544.350	256545.350	without hose *	G 3/8" (f)	G 1/2" (f)	33,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 150 m	5/16" 110 m	3/8" 65 m				
s. 560	246564.350	256565.350	without hose *	G 3/8" (f)	G 1/2" (f)	40,0 kg			
* Hose reel capacity		inner hose ø max. length	1/4" 320 m	5/16" 200 m	3/8" 140 m				



ACCESSORIES FOR MANUAL HOSE REELS



P/N 843001
P/N 853001



P/N 843002
P/N 853002



P/N 854001
P/N 856001



P/N 854002
P/N 856002

P/N 843001

Fixed support in steel for fixed painted steel hose reels s. 430.

P/N 843002

Fixed support in AISI 304 stainless steel - for fixed hose reels in AISI 304 stainless steel s. 430.

P/N 853001

Fixed support in steel - for fixed painted steel hose reels s. 530.

P/N 853002

Fixed support in AISI 304 stainless steel - for fixed hose reels in AISI 304 stainless steel s. 530.

P/N 854001

Fixed support in steel - for fixed painted steel hose reels s. 540.

P/N 854002

Fixed support in AISI 304 stainless steel - for fixed hose reels in AISI 304 stainless steel s. 540.

P/N 856001

Fixed support in steel - for fixed painted steel hose reels s. 560.

P/N 856002

Fixed support in AISI 304 stainless steel - for fixed hose reels in AISI 304 stainless steel s. 560.

For more information on the supports, see page 80.



**PAINTED
STEEL**

**STAINLESS
STEEL**

ARMS AND HOSE GUIDE FOR MANUAL HOSE REEL

	painting steel	AISI 304 stainless steel	AISI 316 stainless steel
s. 430	P/N 743001	P/N 743401	P/N 743501
s. 530	P/N 753001	P/N 753401	P/N 753501
s. 540	P/N 754001	P/N 754401	P/N 754501
s. 560	P/N 756001	P/N 756401	P/N 756501

FOLD-IN HANDLE FOR MANUAL HOSE REEL

	galvanized steel	AISI 304 stainless steel	AISI 316 stainless steel
s. 430	P/N 743004	P/N 743404	P/N 743504
s. 530 s. 540 s. 560	P/N 753004	P/N 753404	P/N 753504



**GALVANIZED
STEEL**



**STAINLESS
STEEL**



P/N 74301

Rotation lock in AISI 304 stainless steel - for hose reels in painted steel and AISI 304 stainless steel series 430 - 430 ABS - 530 - 540 - 560.

P/N 74302

Rotation lock in AISI 316 stainless steel - for hose reels in painted steel and AISI 316 stainless steel series 430 - 430 ABS - 530 - 540 - 560.



P/N 88650


Protective rack side cover in ABS - for hose reel series 430.

P/N 88651

Protective rack side cover in ABS - for hose reel series 530 - 540 - 560.



ACCESSORIES FOR MANUAL, PAINTED STEEL HOSE REELS SERIES 700



High manual operation hose guide

P/N 77/22775B for width 270 mm

P/N 77/24175B for width 410 mm

P/N 77/25575B for width 550 mm

P/N 77/26975B for width 690 mm

By operating the special handle, the operator moves the hose to the right or left, ensuring correct rewinding.

Low manual operation hose guide

P/N 77/22775 for width 270 mm

P/N 77/24175 for width 410 mm

P/N 77/25575 for width 550 mm

P/N 77/26975 for width 690 mm

Standard closed hose guide, high

P/N 77/12775B for width 270 mm

P/N 77/14175B for width 410 mm

P/N 77/15575B for width 550 mm

P/N 77/16975B for width 690 mm

Hose guide with rollers that allow the hose to slide easily during unwinding and rewinding operations.

Standard closed hose guide, low

P/N 77/12775 for width 270 mm

P/N 77/14175 for width 410 mm

P/N 77/15575 for width 550 mm

P/N 77/16975 for width 690 mm

Standard open hose guide, high

P/N 77/32775B for width 270 mm

P/N 77/34175B for width 410 mm

P/N 77/35575B for width 550 mm

P/N 77/36975B for width 690 mm

This type of hose guide allows for installation of both versions (high and low) on the same hose reel, thus allowing hose unwinding in two opposing directions.








Standard open hose guide, low

P/N 77/32775 for width 270 mm

P/N 77/34175 for width 410 mm

P/N 77/35575 for width 550 mm

P/N 77/36975 for width 690 mm



P/N 77/2F Painted steel free fall clutch permits controlled unwinding of the hose and switches to neutral during rewinding phase.

P/N 77/3F Free fall clutch in AISI 316 stainless steel permits controlled unwinding of the hose and switches to neutral during rewinding phase.


P/N 77/4F Free fall clutch in AISI 304 stainless steel permits controlled unwinding of the hose and switches to neutral during rewinding phase.



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

MOTORIZED HOSE REELS





REFUELLING SHIPS IN PORT

ROADS CLEANING



EXAMPLES OF **USE**

LUBE
TRUCKS AND
INDUSTRIAL
VEHICLES

MINING
INDUSTRY

SHIPPING AND
OFFSHORE

CHEMICAL
INDUSTRY

RAILWAY
TRANSPORT

...and much more



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

MOTORIZED HOSE REELS




STRENGTH POINTS

- Different hose guides have been designed to extend average hose life and facilitate unwinding.
- Available for all standard models: rotation lock for use in vibration-prone environments (trucks, industrial machines, etc.).
- All moving parts are secured and protected against accidental access from the outside.
- The catalogue also contains models compliant with the ATEX directive for use in environments with potentially explosive atmospheres.
- Articles are also available in AISI 304 and 316 stainless steel for use in aggressive or corrosive environments.
- These are the largest capacity hose reels in the RAASM product range for rewinding hoses up to 2" in diameter.

TECHNICAL CHARACTERISTICS

Visit our
website






Type of fluid
AIR-WATER

Pressure
20 bar

Material
PAINTED STEEL


MOTORIZED




without hose, max. 100 °C



Seals	Swivel joint	Central pin
Viton®	brass	galvanized steel
	aluminum (s. 700)	
		

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			617	283	185	140	130	310	360	200	465	317	570		670 x 610 x 760
			618	283	185	140	130	310	360	200	560	317	570		670 x 610 x 760
			637	467	370	140	130	310	360	390	650	317	570		810 x 670 x 760
			638	467	370	140	130	310	360	390	730	317	570		810 x 670 x 760

(W: width - D: depth - H: height)

Overall dimensions s. 700 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			270	300	200	542	365	570	260	435	700	760	670		820 x 770 x 845
			410	440	340	542	365	712	398	575	700	760	670		875 x 845 x 820
			550	580	480	542	365	850	538	717	700	760	670		1030 x 830 x 830
			690	720	620	542	365	990	680	855	700	760	670		1170 x 830 x 845

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

HYDRAULIC

s. 617	8617.100	220	G 1" (f)		G 1" (f)		63,0 kg
Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"	
	max. length	90 m	65 m	45 m	30 m	20 m	
s. 637	8637.100	400	G 1" (f)		G 1" (f)		85,0 kg
Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"	
	max. length	200 m	150 m	110 m	75 m	50 m	

PNEUMATIC

s. 618	8618.100	220	G 1" (f)	G 1" (f)	70,4 kg	
Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m
s. 638	8638.100	400	G 1" (f)	G 1" (f)	92,4 kg	
Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

ELECTRIC 24 V DC

s. 700	7721301.100	270	G 2" (f)	G 2" (f)	105,0 kg
	7741301.100	410	G 2" (f)	G 2" (f)	111,0 kg
	7751301.100	550	G 2" (f)	G 2" (f)	116,0 kg
	7771301.100	690	G 2" (f)	G 2" (f)	121,7 kg

ELECTRIC 230 V AC - 50 Hz

s. 700	7721601.100	270	G 2" (f)	G 2" (f)	110,0 kg
	7741601.100	410	G 2" (f)	G 2" (f)	116,0 kg
	7751601.100	550	G 2" (f)	G 2" (f)	120,8 kg
	7771601.100	690	G 2" (f)	G 2" (f)	126,5 kg

ELECTRIC 230 V AC - 50 Hz (with standard clutch) II 3 GD

s. 700	7721702.100	270	G 2" (f)	G 2" (f)	112,6 kg
	7741702.100	410	G 2" (f)	G 2" (f)	118,4 kg
	7751702.100	550	G 2" (f)	G 2" (f)	123,4 kg
	7771702.100	690	G 2" (f)	G 2" (f)	129,1 kg

HYDRAULIC

s. 700	7721801.100	270	G 2" (f)	G 2" (f)	100,0 kg
	7741801.100	410	G 2" (f)	G 2" (f)	106,3 kg
	7751801.100	550	G 2" (f)	G 2" (f)	111,3 kg
	7771801.100	690	G 2" (f)	G 2" (f)	117,0 kg

PNEUMATIC (This series is in accordance with ATEX directive II 3GD if ordered with clutch P/N 77/2F)

s. 700	7721901.100	270	G 2" (f)	G 2" (f)	104,2 kg
	7741901.100	410	G 2" (f)	G 2" (f)	110,0 kg
	7751901.100	550	G 2" (f)	G 2" (f)	115,0 kg
	7771901.100	690	G 2" (f)	G 2" (f)	120,7 kg

Hose reel capacity s. 700	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	32 m	20 m	17 m	10 m
	drum width 410	290 m	180 m	120 m	64 m	39 m	34 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	54 m	30 m
	drum width 690	550 m	375 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
HOT WATER

Pressure
70-100 bar

Material
PAINTED STEEL


MOTORIZED




without hose, max. 130 °C



Seals	Swivel joint	Central pin
Viton®	AISI 304 s. steel	galvanized steel (s. 600)
	AISI 316 s. steel	AISI 316 s. steel (s. 700)
		

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			617	283	185	140	130	310	360	200	465	317	570		670 x 610 x 760
			618	283	185	140	130	310	360	200	560	317	570		670 x 610 x 760
			637	467	370	140	130	310	360	390	650	317	570		810 x 670 x 760
			638	467	370	140	130	310	360	390	730	317	570		810 x 670 x 760

(W: width - D: depth - H: height)

Overall dimensions s. 700 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			270	300	200	542	365	570	260	435	700	760	670		820 x 770 x 845
			410	440	340	542	365	712	398	575	700	760	670		875 x 845 x 820
			550	580	480	542	365	850	538	717	700	760	670		1030 x 830 x 830
			690	720	620	542	365	990	680	855	700	760	670		1170 x 830 x 845

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

HYDRAULIC

s. 617 100 bar	8617.200	220	G 1" (f)	G 1" (f)	63,0 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 637 100 bar	8637.200	400	G 1" (f)	G 1" (f)	85,0 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

PNEUMATIC

s. 618 100 bar	8618.200	220	G 1" (f)	G 1" (f)	70,4 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 638 100 bar	8638.200	400	G 1" (f)	G 1" (f)	92,4 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

ELECTRIC 230 V AC - 50 Hz PASSAGE AND SWIVEL JOINT IN AISI 316 STAINLESS STEEL

s. 700 70 bar	7726601.200	270	G 2" (f)	G 2" (f)	110,0 kg
	7746601.200	410	G 2" (f)	G 2" (f)	116,0 kg
	7756601.200	550	G 2" (f)	G 2" (f)	120,8 kg

ELECTRIC 230 V AC - 50 Hz (with standard clutch) PASSAGE AND SWIVEL JOINT IN AISI 316 STAINLESS STEEL



s. 700 70 bar	7726702.200	270	G 2" (f)	G 2" (f)	112,8 kg
	7756702.200	550	G 2" (f)	G 2" (f)	123,6 kg

PNEUMATIC - PASSAGE AND SWIVEL JOINT IN AISI 316 STAINLESS STEEL (This series is in accordance with ATEX directive II 3GD if ordered with clutch P/N 77/2F)

s. 700 70 bar	7746901.200	410	G 2" (f)	G 2" (f)	110,0 kg
-------------------------	--------------------	-----	----------	----------	----------

Hose reel capacity s. 700	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
HOT WATER

Pressure
70 bar

Material
- AISI 304 S. STEEL
- AISI 316 S. STEEL


MOTORIZED



without hose, max. 130 °C



			Seals	Swivel joint	Central pin
WASTE OIL	OIL AND SIMILAR	DIESEL	Viton®	stainless steel AISI 304-316	stainless steel AISI 304-316
					

Overall dimensions s. 700 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			270	300	200	542	365	570	260	200	465	760	670		820 x 770 x 845
			410	440	340	542	365	712	398	200	560	760	670		875 x 845 x 820
			550	580	480	542	365	850	538	390	650	760	670		1030 x 830 x 830
			690	720	620	542	365	990	680	390	730	760	670		1170 x 830 x 845

(W: width - D: depth - H: height)



P/N in AISI 304 stainless steel	P/N in AISI 316 stainless steel	Drum external width (mm)	Connection		Weight
			inlet	outlet	

ELECTRIC 24 V DC

s. 700	7724301.200	7725301.200	270	G 2" (f)	G 2" (f)	105,0 kg
	7744301.200	7745301.200	410	G 2" (f)	G 2" (f)	111,0 kg
	7754301.200	7755301.200	550	G 2" (f)	G 2" (f)	116,0 kg
	7774301.200	7775301.200	690	G 2" (f)	G 2" (f)	121,7 kg

ELECTRIC 230 V AC - 50 Hz

s. 700	7724601.200	7725601.200	270	G 2" (f)	G 2" (f)	110,0 kg
	7744601.200	7745601.200	410	G 2" (f)	G 2" (f)	116,0 kg
	7754601.200	7755601.200	550	G 2" (f)	G 2" (f)	120,8 kg
	7774601.200	7775601.200	690	G 2" (f)	G 2" (f)	126,5 kg

ELECTRIC 230 V AC - 50 Hz (with standard clutch) II 3 GD

s. 700 ATEX	7724702.200	7725702.200	270	G 2" (f)	G 2" (f)	112,8 kg
	7744702.200	7745702.200	410	G 2" (f)	G 2" (f)	118,8 kg
	7754702.200	7755702.200	550	G 2" (f)	G 2" (f)	123,6 kg
	7774702.200	7775702.200	690	G 2" (f)	G 2" (f)	129,3 kg

HYDRAULIC

s. 700	7724801.200	7725801.200	270	G 2" (f)	G 2" (f)	100,0 kg
	7744801.200	7745801.200	410	G 2" (f)	G 2" (f)	106,3 kg
	7754801.200	7755801.200	550	G 2" (f)	G 2" (f)	111,3 kg
	7774801.200	7775801.200	690	G 2" (f)	G 2" (f)	117,0 kg

PNEUMATIC (This series is in accordance with ATEX directive II 3GD if ordered with clutch P/N 77/2F)

s. 700	7724901.200	7725901.200	270	G 2" (f)	G 2" (f)	104,2 kg
	7744901.200	7745901.200	410	G 2" (f)	G 2" (f)	110,0 kg
	7754901.200	7755901.200	550	G 2" (f)	G 2" (f)	115,0 kg
	7774901.200	7775901.200	690	G 2" (f)	G 2" (f)	120,7 kg

Hose reel capacity s. 700	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
**OIL AND
SIMILAR**

Pressure
70-150 bar

Material
PAINTED STEEL


MOTORIZED



without hose, max. 80 °C




	Seals	Swivel joint	Central pin
S. 600	polyurethane	galvanized steel	galvanized steel
S. 700	Viton®		
			

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
	617	283	185	140	130	310	360	200	465	317	570		670 x 710 x 760		
	618	283	185	140	130	310	360	200	560	317	570		670 x 710 x 760		
	637	467	370	140	130	310	360	390	650	317	570		810 x 670 x 760		
	638	467	370	140	130	310	360	390	730	317	570		810 x 670 x 760		

(W: width - D: depth - H: height)

(W: width - D: depth - H: height)

Overall dimensions s. 700 (mm)			Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H		
	270	300	200	542	365	570	260	422	700	760	659		820 x 770 x 845			
	410	440	340	542	365	710	398	562	700	760	659		875 x 845 x 820			
	550	580	480	542	365	850	538	702	700	760	659		1030 x 830 x 830			
	690	720	620	542	365	990	680	842	700	760	659		1170 x 830 x 845			
															(W: width - D: depth - H: height)	

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

HYDRAULIC

s. 617 150 bar	8617.400	220	G 1" (f)	G 1" (f)	63,0 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 637 150 bar	8637.400	400	G 1" (f)	G 1" (f)	85,0 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

PNEUMATIC

s. 618 150 bar	8618.400	220	G 1" (f)	G 1" (f)	70,4 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 638 150 bar	8638.400	400	G 1" (f)	G 1" (f)	92,4 kg
--------------------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

ELECTRIC 24 V DC

s. 700 70 bar	7721301.400	270	G 2" (f)	G 2" (f)	105,0 kg
	7741301.400	410	G 2" (f)	G 2" (f)	111,0 kg
	7751301.400	550	G 2" (f)	G 2" (f)	116,0 kg
	7771301.400	690	G 2" (f)	G 2" (f)	121,7 kg

ELECTRIC 230 V AC - 50 Hz

s. 700 70 bar	7721601.400	270	G 2" (f)	G 2" (f)	110,0 kg
	7741601.400	410	G 2" (f)	G 2" (f)	116,0 kg
	7751601.400	550	G 2" (f)	G 2" (f)	120,8 kg
	7771601.400	690	G 2" (f)	G 2" (f)	126,5 kg

ELECTRIC 230 V AC - 50 Hz (with standard clutch) II 3 GD

s. 700 70 bar	7721702.400	270	G 2" (f)	G 2" (f)	112,6 kg
	7741702.400	410	G 2" (f)	G 2" (f)	118,4 kg
	7751702.400	550	G 2" (f)	G 2" (f)	123,4 kg
	7771702.400	690	G 2" (f)	G 2" (f)	129,1 kg

HYDRAULIC

s. 700 70 bar	7721801.400	270	G 2" (f)	G 2" (f)	100,0 kg
	7741801.400	410	G 2" (f)	G 2" (f)	106,3 kg
	7751801.400	550	G 2" (f)	G 2" (f)	111,3 kg
	7771801.400	690	G 2" (f)	G 2" (f)	117,0 kg

PNEUMATIC (This series is in accordance with ATEX directive II 3GD if ordered with clutch P/N 77/2F)

s. 700 70 bar	7721901.400	270	G 2" (f)	G 2" (f)	104,2 kg
	7741901.400	410	G 2" (f)	G 2" (f)	110,0 kg
	7751901.400	550	G 2" (f)	G 2" (f)	115,0 kg
	7771901.400	690	G 2" (f)	G 2" (f)	120,7 kg

Hose reel capacity s. 700	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m




Type of fluid
GREASE

Pressure
400 bar

Material
PAINTED STEEL


MOTORIZED



without hose, max. 80 °C



Seals	Swivel joint	Central pin
polyurethane	galvanized steel	galvanized steel
		

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
			617	283	185	140	130	310	360	200	465	317	570		670 x 610 x 760
			618	283	185	140	130	310	360	200	560	317	570		670 x 610 x 760
			637	467	370	140	130	310	360	390	650	317	570		810 x 670 x 760
			638	467	370	140	130	310	360	390	730	317	570		810 x 670 x 760

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

HYDRAULIC

s. 617	8617.500	220	G 1" (f)	G 1" (f)	63,0 kg
---------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 637	8637.500	400	G 1" (f)	G 1" (f)	85,0 kg
---------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

PNEUMATIC

s. 618	8618.500	220	G 1" (f)	G 1" (f)	70,4 kg
---------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 638	8638.500	400	G 1" (f)	G 1" (f)	92,4 kg
---------------	-----------------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m




Type of fluid
DIESEL

Pressure
20 bar

Material
PAINTED STEEL


MOTORIZED




without hose, max. 100 °C



Seals	Swivel joint	Central pin
Viton®	brass	galvanized steel
	aluminum (s. 700)	
		

Overall dimensions (mm)			Series	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
	617	283	185	140	130	310	360	200	465	317	570		670 x 710 x 760		
	618	283	185	140	130	310	360	200	560	317	570		670 x 710 x 760		
	637	467	370	140	130	310	360	390	650	317	570		810 x 670 x 760		
	638	467	370	140	130	310	360	390	730	317	570		810 x 670 x 760		
(W: width - D: depth - H: height)															

(W: width - D: depth - H: height)

Overall dimensions s. 700 (mm)													
	Drum W	A	B	C	D	E	F	G	H	I	L	Packaging (mm) W x D x H	
	270	300	200	542	365	570	260	435	700	760	670		820 x 770 x 845
	410	440	340	542	365	712	398	575	700	760	670		875 x 845 x 820
	550	580	480	542	365	850	538	717	700	760	670		1030 x 830 x 830
	690	720	620	542	365	990	680	855	700	760	670		1170 x 830 x 845
													(W: width - D: depth - H: height)

(W: width - D: depth - H: height)



P/N	Drum external width (mm)	Connection		Weight
		inlet	outlet	

HYDRAULIC

s. 617	8617.600	220	G 1.1/2" (f)	G 1.1/2" (f)	63,0 kg
--------	----------	-----	--------------	--------------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"
	max. length	90 m	65 m	45 m	30 m	20 m	15 m	10 m

s. 637	8637.600	400	G 1.1/2" (f)	G 1.1/2" (f)	85,0 kg
--------	----------	-----	--------------	--------------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"
	max. length	200 m	150 m	110 m	75 m	50 m	30 m	20 m

PNEUMATIC

s. 618	8618.100	220	G 1" (f)	G 1" (f)	70,4 kg
--------	----------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	90 m	65 m	45 m	30 m	20 m

s. 638	8638.100	400	G 1" (f)	G 1" (f)	92,4 kg
--------	----------	-----	----------	----------	---------

Hose reel capacity	inner hose ø	3/8"	1/2"	5/8"	3/4"	1"
	max. length	200 m	150 m	110 m	75 m	50 m

ELECTRIC 24 V DC

s. 700	7721301.100	270	G 2" (f)	G 2" (f)	105,0 kg
	7741301.100	410	G 2" (f)	G 2" (f)	111,0 kg
	7751301.100	550	G 2" (f)	G 2" (f)	116,0 kg
	7771301.100	690	G 2" (f)	G 2" (f)	121,7 kg

ELECTRIC 230 V AC - 50 Hz

s. 700	7721601.100	270	G 2" (f)	G 2" (f)	110,0 kg
	7741601.100	410	G 2" (f)	G 2" (f)	116,8 kg
	7751601.100	550	G 2" (f)	G 2" (f)	120,8 kg
	7771601.100	690	G 2" (f)	G 2" (f)	126,8 kg

ELECTRIC 230 V AC - 50 Hz (with standard clutch) II 3 GD

s. 700	7721702.100	270	G 2" (f)	G 2" (f)	112,6 kg
	7741702.100	410	G 2" (f)	G 2" (f)	118,4 kg
	7751702.100	550	G 2" (f)	G 2" (f)	123,4 kg
	7771702.100	690	G 2" (f)	G 2" (f)	129,1 kg

HYDRAULIC


s. 700	7721801.100	270	G 2" (f)	G 2" (f)	100,0 kg
	7741801.100	410	G 2" (f)	G 2" (f)	106,3 kg
	7751801.100	550	G 2" (f)	G 2" (f)	111,3 kg
	7771801.100	690	G 2" (f)	G 2" (f)	117,0 kg

PNEUMATIC

s. 700	7721901.100	270	G 2" (f)	G 2" (f)	104,2 kg
	7741901.100	410	G 2" (f)	G 2" (f)	110,0 kg
	7751901.100	550	G 2" (f)	G 2" (f)	115,0 kg
	7771901.100	690	G 2" (f)	G 2" (f)	120,7 kg

Hose reel capacity s. 700	inner hose ø	3/8"	1/2"	3/4"	1"	1.1/4"	1.1/2"	2"
	drum width 270	160 m	110 m	65 m	30 m	20 m	15 m	10 m
	drum width 410	290 m	180 m	120 m	60 m	35 m	30 m	20 m
	drum width 550	420 m	280 m	180 m	100 m	60 m	50 m	30 m
	drum width 690	550 m	350 m	244 m	134 m	84 m	75 m	43 m

ACCESSORIES FOR MOTORIZED HOSE REELS - SERIES 700



High manual operation hose guide

P/N 77/22775B for width 270 mm

P/N 77/24175B for width 410 mm

P/N 77/25575B for width 550 mm

P/N 77/26975B for width 690 mm

By operating the special handle, the operator moves the hose to the right or left, ensuring correct rewinding.



Low manual operation hose guide

P/N 77/22775 for width 270 mm

P/N 77/24175 for width 410 mm

P/N 77/25575 for width 550 mm

P/N 77/26975 for width 690 mm



Standard closed hose guide, high

P/N 77/12775B for width 270 mm

P/N 77/14175B for width 410 mm

P/N 77/15575B for width 550 mm

P/N 77/16975B for width 690 mm

Hose guide with rollers that allow the hose to slide easily during unwinding and rewinding operations.



Standard closed hose guide, low

P/N 77/12775 for width 270 mm

P/N 77/14175 for width 410 mm

P/N 77/15575 for width 550 mm

P/N 77/16975 for width 690 mm



Standard open hose guide, high

P/N 77/32775B for width 270 mm

P/N 77/34175B for width 410 mm

P/N 77/35575B for width 550 mm

P/N 77/36975B for width 690 mm

This type of hose guide allows for installation of both versions (high and low) on the same hose reel, thus allowing hose unwinding in two opposing directions.



Standard open hose guide, low

P/N 77/32775 for width 270 mm

P/N 77/34175 for width 410 mm

P/N 77/35575 for width 550 mm








P/N 77/36975 for width 690 mm



P/N 77/2F Painted steel free fall clutch permits controlled unwinding of the hose and switches to neutral during rewinding phase.

P/N 77/3F Free fall clutch in AISI 316 stainless steel permits controlled unwinding of the hose and switches to neutral during rewinding phase.

P/N 77/4F Free fall clutch in AISI 304 stainless steel permits controlled unwinding of the hose and switches to neutral during rewinding phase.



HOSES

TECHNICAL DATA



STRENGTH POINTS

The range of hoses offered by RAASM for its hose reels is in line with company's quality standards and guarantees superb performance in applications with the pressures specified in the catalogue.

For conditions other than those recommended, RAASM will work with the customer to evaluate each and every aspect of the pertinent application (material compatibility with the fluid, working temperature, operating pressure, etc.) to determine the best hose for each specific case.



The hoses mounted on the hose reels must be suitable to handle the operating pressures indicated on the hose reel's label.

HOSES: TECHNICAL DATA



CONNECTION HOSE FOR HOSE REEL - SYSTEM INTERCONNECTION

P/N	Pressure	Hose length	Hose characteristics	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
987.205	10 bar	0,6 m	antistatic EPDM	3/4"	19 x 27 mm	G 3/4" (f)	G 1/2" (m)	AISI 304 s. steel
987.206	10 bar	0,6 m	antistatic EPDM	3/4"	19 x 27 mm	G 3/4" (f)	G 1" (m)	AISI 304 s. steel
995.106	10 bar	0,6 m	atoxic hygienic	3/8"	10 x 17 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
996.106	10 bar	0,6 m	atoxic hygienic	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
997.806	10 bar	0,6 m	black rubber	3/4"	19 x 27 mm	G 1/2" (m)	G 3/4" (f)	galvanized steel
998.106	10 bar	0,6 m	atoxic hygienic	1"	25 x 35 mm	G 1" (m)	G 1" (f)	galvanized steel
972.102	20 bar	1,5 m	polyurethane	10 x 14,5	10 x 14,5 mm	G 3/8" (m)	G 3/8" (f)	brass
975.1002	20 bar	1,5 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.902	20 bar	1,5 m	SBR/EPDM	2 x 3/8"	9 + 9 x 16 mm	G 3/8" (f)	G 3/8" (f)	brass
976.102	20 bar	1,5 m	polyurethane	13 x 19	13 x 19 mm	G 1/2" (f)	G 1/2" (m)	brass
993.201	20 bar	1 m	black rubber	1/4"	6,4 x 13 mm	G 1/4" (f)	G 1/4" (m)	galvanized steel
993.202	20 bar	2 m	black rubber	1/4"	6,4 x 13 mm	G 1/4" (f)	G 1/4" (m)	galvanized steel
995.206	20 bar	0,6 m	black rubber	3/8"	9,5 x 16 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
998.305	50 bar	0,6 m	black rubber	1"	25,4 x 31,5 mm	G 1" (m)	G 1" (f)	galvanized steel
998.3301	50 bar	1 m	black rubber	1"	25,4 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.3302	50 bar	2 m	black rubber	1"	25,4 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.3306	50 bar	0,6 m	black rubber	1"	25,4 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.406	50 bar	0,6 m	hygienic	1"	24,5 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.806	50 bar	0,6 m	black rubber	1"	25 x 35 mm	G 1" (m)	G 1" (f)	galvanized steel
996.305	100 bar	0,6 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
997.3305	100 bar	5 m	black rubber	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.3306	100 bar	0,6 m	black rubber	3/4"	19 x 26,5 mm	G 1/2" (m)	G 3/4" (f)	galvanized steel
996.406	100 bar	0,6 m	hygienic	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
995.301	150 bar	1,2 m	black rubber	3/8"	9,5 x 16 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
996.301	150 bar	1 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.3015	150 bar	1,5 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
996.302	150 bar	2 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (f)	galvanized steel
996.304	150 bar	4 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.306	150 bar	0,6 m	black rubber	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
995.506	200 bar	0,6 m	black rubber	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.606	200 bar	0,6 m	hygienic	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
993.504	400 bar	4 m	black rubber	1/4"	6,3 x 17,5 mm	G 1/4" (f)	G 1/4" (m)	galvanized steel
995.701	400 bar	1 m	black rubber	3/8"	9,5 x 18 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.702	400 bar	2 m	black rubber	3/8"	9,5 x 18 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.706	400 bar	0,6 m	black rubber	3/8"	9,5 x 18 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.806	400 bar	0,6 m	black rubber	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.906	400 bar	0,6 m	hygienic	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel

Air-water 10 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
995.112	12 m	atoxic hygienic	95 °C	3/8"	10 x 17 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
996.110	10 m	atoxic hygienic	95 °C	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
996.116	15 m	atoxic hygienic	95 °C	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
996.120	20 m	atoxic hygienic	95 °C	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
996.125	25 m	atoxic hygienic	95 °C	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
996.130	30 m	atoxic hygienic	95 °C	1/2"	13 x 20 mm	G 1/2" (m)	G 1/2" (f)	galvanized steel
997.115	15 m	atoxic hygienic	95 °C	3/4"	19 x 27 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
997.120	20 m	atoxic hygienic	95 °C	3/4"	19 x 27 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
997.130	30 m	atoxic hygienic	95 °C	3/4"	19 x 27 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
997.140	40 m	atoxic hygienic	95 °C	3/4"	19 x 27 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
998.115	15 m	atoxic hygienic	95 °C	1"	25 x 35 mm	G 1" (m)	G 1" (f)	galvanized steel
998.120	20 m	atoxic hygienic	95 °C	1"	25 x 35 mm	G 1" (m)	G 1" (f)	galvanized steel
998.130	30 m	atoxic hygienic	95 °C	1"	25 x 35 mm	G 1" (m)	G 1" (f)	galvanized steel

Air-water 20 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
971.010	10 m	polyurethane	60 °C	1/4"	6 x 10 mm	G 3/8" (m)	G 1/4" (m)	brass
971.011	11 m	polyurethane	60 °C	1/4"	6 x 10 mm	G 1/4" (m)	G 1/4" (m)	brass
971.015	15 m	polyurethane	60 °C	1/4"	6 x 10 mm	G 3/8" (m)	G 1/4" (m)	brass
971.111	11 m	polyurethane	60 °C	5/16"	8 x 12 mm	G 1/4" (m)	G 1/4" (m)	brass
971.115	15 m	polyurethane	60 °C	5/16"	6 x 12 mm	G 3/8" (m)	G 1/4" (m)	brass
971.118	18 m	polyurethane	60 °C	5/16"	8 x 12 mm	G 3/8" (m)	G 1/4" (m)	brass
971.120	20 m	polyurethane	60 °C	5/16"	8 x 12 mm	G 3/8" (m)	G 1/4" (m)	brass
972.113	13 m	polyurethane	60 °C	3/8"	10 x 14,5 mm	G 3/8" (m)	G 3/8" (m)	brass
972.115	15 m	polyurethane	60 °C	3/8"	10 x 14,5 mm	G 3/8" (m)	G 3/8" (m)	brass
972.120	20 m	polyurethane	60 °C	3/8"	10 x 14,5 mm	G 3/8" (m)	G 3/8" (m)	brass
976.108	8 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (m)	G 1/2" (m)	brass
976.110	10 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (m)	G 1/2" (m)	brass
976.111	10 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (f)	G 1/2" (m)	brass
976.112	12 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (m)	G 1/2" (m)	brass
976.114	15 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (m)	G 1/2" (m)	brass
976.115	15 m	polyurethane	60 °C	1/2"	13 x 19 mm	G 1/2" (f)	G 1/2" (m)	brass
993.215	15 m	black rubber	80 °C	1/4"	6,5 x 12,6 mm	G 3/8" (m)	G 1/4" (m)	galvanized steel
995.210	10 m	black rubber	80 °C	3/8"	9,5 x 17 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
995.211	12 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
995.212	12 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
995.217	18 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
995.218	18 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (f)	G 3/8" (m)	galvanized steel
996.210	10 m	black rubber	80 °C	1/2"	12,7 x 20 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.215	15 m	black rubber	80 °C	1/2"	12,7 x 20 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.220	20 m	black rubber	80 °C	1/2"	12,7 x 20 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.225	25 m	black rubber	80 °C	1/2"	12,7 x 20 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.230	30 m	black rubber	80 °C	1/2"	12,7 x 20 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
997.215	15 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.220	20 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.230	30 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.240	40 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
998.215	15 m	black rubber	80 °C	1"	25,4 x 32,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.220	20 m	black rubber	80 °C	1"	25,4 x 32,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.230	30 m	black rubber	80 °C	1"	25,4 x 32,5 mm	G 1" (f)	G 1" (m)	galvanized steel

Hot water 50 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
998.315	15 m	black rubber	80 °C	1"	25,4 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.330	30 m	black rubber	80 °C	1"	25,4 x 31,5 mm	G 1" (f)	G 1" (m)	galvanized steel

Hot water 100 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
995.313	12 m	black rubber	80 °C	3/8"	9,5 x 15 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
995.318	17 m	black rubber	80 °C	3/8"	9,5 x 15 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
995.412	12 m	hygienic	130 °C	3/8"	9,5 x 15 mm	G 3/8" (m)	G 3/8" (m)	galvanized steel
996.311	10 m	black rubber	80 °C	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.316	15 m	black rubber	80 °C	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.321	20 m	black rubber	80 °C	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.415	15 m	hygienic	130 °C	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.425	25 m	hygienic	130 °C	1/2"	12,7 x 18,5 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
997.320	20 m	black rubber	80 °C	3/4"	19 x 25 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.420	20 m	hygienic	130 °C	3/4"	19 x 25 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel

Hot water 200 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
994.512	12 m	black rubber	130 °C	5/16"	8 x 15 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
994.517	17 m	black rubber	130 °C	5/16"	8 x 15 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
994.612	12 m	hygienic	130 °C	5/16"	8 x 15 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
995.512	12 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.518	18 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.520	20 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.525	25 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.530	30 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.540	40 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.550	50 m	black rubber	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.618	18 m	hygienic	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.625	25 m	hygienic	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.630	30 m	hygienic	130 °C	3/8"	9,5 x 17 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel

Hot water 400 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
994.717	17 m	black rubber	130 °C	5/16"	8 x 16 mm	G 3/8" (m)	G 3/8" (f)	galvanized steel
995.815	15 m	black rubber	130 °C	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.820	20 m	black rubber	130 °C	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.825	25 m	black rubber	130 °C	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.915	15 m	hygienic	130 °C	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel
995.925	25 m	hygienic	130 °C	3/8"	9,5 x 17,5 mm	G 3/8" (f)	G 3/8" (f)	galvanized steel

Oil and similar 50 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
998.3310	10 m	black rubber	80 °C	1"	25,4 x 33,5 mm	G 1" (m)	G 1" (f)	galvanized steel
998.3315	15 m	black rubber	80 °C	1"	25,4 x 33,5 mm	G 1" (f)	G 1" (m)	galvanized steel
998.3320	20 m	black rubber	80 °C	1"	25,4 x 33,5 mm	G 1" (m)	G 1" (f)	galvanized steel
998.3330	30 m	black rubber	80 °C	1"	25,4 x 33,5 mm	G 1" (f)	G 1" (m)	galvanized steel

Oil and similar 100 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
997.3308	8 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (m)	G 1/2" (f)	galvanized steel
997.3312	12 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
997.3315	15 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.3320	20 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.3330	30 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
997.3340	40 m	black rubber	80 °C	3/4"	19 x 26,5 mm	G 3/4" (m)	G 3/4" (f)	galvanized steel
999.3310	10 m	black rubber	80 °C	5/8"	16 x 23 mm	G 1/2" (f)	G 3/4" (m)	galvanized steel

Oil and similar 150 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
995.312	12 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (m)	G 1/2" (m)	galvanized steel
995.317	17 m	black rubber	80 °C	3/8"	9,5 x 16 mm	G 3/8" (m)	G 1/2" (m)	galvanized steel
996.310	10 m	black rubber	80 °C	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.315	15 m	black rubber	80 °C	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.320	20 m	black rubber	80 °C	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.325	25 m	black rubber	80 °C	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
996.330	30 m	black rubber	80 °C	1/2"	12,7 x 19 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel

Grease 400 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
993.511	12 m	black rubber	80 °C	1/4"	6,3 x 17,5 mm	G 3/8" (m)	G 1/4" (m)	galvanized steel
993.512	12 m	black rubber	80 °C	1/4"	6,3 x 17,5 mm	G 1/4" (f)	G 1/4" (m)	galvanized steel
993.516	16 m	black rubber	80 °C	1/4"	6,3 x 17,5 mm	G 3/8" (m)	G 1/4" (m)	galvanized steel
993.518	18 m	black rubber	80 °C	1/4"	6,3 x 17,5 mm	G 1/4" (f)	G 1/4" (m)	galvanized steel
995.710	10 m	black rubber	80 °C	3/8"	9,5 x 18 mm	G 3/8" (f)	G 1/4" (m)	galvanized steel
995.715	15 m	black rubber	80 °C	3/8"	9,5 x 18 mm	G 3/8" (f)	G 1/4" (m)	galvanized steel
995.720	20 m	black rubber	80 °C	3/8"	9,5 x 18 mm	G 3/8" (f)	G 1/4" (m)	galvanized steel
995.725	25 m	black rubber	80 °C	3/8"	9,5 x 18 mm	G 3/8" (f)	G 1/4" (m)	galvanized steel
995.730	30 m	black rubber	80 °C	3/8"	9,5 x 18 mm	G 3/8" (f)	G 1/4" (m)	galvanized steel

Diesel 10 bar

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
997.808	8 m	black rubber	80 °C	3/4"	19 x 27 mm	G 1/2" (f)	G 3/4" (m)	galvanized steel
997.812	12 m	black rubber	80 °C	3/4"	19 x 27 mm	G 1/2" (f)	G 1/2" (m)	galvanized steel
997.815	15 m	black rubber	80 °C	3/4"	19 x 27 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.820	20 m	black rubber	80 °C	3/4"	19 x 27 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
997.840	40 m	black rubber	80 °C	3/4"	19 x 27 mm	G 3/4" (f)	G 3/4" (m)	galvanized steel
998.808	8 m	black rubber	80 °C	1"	25 x 35 mm	G 1" (f)	G 1" (m)	galvanized steel
998.815	15 m	black rubber	80 °C	1"	25 x 35 mm	G 1" (f)	G 1" (m)	galvanized steel
998.820	20 m	black rubber	80 °C	1"	25 x 35 mm	G 1" (f)	G 1" (m)	galvanized steel
998.830	30 m	black rubber	80 °C	1"	25 x 35 mm	G 1" (f)	G 1" (m)	galvanized steel
999.810	10 m	black rubber	80 °C	5/8"	16 x 23 mm	G 1/2" (f)	G 3/4" (m)	galvanized steel

P/N	Hose length	Hose characteristics	Max. working temperature	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
987.208	8 m	Antistatic EPDM	80 °C	3/4"	19 x 27 mm	G 1/2" (f)	G 3/4" (m)	AISI 304 s. steel
987.210	10 m	Antistatic EPDM	80 °C	3/4"	19 x 27 mm	G 3/4" (f)	G 3/4" (m)	AISI 304 s. steel
987.215	15 m	Antistatic EPDM	80 °C	3/4"	19 x 27 mm	G 3/4" (f)	G 3/4" (m)	AISI 304 s. steel

 Welding 20 bar - EN ISO 3821


P/N	Hose length	Hose characteristics	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
973.913	13 m	SBR/EPDM	2 x 1/4"	2 x (6,3 x 13) mm	G 3/8" (f)	G 3/8" (f)	brass
973.917	17 m	SBR/EPDM	2 x 1/4"	2 x (6,3 x 13) mm	G 3/8" (f)	G 3/8" (f)	brass
973.920	20 m	SBR/EPDM	2 x 1/4"	2 x (6,3 x 13) mm	G 3/8" (f)	G 3/8" (f)	brass
973.925	25 m	SBR/EPDM	2 x 1/4"	2 x (6,3 x 13) mm	G 3/8" (f)	G 3/8" (f)	brass
973.930	30 m	SBR/EPDM	2 x 1/4"	2 x (6,3 x 13) mm	G 3/8" (f)	G 3/8" (f)	brass
974.912	12 m	SBR/EPDM	2 x 5/16"	2 x (8 x 15) mm	G 3/8" (f)	G 3/8" (f)	brass
974.915	15 m	SBR/EPDM	2 x 5/16"	2 x (8 x 15) mm	G 3/8" (f)	G 3/8" (f)	brass
974.920	20 m	SBR/EPDM	2 x 5/16"	2 x (8 x 15) mm	G 3/8" (f)	G 3/8" (f)	brass
974.925	25 m	SBR/EPDM	2 x 5/16"	2 x (8 x 15) mm	G 3/8" (f)	G 3/8" (f)	brass
974.930	30 m	SBR/EPDM	2 x 5/16"	2 x (8 x 15) mm	G 3/8" (f)	G 3/8" (f)	brass
975.915	15 m	SBR/EPDM	2 x 3/8"	2 x (9 x 16) mm	G 3/8" (f)	G 3/8" (f)	brass
975.920	20 m	SBR/EPDM	2 x 3/8"	2 x (9 x 16) mm	G 3/8" (f)	G 3/8" (f)	brass
975.927	27 m	SBR/EPDM	2 x 3/8"	2 x (9 x 16) mm	G 3/8" (f)	G 3/8" (f)	brass

 LPG-methane 20 bar - EN ISO 3821

P/N	Hose length	Hose characteristics	Hose ø	Dimensions - internal ø x external ø	Inlet	Outlet	Connections
974.1008	8 m	NBR/PVC	5/16"	8 x 15 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
974.1015	15 m	NBR/PVC	5/16"	8 x 15 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
974.1020	20 m	NBR/PVC	5/16"	8 x 15 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
974.1028	28 m	NBR/PVC	5/16"	8 x 15 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.1010	10 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.1015	15 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.1018	18 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.1027	27 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass
975.1030	30 m	NBR/PVC	3/8"	10 x 17 mm	G 3/8" (f) LH	G 3/8" (f) LH	brass

HOSE STOP

Adapters for hoses of different diameters (supplied with the hose stop).



Universal hose stop, supplied with all hose reels that come without hose, complete with adapters for the use of different diameter hoses.

P/N	Hose reel series		ø Reduction
KR7201	290 - 330 380 - 390	Painted - Stainless steel	12 - 14 - 16 mm
KR8104	420 - 430 - 440 450 - 520 - 530	Painted - Stainless steel	14 - 17 - 19 mm
KR8705	540 - 550 - 560	Painted - Stainless steel	14 - 17,5 - 21 28,5 - 30 - 34 mm
KR8907	420 - 520 - 540	Twin hose	12 - 14 - 15 - 16 mm

FITTINGS TO CONNECT HOSES EXITING THE HOSE REEL




Nipple, carbon steel		
Article	Thread dimensions	Thread type
33114	G 1" (m) x G 1/2" (m)	cylindrical/cylindrical thread
33116	G 1" (m) x G 1" (m)	cylindrical/cylindrical thread
33117	G 3/4" (m) x G 3/4" (m)	cylindrical/cylindrical thread
33118	G 1/2" (m) x G 3/4" (m)	tapered/cylindrical thread
33119	G 1" (m) x G 3/4" (m)	cylindrical/cylindrical thread
33270	G 1.1/2" (m) x G 3/4" (m)	cylindrical/cylindrical thread
33271	G 1.1/2" (m) x G 1" (m)	cylindrical/cylindrical thread
33272	G 1.1/2" (m) x G 1.1/4" (m)	cylindrical/cylindrical thread
33273	G 1.1/2" (m) x G 1.1/4" (f)	cylindrical/cylindrical thread
33274	G 1" (m) x G 1/2" (m)	cylindrical/cylindrical thread
38071	G 1/2" (m) x G 1/2" (m)	tapered/cylindrical thread
38072	G 1/2" (m) x G 3/8" (m)	cylindrical/cylindrical thread
38073	G 3/8" (m) x G 3/8" (m)	tapered/cylindrical thread
38074	G 1/2" (m) x G 1/2" (m)	cylindrical/cylindrical thread
66891	G 1/4" (m) x G 1/4" (m)	tapered/cylindrical thread
66892	G 1/4" (m) x G 1/2" (m)	cylindrical/cylindrical thread
66893	G 1/2" (m) x G 1/4" (m)	cylindrical/cylindrical thread


Nipple, AISI 304 stainless steel		
Article	Thread dimensions	Thread type
33128	G 1" (m) x G 3/4" (m)	cylindrical/cylindrical thread
33129	G 1" (m) x G 1" (m)	cylindrical/cylindrical thread
33130	G 3/4" (m) x G 3/4" (m)	cylindrical/cylindrical thread
38120	G 1/2" (m) x G 3/8" (m)	cylindrical/cylindrical thread
38121	G 1/2" (m) x G 1/2" (m)	cylindrical/cylindrical thread
38122	G 1/2" (m) x G 3/8" (m)	cylindrical/cylindrical thread
38124	G 1/2" (m) x G 1/2" (m)	tapered/cylindrical thread

Nipple, AISI 316 stainless steel		
Article	Thread dimensions	Thread type
33131	G 1" (m) x G 3/4" (m)	cylindrical/cylindrical thread
33132	G 1" (m) x G 1" (m)	cylindrical/cylindrical thread
33133	G 1" (m) x G 1/2" (m)	cylindrical/cylindrical thread
38123	G 1/2" (m) x G 3/8" (m)	cylindrical/cylindrical thread
38125	G 1/2" (m) x G 3/4" (m)	cylindrical/cylindrical thread


CONNECTING HOSES EXITING THE HOSE REEL




Series 290 - 330 - 380 - 390




Series 420 - 430 - 520 - 530




Series 440 - 450



Series 540-550-560
outlet 1"



Series 540-550-560
outlet 1/2"



Welding-gas series



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED ELECTRIC CABLE REELS



EXAMPLES OF **USE**

AUTOMOTIVE


MINING
INDUSTRY

MANUFACTUR-
ING INDUSTRY

AERONAUTICS


BUILDING
AND ROAD
CONSTRUCTION

...and much more



POWER PNEUMATIC EQUIPMENT ON CONSTRUCTION SITES

MAINTENANCE OF WINE CELLAR PRODUCTION EQUIPMENT





**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

SPRING OPERATED **ELECTRIC CABLE REELS**




STRENGTH POINTS

- Special electric collector to drastically reduce overheating during operation.
- Thermal protector standard on all models.
- IP44 protection degree standard on all models (IP45 if equipped with protection cap).
- An optional protection degree is available, useful to protect against accidental, uncontrolled rewinding of the cable.
- Cable guide with rollers, horizontal and vertical, on 4 sides, designed to extend average cable life, comes standard on all models.
- Repeated spring stress-tests guarantees decades of life and efficiency.



TECHNICAL CHARACTERISTICS

Visit our
website



PAWL

Easy to remove for maintenance or when the work requires free sliding.

REWINDING CLUTCH

Optional: lets you rewind the drum at a safe speed.

SPRING

Tested to withstand over 20000 work cycles.

SIDE CLUTCH

Has special seals that act as bracket clutch.

PROTECTION CAP

BAYONET BRACKET

Lets you quickly move the cable reel around the various workstations.

FIXING BRACKET

Can be rotated up to 90° per side and has 2 slotted holes for safe, easy installation. The bracket can be locked in place with a screw, making the cable reel fixed.

ELECTRIC COLLECTOR

Has double earth contact and can be easily replaced en bloc during maintenance.

STOP RACK

Makes it possible to lock the cable around every 0,5 m.

THERMAL PROTECTOR

CABLE GUIDE



Series
280


Type
**extension
cord**

Power supply
230 V SINGLE PHASE

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature -5 ÷ +40 °C



THERMAL PROTECTOR

standard

INPUT CABLE


1,2 m

COVER COLOURS

Shockproof plastic



Number of conductors 2



EN 61242

2014/35/EU 2014/30/EU
2011/65/EU

Number of conductors 3



EN 61242

2014/35/EU 2014/30/EU
2011/65/EU

Electrical protection rating

IP44 without cap
IP45 with cap

Warning, the system IP rating
is reduced according that of the
connected components.

Overall dimensions without bracket (mm)	Overall dimensions with bracket (mm)	Packaging (mm) W x D x H

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2210	2	2 x 1 - H05 VV-F	17 + 1 m	0,9 kW	1,4 kW	6,8 kg
3210	2	2 x 1 - H07 RN-F	12 + 1 m	0,9 kW	1,4 kW	6,9 kg
2215	2	2 x 1,5 - H05 VV-F	15 + 1 m	1,1 kW	2,3 kW	7,0 kg
2225	2	2 x 2,5 - H05 VV-F	10 + 1 m	1,9 kW	3,5 kW	7,1 kg
2310	3	3G x 1 - H05 VV-F	14 + 1 m	0,9 kW	1,4 kW	6,8 kg
3310	3	3G x 1 - H07 RN-F	10 + 1 m	0,9 kW	1,4 kW	7,0 kg
2315	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	7,2 kg
3315	3	3G x 1,5 - H07 RN-F	9 + 1 m	1,2 kW	2,3 kW	7,2 kg
2325	3	3G x 2,5 - H05 VV-F	9 + 1 m	1,9 kW	3,5 kW	7,3 kg
3325	3	3G x 2,5 - H07 RN-F	7 + 1 m	1,9 kW	3,5 kW	7,4 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2210F	2	2 x 1 - H05 VV-F	17 + 1 m	0,9 kW	1,4 kW	7,2 kg
3210F	2	2 x 1 - H07 RN-F	12 + 1 m	0,9 kW	1,4 kW	7,3 kg
2215F	2	2 x 1,5 - H05 VV-F	15 + 1 m	1,1 kW	2,3 kW	7,4 kg
2225F	2	2 x 2,5 - H05 VV-F	10 + 1 m	1,9 kW	3,5 kW	7,5 kg
2310F	3	3G x 1 - H05 VV-F	14 + 1 m	0,9 kW	1,4 kW	7,2 kg
3310F	3	3G x 1 - H07 RN-F	10 + 1 m	0,9 kW	1,4 kW	7,4 kg
2315F	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	7,6 kg
3315F	3	3G x 1,5 - H07 RN-F	9 + 1 m	1,2 kW	2,3 kW	7,6 kg
2325F	3	3G x 2,5 - H05 VV-F	9 + 1 m	1,9 kW	3,5 kW	7,7 kg
3325F	3	3G x 2,5 - H07 RN-F	7 + 1 m	1,9 kW	3,5 kW	7,8 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
280


Type
**extension
cord**

Power supply
400 V THREE PHASE

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature -5 ÷ +40 °C



THERMAL PROTECTOR

standard

INPUT CABLE

1,2 m

COVER COLOURS

Shockproof plastic



Number of conductors 4 and 5	Electrical protection rating
 EN 61242 2014/35/EU 2014/30/EU 2011/65/EU	IP44 without cap IP45 with cap Warning, the system IP rating is reduced according that of the connected component.

Overall dimensions without bracket (mm)	Overall dimensions with bracket (mm)	Packaging (mm) W x D x H
 40 175 492 387 318 94 130 94 331	 165 132 175 242 206 500 395 395	 440 x 195 x 485 No. 40 packages per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
4410	4	4G x 1 - H05 VV-F	11 + 1 m	1,1 kW	2,3 kW	6,9 kg
4415	4	4G x 1,5 - H05 VV-F	10 + 1 m	1,4 kW	4 kW	7,2 kg
5415	4	4G x 1,5 - H07 RN-F	8 + 1 m	1,4 kW	4 kW	7,4 kg
4425	4	4G x 2,5 - H05 VV-F	8 + 1 m	2 kW	6 kW	7,6 kg
5425	4	4G x 2,5 - H07 RN-F	5 + 1 m	2 kW	6 kW	7,5 kg
4510	5	5G x 1 - H05 VV-F	11 + 1 m	1 kW	2,3 kW	7,2 kg
4517	5	5G x 1,5 - H05 VV-F	8 + 1 m	1,4 kW	4 kW	7,3 kg
5515	5	5G x 1,5 - H07 RN-F	7 + 1 m	1,4 kW	4 kW	7,7 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
4410F	4	4G x 1 - H05 VV-F	11 + 1 m	1,1 kW	2,3 kW	7,3 kg
4415F	4	4G x 1,5 - H05 VV-F	10 + 1 m	1,4 kW	4 kW	7,6 kg
5415F	4	4G x 1,5 - H07 RN-F	8 + 1 m	1,4 kW	4 kW	7,8 kg
4425F	4	4G x 2,5 - H05 VV-F	8 + 1 m	2 kW	6 kW	8,0 kg
5425F	4	4G x 2,5 - H07 RN-F	5 + 1 m	2 kW	6 kW	7,9 kg
4510F	5	5G x 1 - H05 VV-F	11 + 1 m	1 kW	2,3 kW	7,6 kg
4517F	5	5G x 1,5 - H05 VV-F	8 + 1 m	1,4 kW	4 kW	7,7 kg
5515F	5	5G x 1,5 - H07 RN-F	7 + 1 m	1,4 kW	4 kW	8,1 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
280


Type
extension cord with Schuko IP44 socket and plug

Power supply
**230 V
SINGLE PHASE**

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature -5 ÷ +40 °C



THERMAL PROTECTOR

standard

INPUT CABLE

1,2 m

COVER COLOURS

Shockproof plastic



CABLE REEL

Number of conductors 3

Electrical protection rating



EN 61242

2014/35/EU 2014/30/EU
2011/65/EU

IP44 without cap
IP45 with cap


Warning, the system IP rating
is reduced according that of the
connected components.

SOCKETS AND PLUGS


Protection rating

IP44 Schuko sockets
IP44 Schuko plugs

Overall dimensions without bracket (mm)



Overall dimensions with bracket (mm)



Packaging (mm) W x D x H



440 x 195 x 485



No. 40 packages
per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2315S	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	6,9 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2315SF	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	7,3 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
280


Type
**extension cord with triple
Schuko IP44 socket and plug**

Power supply
**230 V
SINGLE PHASE**

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature -5 ÷ +40 °C



THERMAL PROTECTOR

standard

INPUT CABLE

1,2 m

COVER COLOURS

Shockproof plastic



CABLE REEL

Number of conductors 3

Electrical protection rating



EN 61242

2014/35/EU 2014/30/EU
2011/65/EU

IP44 without cap
IP45 with cap


Warning, the system IP rating
is reduced according that of the
connected components.

SOCKETS AND PLUGS


Protection rating

IP44 Schuko sockets
IP44 Schuko plugs

Overall dimensions without bracket (mm)



Overall dimensions with bracket (mm)



Packaging (mm) W x D x H



440 x 195 x 485



No. 40 packages
per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2315T	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	7,1 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Max. operating power (20 °C)		Weight
				Wound up	Unwound *	
2315TF	3	3G x 1,5 - H05 VV-F	14 + 1 m	1,2 kW	2,3 kW	7,5 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

* Values are with cable completely unwound.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
280


Type
**without transformer
fluorescent lamp**

Power supply
**230 V AC - 50 Hz
12 V DC - 24 V DC**

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature -5 ÷ +40 °C



230 V AC - 50 Hz
12 V - 24 V DC

230 V AC - 50 Hz
12 V - 24 V DC

LED = 3,6 W = 11 W = 50 W
600 LUMEN
6400-6500 °K (12 V e 230 V)
2700 °K (24 V)

THERMAL PROTECTOR

standard

INPUT CABLE

1,2 m

COVER COLOURS


Shockproof plastic



CABLE REEL

Number of conductors 2

Electrical protection rating



EN 61242 EN 60598

2014/35/EU 2014/30/EU
2011/65/EU UE 874/2012

IP44 without cap
IP45 with cap


Warning, the system IP rating
is reduced according that of the
connected components.

LAMP

Protection rating




IP65




IK09

Overall dimensions without bracket (mm)



Overall dimensions with bracket (mm)



Packaging (mm) W x D x H



440 x 195 x 485



No. 40 packages
per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210F23	2	2 x 1 - H05 RN-F	14 + 1 m	230 V AC - 50 Hz	F230	8,0 kg
2210F12	2	2 x 1 - H05 RN-F	14 + 1 m	12 V DC	F12	8,0 kg
2210F24	2	2 x 1 - H05 RN-F	14 + 1 m	24 V DC	F24	8,0 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210F23F	2	2 x 1 - H05 RN-F	14 + 1 m	230 V AC - 50 Hz	F230	8,4 kg
2210F12F	2	2 x 1 - H05 RN-F	14 + 1 m	12 V DC	F12	8,4 kg
2210F24F	2	2 x 1 - H05 RN-F	14 + 1 m	24 V DC	F24	8,4 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap

P/N with bayonet bracket

P/N with speed control and protection cap

P/N with speed control and bayonet bracket

P/N with protection cap and bayonet bracket

P/N complete



Series
280

Type
**without transformer
LED lamp**

Power supply
12 ÷ 24 V AC/DC

WITH SPRING



**FIXED AND
SWIVELLING**

°C
environment working
temperature -5 ÷ +40 °C



12 ÷ 24 V AC/DC

12 ÷ 24 V AC/DC

LED
3,6 W
360 LUMEN
5000 °K
11 W
50 W

THERMAL PROTECTOR
standard


INPUT CABLE
1,2 m

COVER COLOURS
Shockproof plastic



CABLE REEL

Number of conductors 2



EN 61242 EN 60598
2014/35/EU 2014/30/EU
2011/65/EU EU 874/2012



Electrical protection rating

IP44 without cap
IP45 with cap


Warning, the system IP rating
is reduced according that of the
connected components.

LAMP


Protection rating




Overall dimensions without bracket (mm)



Overall dimensions with bracket (mm)



Packaging (mm) W x D x H





P/N standard	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210L	3	3G x 1,5 - H05 VV-F	14 + 1 m	12 ÷ 24 V AC/DC	L1224	7,1 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210LF	3	3G x 1,5 - H05 VV-F	14 + 1 m	12 ÷ 24 V AC/DC	L1224	7,5 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
290


Type
**with transformer
with LED lamp**

Power supply
**230 V
SINGLE PHASE**

WITH SPRING



**FIXED AND
SWIVELLING**

 °C
environment working
temperature -5 ÷ +40 °C



12 ÷ 24 V AC/DC

230 V AC - 50 Hz

 LED
3,6 W  11 W  50 W
360 LUMEN
5000 °K


THERMAL PROTECTOR
standard

INPUT CABLE
1,2 m

COVER COLOURS
Shockproof plastic  

CABLE REEL

Number of conductors 2



EN 61242 EN 60598
EN 62471

2014/35/EU 2014/30/EU
2011/65/EU UE.874/2012


Electrical protection rating

IP44 without cap
IP45 with cap


Warning, the system IP rating
is reduced according that of the
connected components.

LAMP

Protection rating




IP65




IK09

Overall dimensions without bracket (mm)



Overall dimensions with bracket (mm)



Packaging (mm) W x D x H



440 x 195 x 485



No. 40 packages
per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210TL	2	2 x 1 - H05 RN-F	14 + 1 m	230 V AC - 50 Hz	L1224	9,0 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Input voltage	Lamp	Weight
2210TLF	2	2 x 1 - H05 RN-F	14 + 1 m	230 V AC - 50 Hz	L1224	9,4 kg

⚠ The codes above are supplied without accessories: protection cap - bayonet bracket.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
F12 - F24
F230 - L1224

Type
Fluorescent
and LED lamp

Power supply
12 ÷ 24 V AC/DC
230 V AC - 50 Hz

WITH SPRING



MAGNETIC SUPPORT
REPLACEABLE, TRANSPARENT
PROTECTION COVER
ANTI-SKIDDING GRIP
PROTECTION FUSE - 2 A
ADJUSTABLE HOOK
PROTECTED SWITCH

Series F12 - F24	Series F230	Series L1224
 EN 60598-1 EN 60598-2-8 2014/35/EU 2014/30/EU 2011/65/EU EU 874/2012	 EN 60598-1 EN 60598-2-8 2014/35/EU 2014/30/EU 2011/65/EU EU 874/2012	 EN 60598-1 EN 60598-2-8 CEI.EN.62471 2014/35/EU 2014/30/EU 2011/65/EU EU 874/2012

Protection rating	Overall dimensions (mm)	Packaging (mm) W x D x H
 IP 65 IK 09		 525 x 135 x 80 No. 40 packages per pallet

(W: width - D: depth - H: height)




PORTABLE FLUORESCENT LAMP series F12 - F24 - F230


Lamp code	Power supply voltage	Lamp connection	Max. power	Lamp protection rating	Bulb supplied	Weight
F12	12 V DC	E27	11 W	IP65	P/N 728002	0,6 kg
F24	24 V DC	E27	11 W	IP65	P/N 728003	0,6 kg
F230	230 V AC - 50 Hz	E27	11 W	IP65	P/N 728001	0,6 kg

⚠ The codes above refer to the lamp supplied without cable.

⚠ All models shown can be supplied with energy efficiency class B, A and A + bulbs as per EU regulation 874/2012. Fluorescent bulbs can be replaced as long as the same energy efficiency class is used.



P/N 728002 Bulb 11 W 12 V DC
P/N 728003 Bulb 11 W 24 V DC
P/N 728001 Bulb 11 W 230 V AC - 50 Hz




Power the cable reel only with the correct voltage for the lamp. Use with any other voltage will irreparably damage the lamp, and will void any warranty.

PORTABLE LED LAMP series L1224

Lamp code	Power supply voltage	No. of LEDs	LED power module	Lamp protection rating	LED module	Weight
L1224	12 ÷ 24 V AC/DC	12	3,6 W	IP65	P/N 728005	0,6 kg

⚠ All models shown can be supplied with energy efficiency class B, A and A + bulbs as per EU regulation 874/2012.



P/N 728005
 LED module, consisting of 12 LEDs, 0.3 W each. The LED modules cannot be replaced with others available on the market.



Power the cable reel only with the correct voltage for the lamp. Use with any other voltage will irreparably damage the lamp, and will void any warranty.






Series
280

Type
EARTHING

WITH SPRING



**FIXED AND
SWIVELLING**



environment working
temperature $-5 \div +40^{\circ}\text{C}$

INPUT CABLE

1,2 m

COVER COLOURS

Shockproof plastic



CABLE REEL

Number of conductors 1	Electrical protection rating
CE EN 61242 2014/35/EU 2014/30/EU 2011/65/EU	IP44 without cap IP45 with cap Warning, the system IP rating is reduced according that of the connected components.

Overall dimensions without bracket (mm)	Overall dimensions with bracket (mm)	Packaging (mm) W x D x H
		440 x 195 x 485 No. 40 packages per pallet

(W: width - D: depth - H: height)



P/N standard	Number of conductors	Type of cable	Cable length	Earthing clamp		Weight
				P/N	Ampere	
1065	1	1 x 6 - H07 V-K	15 + 1 m	-	-	6,7 kg
1161	1	1 x 16 - H07 V-K	10 + 1 m	-	-	5,0 kg
1065P	1	1 x 6 - H07 V-K	15 + 1 m	735112	50	6,8 kg
1161P	1	1 x 16 - H07 V-K	10 + 1 m	735111	100	7,5 kg
1064P	1	1 x 6 - PUR	14,5 m	explosion-proof	10	9,0 kg

△ The codes above are supplied without accessories: protection cap - bayonet bracket.

SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.



P/N with speed control	Number of conductors	Type of cable	Cable length	Earthing clamp		Weight
				P/N	Ampere	
1065F	1	1 x 6 - H07 V-K	15 + 1 m	-	-	7,1 kg
1161F	1	1 x 16 - H07 V-K	10 + 1 m	-	-	5,4 kg
1065PF	1	1 x 6 - H07 V-K	15 + 1 m	735112	50	7,2 kg
1161PF	1	1 x 16 - H07 V-K	10 + 1 m	735111	100	7,9 kg
1064PF	1	1 x 6 - PUR	14,5 m	explosion-proof	10	9,4 kg

△ The codes above are supplied without accessories: protection cap - bayonet bracket.

ACCESSORIES FOR ELECTRIC CABLE REELS

P/N 728115

Protection cap, in oil resistant rubber, useful to protect against accidental entry of water or foreign objects into the cable reel.



P/N 89003

Bayonet bracket, lets you easily move the cable reel within the various workstations.



EXAMPLES OF ELECTRIC CABLE REELS



P/N with protection cap



P/N with bayonet bracket



P/N with speed control and protection cap



P/N with speed control and bayonet bracket



P/N with protection cap and bayonet bracket



P/N complete



Series
350

Type
EARTHING

WITH SPRING



°C
environment working
temperature -5 ÷ +40 °C

In accordance with directive



Overall dimensions (mm)			Packaging (mm) W x D x H	
				390 x 188 x 403
				No. 36 packages per pallet

COVER COLOURS


Shockproof plastic



P/N standard	Type of cable	Cable conductor material	Cable conductor insulation	Cable length (m)	Earthing clamp		Weight
					P/N	Ampere	
735000	without cable	cable capacity max. 30 m - section 16 mm ²			-	-	12,3 kg
735131.60141	1 x 6	copper	PUR	14,5 m	explosion-proof	10	14,1 kg
735131.60261	1 x 6	copper	PUR	26 m	explosion-proof	10	22,3 kg
735131.60152	1 x 6	copper	PUR	15 m	735112	50	13,6 kg
735131.60252	1 x 6	copper	PUR	25 m	735112	50	14,7 kg
735141.60152	1 x 7	steel	PVC	15 m	735112	50	13,2 kg
735141.60252	1 x 7	steel	PVC	25 m	735112	50	14,0 kg



TECHNICAL CHARACTERISTICS



ACCESSORIES FOR EARTHING CABLE REELS

P/N 735111
Earthing clamp 100 A.



P/N 735112
Earthing clamp 50 A.



EXPLOSION-PROOF earthing clamp 10 A with cable measuring from 14,5 m or from 26 m. For information, contact our offices.



ARTICLES INDEX

P/N	page
1064P	167
1064PF	167
1065	167
1065F	167
1065P	167
1065PF	167
1161	167
1161F	167
1161P	167
1161PF	167
2210	151
2210F	151
2210F12	159
2210F12F	159
2210F23	159
2210F23F	159
2210F24	159
2210F24F	159
2210L	161
2210LF	161
2210TL	163
2210TLF	163
2215	151
2215F	151
2225	151
2225F	151
2310	151
2310F	151
2315	151
2315F	151
2315S	155
2315SF	155
2315T	157
2315TF	157
2325	151
2325F	151
236530.100	117
236530.200	117
236530.300	117
236530.350	117
236540.100	117
236540.105	117
236540.200	117
236540.205	117
236540.300	117
236540.350	117
236560.100	117
236560.105	117
236560.200	117
236560.205	117
236560.300	117
236560.350	117
246532.100	119
246534.200	119
246534.300	119
246534.350	119
246542.100	119
246542.105	119
246544.200	119
246544.205	119
246544.300	119
246544.350	119
246562.100	119
246562.105	119
246564.200	119
246564.205	119
246564.300	119
246564.350	119

P/N	page
256535.200	119
256535.300	119
256535.350	119
256545.200	119
256545.205	119
256545.300	119
256545.350	119
256565.200	119
256565.205	119
256565.300	119
256565.350	119
3210	151
3210F	151
3310	151
3310F	151
33114	145
33116	145
33117	145
33118	145
33119	145
33128	145
33129	145
33130	145
33131	145
33132	145
33133	145
3315	151
3315F	151
3325	151
3325F	151
33270	145
33271	145
33272	145
33273	145
33274	145
38071	145
38072	145
38073	145
38074	145
38120	145
38121	145
38122	145
38123	145
38124	145
38125	145
4410	153
4410F	153
4415	153
4415F	153
4425	153
4425F	153
4510	153
4510F	153
4517	153
4517F	153
5415	153
5415F	153
5425	153
5425F	153
5515	153
5515F	153
66891	145
66892	145
66893	145
728001	165
728002	165
728003	165
728005	165

P/N	page
728115	151-153 155-157 159-161 163-167
735000	168
735111	169
735112	169
735131.60141	168
735131.60152	168
735131.60252	168
735131.60261	168
735141.60152	168
735141.60252	168
74300.100	93
74300.200	97
74300.250	97
74300.300	97
74300.350	97
74300.400	101
74300.450	101
74300.500	105
74300.600	109
743001	120
743004	120
74301	120
74302	120
74305.100	93
74305.200	97
74305.300	97
74305.350	97
74305.400	101
74305.500	105
74305.600	109
74320.100	95
74320.150	95
74320.500	107
74320.600	111
74325.100	95
74325.500	107
74325.600	111
74340.200	99-103
74340.250	99
74340.300	99
74340.350	99
743401	120
743404	120
74345.200	99-103
74345.300	99
74345.350	99
74350.200	99
74350.300	99
74350.350	99
743501	120
743504	120
7522001.100	93-109
7522001.150	93
7522001.200	97
7522001.250	97
7522001.300	97
7522001.400	101
7522001.450	101
75300.100	93
75300.150	93-109
75300.200	97
75300.300	97
75300.350	97
75300.400	101
75300.500	105
753001	120

P/N	page
753004	120
75320.100	95
75320.150	95-111
75320.500	107
7532001.100	93-109
7532001.150	93
7532001.200	97
7532001.250	97
7532001.300	97
7532001.400	101
7532001.450	101
75340.200	99-103
75340.300	99
75340.350	99
753401	120
753404	120
75350.200	99
75350.300	99
75350.350	99
753501	120
753504	120
75400.100	93-109
75400.105	93
75400.200	97
75400.205	97
75400.300	97
75400.350	97
75400.400	101
75400.405	101
75400.500	105
754001	120
75420.100	95-111
75420.105	95
75420.500	107
75440.200	99-103
75440.205	99-103
75440.300	99
75440.350	99
754401	120
75450.200	99
75450.205	99
754501	120
7552001.100	93-109
7552001.150	93
7552001.200	97
7552001.250	97
7552001.300	97
7552001.400	101
7552001.450	101
75600.100	93-109
75600.106	93
75600.200	97
75600.206	97
75600.300	97
75600.350	97
75600.400	101
75600.406	101
75600.500	105
756001	120
75620.100	95-111
75620.106	95
75620.500	107
7562001.100	93-109
7562001.150	93
7562001.200	97
7562001.250	97
7562001.300	97
7562001.400	101

P/N	page
7562001.450	101
75640.200	99-103
75640.206	99-103
75640.300	99
75640.350	99
756401	120
75650.200	99
75650.206	99
756501	120
77/12775	121-138
77/12775B	121-138
77/14175	121-138
77/14175B	121-138
77/15575	121-138
77/15575B	121-138
77/16975	121-138
77/16975B	121-138
77/22775	121-138
77/22775B	121-138
77/24175	121-138
77/24175B	121-138
77/25575	121-138
77/25575B	121-138
77/26975	121-138
77/26975B	121-138
77/2F	121-138
77/32775	121-138
77/32775B	121-138
77/34175	121-138
77/34175B	121-138
77/35575	121-138
77/35575B	121-138
77/36975	121-138
77/36975B	121-138
77/3F	121-138
77/44312	78
77/45312	78
77/45401	78
77/45412	78
77/45601	78
77/45612	78
77/4F	121-138
7721001.100	93-109
7721001.400	101
7721301.100	127-137
7721301.400	133
7721601.100	127-137
7721601.400	133
7721702.100	127-137
7721702.400	133
7721801.100	127-137
7721801.400	133
7721901.100	127-137
7721901.400	133
7724001.200	99
7724301.200	131
7724601.200	131
7724702.200	131
7724801.200	131
7724901.200	131
7725001.200	99
7725301.200	131
7725601.200	131
7725702.200	131
7725801.200	131
7725901.200	131
7726601.200	129
7726702.200	129

P/N	page
7741001.100	93-109
7741001.400	101
7741301.100	127-137
7741301.400	133
7741601.100	127-137
7741601.400	133
7741702.100	127-137
7741702.400	133
7741801.100	127-137
7741801.400	133
7741901.100	127-137
7741901.400	133
7744001.200	99
7744301.200	131
7744601.200	131
7744702.200	131
7744801.200	131
7744901.200	131
7745001.200	99
7745301.200	131
7745601.200	131
7745702.200	131
7745801.200	131
7745901.200	131
7746601.200	129
7746901.200	129
7751001.100	93-109
7751001.400	101
7751301.100	127-137
7751301.400	133
7751601.100	127-137
7751601.400	133
7751702.100	127-137
7751702.400	133
7751801.100	127-137
7751801.400	133
7751901.100	127-137
7751901.400	133
7754301.200	131
7754601.200	131
7754702.200	131
7754801.200	131
7754901.200	131
7755001.200	99
7755301.200	131
7755601.200	131
7755702.200	131
7755801.200	131
7755901.200	131
7756601.200	129
7756702.200	129
7771001.100	93-109
7771001.400	101
7771301.100	127-137
7771301.400	133
7771601.100	127-137
7771601.400	133
7771702.100	127-137
7771702.400	133
7771801.100	127-137
7771801.400	133
7771901.100	127-137
7771901.400	133
7774001.200	99
7774301.200	131
7774601.200	131
7774702.200	131
7774801.200	131

P/N	page
7774901.200	131
7775001.200	99
7775301.200	131
7775601.200	131
7775702.200	131
7775801.200	131
7775901.200	131
79/44312	79
79/45312	79
79/45401	79
79/45412	79
79/45601	79
79/45601	79
79/45612	79
8288.100	67
8288.102	67
8288.103	67
8288.104	67
8288.105	67
8290.100	19
8290.101	19
8290.104	19
8292.100	21
8292.101	21
8292.104	21
8328.100	67
8328.102	67
8328.103	67
8328.104	67
8328.105	67
8330.100	19
8330.101	19
8330.200	23
8330.201	23
8330.300	27
8330.301	27
8330.350	31
8330.400	37
8330.402	37
8330.500	41
8330.501	41
8330.800	51
8330.801	51
8330.802	51
8332.100	21
8332.101	21
8332.201	25
8332.300	29
8332.301	29
8332.350	33
8332.400	25
8333.101	21
8333.202	25
8333.301	29
8378.100	67
8378.102	67
8378.103	67
8378.104	67
8378.105	67
8380.100	19
8380.102	19
8380.200	23
8380.202	23
8380.300	27
8380.302	27
8380.350	31
8380.352	31
8380.400	37

P/N	page
8380.401	37
8380.402	37
8380.500	41
8380.501	41
8380.502	41
8382.100	21
8382.102	21
8382.200	25-39
8382.202	25
8382.300	29
8382.302	29
8382.350	33
8382.352	33
8382.500	43
8383.201	25
8383.301	29
8390.100	19
8390.102	19
8390.200	23
8390.202	23
8390.300	27
8390.302	27
8390.350	31
8390.352	31
8390.400	37
8390.401	37
8390.402	37
8390.500	41
8390.501	41
8390.502	41
8390.800	51
8390.801	51
8390.802	51
8392.100	21
8392.102	21
8392.200	25-39
8392.202	25
8392.300	29
8392.302	29
8392.350	33
8392.352	33
8392.500	43
8393.201	25
8393.301	29
8420.100	19
8420.101	19
8420.102	19
8420.103	19
8420.104	19
8420.200	23
8420.201	23
8420.202	23
8420.300	27
8420.301	27
8420.302	27
8420.350	31
8420.354	31
8420.400	37
8420.401	37
8420.401/AS	37
8420.402	37
8420.500	41
8420.501	41
8420.502	41
8420.505	41
8420.506	41
8422.100	21
8422.101	21

P/N	page
8422.102	21
8422.103	21
8422.104	21
8422.201	25
8422.202	25
8422.301	29
8422.302	29
8422.354	33
8422.500	43
8423.202	25
8423.302	29
8423.354	33
8424.200	25-39
8424.300	29
8424.350	33
8430.100	19-67
8430.1000	55
8430.101	19
8430.102	19
8430.103	19
8430.104	19
8430.150	19-45
8430.200	23
8430.201	23
8430.202	23
8430.250	23
8430.300	27
8430.3000	55
8430.301	27
8430.302	27
8430.350	31
8430.354	31
8430.400	37
8430.400/AS	37
8430.4000	55
8430.401	37
8430.401/AS	37
8430.402	37
8430.415	37
8430.415/AS	37
8430.416	37
8430.417	37
8430.450	37
8430.452/AS	37
8430.500	41
8430.5000	55
8430.501	41
8430.502	41
8430.505	41
8430.506	41
8430.5500	55
8430.600	45
8430.601	45
8430.602	45
8430.700	53
8430.701	53
8430.702	53
8430.800	51
8430.802	51
8430.804	51
843001	80-120
843002	80-120
843005	81
843006	81
843011	82
843012	82
843013	82
8432.100	21

P/N	page
8432.101	21
8432.102	21
8432.103	21
8432.104	21
8432.150	21
8432.201	25
8432.202	25
8432.301	29
8432.302	29
8432.354	33
8432.500	43
8433.102	21
8433.202	25
8433.302	29
8433.354	33
8434.200	25-39
8434.250	25-39-49
8434.300	29
8434.350	33
8435.200	35
8435.300	35
8435.350	35
8436.200	49
8436.250	49
8436.251	49
8436.252	49
8438.101	67
8438.102	67
8440.100	61
8440.101	61
8440.102	61
8440.103	61
8440.104	61
8440.400	61
8440.401	61
8440.401/AS	61
8440.402	61
8440.500	61
8440.501	61
8440.502	61
8440.505	61
8440.506	61
8450.100	61
8450.101	61
8450.102	61
8450.103	61
8450.104	61
8450.400	61
8450.401	61
8450.401/AS	61
8450.402	61
8450.500	61
8450.501	61
8450.502	61
8450.505	61
8450.506	61
845001	80
845005	81
8520.100	19
8520.101	19
8520.102	19
8520.200	23
8520.201	23
8520.300	27
8520.301	27
8520.302	27
8520.350	31
8520.352	31

ARTICLES INDEX

P/N	page
8520.400	37
8520.401	37
8520.402	37
8520.500	41
8520.501	41
8520.502	41
8522.100	21
8522.101	21
8522.102	21
8522.201	25
8522.301	29
8522.302	29
8522.352	33
8522.500	43
8523.202	25
8523.302	29
8523.352	33
8524.200	25-39
8524.300	29
8524.350	33
8530.100	19
8530.1000	55
8530.101	19
8530.102	19
8530.150	19-45
8530.200	23
8530.201	23
8530.300	27
8530.3000	55
8530.301	27
8530.302	27
8530.350	31
8530.352	31
8530.400	37
8530.4000	55
8530.401	37
8530.402	37
8530.415	37
8530.416	37
8530.500	41
8530.5000	55
8530.501	41
8530.502	41
8530.5500	55
8530.603	45
8530.604	45
8530.700	53
8530.701	53
8530.702	53
8530.703	53
8530.704	53
8530.705	53
8530.800	51
8530.802	51
8530.804	51
853001	80-120
853002	80-120
853005	81
853006	81
8532.100	21
8532.101	21
8532.102	21
8532.150	21-47
8532.201	25
8532.301	29
8532.302	29
8532.352	33
8532.500	43

P/N	page
8533.102	21
8533.202	25
8533.302	29
8533.352	33
8534.200	25-39
8534.250	25-39-49
8534.300	29
8534.350	33
8534.550	33
8535.200	35
8535.300	35
8535.350	35
8537.200	49
8537.251	49
8537.252	49
8540.100	19-45
8540.1000	55
8540.101	19
8540.102	19
8540.103	19
8540.105	19
8540.106	19
8540.200	23
8540.202	23
8540.203	23
8540.300	27
8540.3000	55
8540.301	27
8540.350	31
8540.400	37
8540.4000	55
8540.405	37
8540.406	37
8540.411	37
8540.412	37
8540.413	37
8540.414	37
8540.500	41
8540.5000	55
8540.501	41
8540.5500	55
8540.601	45
8540.602	45
8540.603	45
8540.700	53
8540.701	53
8540.702	53
8540.704	53
8540.705	53
8540.707	53
8540.709	53
8540.800	51
8540.802	51
854001	80-120
854002	80-120
854005	81
854006	81
854007	81
8542.100	21-47
8542.101	21
8542.102	21
8542.103	21
8542.105	21
8542.106	21
8542.202	25
8542.203	25
8542.301	29
8542.601	47

P/N	page
8542.602	47
8542.603	47
8543.102	21
8543.103	21
8543.106	21
8543.202	25
8543.301	29
8544.200	25-39
8544.205	25-39
8544.300	29
8544.350	33
8544.550	33
8545.200	35
8545.205	35
8550.100	19
8550.101	19
8550.102	19
8550.103	19
8550.105	19
8550.106	19
8550.200	23
8550.202	23
8550.203	23
8550.300	27
8550.301	27
8550.350	31
8550.400	37
8550.405	37
8550.406	37
8550.411	37
8550.412	37
8550.413	37
8550.500	41
8550.501	41
8552.100	21
8552.101	21
8552.102	21
8552.103	21
8552.105	21
8552.106	21
8552.202	25
8552.203	25
8552.301	29
8553.202	25
8553.301	29
8554.200	25-39
8554.205	25-39
8554.300	29
8554.350	33
8560.100	19-45
8560.101	19
8560.103	19
8560.104	19
8560.105	19
8560.106	19
8560.200	23
8560.205	23
8560.300	27
8560.301	27
8560.302	27
8560.350	31
8560.400	37
8560.603	45
8560.604	45
8560.605	45
856001	80-120
856002	80-120
8562.100	21-47

P/N	page
8562.101	21
8562.103	21
8562.104	21
8562.105	21
8562.106	21
8562.205	25
8562.301	29
8562.302	29
8562.603	47
8562.604	47
8562.605	47
8563.103	21
8563.105	21
8564.200	25
8564.206	25
8564.300	29
8564.350	33
8565.200	35
8565.206	35
8617.100	127
8617.200	129
8617.400	133
8617.500	135
8617.600	137
8618.100	127-137
8618.200	129
8618.400	133
8618.500	135
8637.100	127
8637.200	129
8637.400	133
8637.500	135
8637.600	137
8638.100	127-137
8638.200	129
8638.400	133
8638.500	135
88630	83
88650	83-120
88651	83-120
89001	83
89002	83
89003	83 151-153 155-157 159-161 163-167
89005	83
89010	71
89011	71
89109	71
89110	71
92438.101	67
92438.102	67
92608.101	75
92608.102	75
92708.101	75
92708.102	75
92808.101	71
92808.102	71
92808.105	71
92818.101	71
92818.102	71
92818.105	71
92848.101	71
92848.102	71
92848.105	71
92858.101	71
92858.102	71

P/N	page
92858.105	71
93108.102	75
93108.103	75
93108.104	75
93108.105	75
93108.106	75
93208.102	75
93208.103	75
93208.104	75
93208.105	75
93208.106	75
9430.100	19
9430.101	19
9430.102	19
9430.103	19
9430.104	19
9430.200	23
9430.201	23
9430.202	23
9430.300	27
9430.301	27
9430.302	27
9430.400	37
9430.400/AS	37
9430.401	37
9430.402	37
9430.415	37
9430.416	37
9430.417	37
9430.500	41
9430.501	41
9430.502	41
9430.505	41
9430.506	41
9430.600	45
9430.601	45
9430.602	45
9431.202	23
9431.302	27
9432.100	21
9432.101	21
9432.102	21
9432.103	21
9432.104	21
9432.201	25
9432.202	25
9432.301	29
9432.302	29
9432.353	33
9432.354	33
9432.401	39
9432.402	39
9432.500	43
9432.501	43
9432.502	43
9432.505	43
9432.506	43
9433.102	21
9433.202	25
9433.302	29
9434.200	25-39
9434.300	29
9434.350	33
9436.200	49
9436.201	49
9437.200	49
9437.201	49
9450.100	61

P/N	page	P/N	page	P/N	page	P/N	page	P/N	page
9450.101	61	975.1010	144	995.217	141	996.125	141	997.3330	143
9450.102	61	975.1015	144	995.218	141	996.130	141	997.3340	143
9450.103	61	975.1018	144	995.301	140	996.210	141	997.420	142
9450.104	61	975.1027	144	995.312	143	996.215	141	997.806	140
9450.400	61	975.1030	144	995.313	142	996.220	141	997.808	143
9450.401	61	975.902	140	995.317	143	996.225	141	997.812	143
9450.402	61	975.915	144	995.318	142	996.230	141	997.815	143
9450.500	61	975.920	144	995.412	142	996.301	140	997.820	143
9450.501	61	975.927	144	995.506	140	996.3015	140	997.840	143
9450.502	61	976.102	140	995.512	142	996.302	140	998.106	140
9450.505	61	976.108	141	995.518	142	996.304	140	998.115	141
9450.506	61	976.110	141	995.520	142	996.305	140	998.120	141
971.010	141	976.111	141	995.525	142	996.306	140	998.130	141
971.011	141	976.112	141	995.530	142	996.310	143	998.215	141
971.015	141	976.114	141	995.540	142	996.311	142	998.220	141
971.102	140	976.115	141	995.550	142	996.315	143	998.230	141
971.111	141	987.205	140	995.606	140	996.316	142	998.305	140
971.115	141	987.206	140	995.618	142	996.320	143	998.315	141
971.118	141	987.208	144	995.625	142	996.321	142	998.330	141
971.120	141	987.210	144	995.630	142	996.325	143	998.3301	140
972.102	140	987.215	144	995.701	140	996.330	143	998.3302	140
972.113	141	993.201	140	995.702	140	996.406	140	998.3306	140
972.115	141	993.202	140	995.706	140	996.415	142	998.3310	142
972.120	141	993.215	141	995.710	143	996.425	142	998.3315	142
973.913	144	993.504	140	995.715	143	997.115	141	998.3320	142
973.917	144	993.511	143	995.720	143	997.120	141	998.3330	142
973.920	144	993.512	143	995.725	143	997.130	141	998.406	140
973.925	144	993.516	143	995.730	143	997.140	141	998.806	140
973.930	144	993.518	143	995.806	140	997.215	141	998.808	143
974.1008	144	994.512	142	995.815	142	997.220	141	998.815	143
974.1015	144	994.517	142	995.820	142	997.230	141	998.820	143
974.1020	144	994.612	142	995.825	142	997.240	141	998.830	143
974.1028	144	994.717	142	995.906	140	997.320	142	999.3310	143
974.912	144	995.106	140	995.915	142	997.3305	140	999.810	143
974.915	144	995.112	141	995.925	142	997.3306	140	F12	165
974.920	144	995.206	140	996.106	140	997.3308	143	F230	165
974.925	144	995.210	141	996.110	141	997.3312	143	F24	165
974.930	144	995.211	141	996.116	141	997.3315	143	L1224	165
975.1002	140	995.212	141	996.120	141	997.3320	143		

R A A S M

