



Product catalogue

Pneumatic Applicators


MADE IN ITALY



1-components 1 - 15 pag.
2-components 16 - 28 pag.

CSG SERIES

PROFESSIONAL


Professional pneumatic gun for sealants and adhesives, such as silicones, mastics, glues and others products packed in standard soft - pack (sausage shaped) or in cartridge.

P.M.T. designed and manufactured the CSG with high quality materials, bestwing the item HIGH RESISTANCE to any use and EXTREME LIGHTNESS at the same time and thoroughly complying to the legal and ecological European legislations, in order to guarantee not only high quality professional standards, but also a total respect of the surrounding environment as well as asbsolute safety in the work place.


In addition, the tests carried out on each single piece ensure top reliability and duration over time.




Legenda packaging




Neutral packaging PAP20 with generic label




Neutral packaging PAP20, with customized label




Customized packaging PAP20, with layout with your logo




Customized packaging PAP20 with P.M.T. layout




Product weight



Multiple Packaging PAP20



PE-LD04 bag, with generic label



PE-LD04 bag, with customized label



Plastic case PE-HD2 customized with logo P.M.T.



Plastic case PE-HD2 customizable through process of laser etching or label

GENERAL SPECIFICATIONS FOR THE SINGLE COMPONENT APPLICATOR

1. Tube, Ringnuts and the main body are machined from solid aluminium, providing high resistance over time, and an overall long durability of the tool. The new air valve ensures the maximum accuracy during dispensing operation and a life-long durability of its internal parts.
2. TUBE HOLDER produced in PA6 plastic to guarantee the lightness of the applicator. A metal hook is provided to give the possibility to hang the applicator for a less heavy use.
3. ERGONOMIC HANDLE place on the device barycentre, to ensure perfect balancing and ease of use, with a single hand too.
4. QUICK RELEASE VALVE to ensure the highest precision. Upon release of the trigger, air is instantly emitted and product extrusion immediately stopped, therefore preventing material being applied outside the desired area, dripping and imperfections during extrusion.
5. MICRO PRESSURE REGULATOR to adjust and stabilise pressure in order to guarantee constant force and speed (only for RC/NE - in all others it is already included). Pressure can be adjusted from 2 to 10 bar max.



ACCESSORIES

6. PRESSURE GAUGE to measure the air pressure and enable better extruded product adjustment.
7. "L" SHAPED SWIVEL CONNECTOR. More comfortable gun handling provided by the swivel connector, with displaceable supply pipe to user's needs. Thanks to the Swivel connector, the tube passes over the arm, (6A) and does not disturb the part to be treated (optional).



1-components Pneumatic Applicators



RC/NE

Pneumatic applicator for the extrusion of sealant products and adhesives, packed in standard plastic cartridges.





MICRO PRESSURE REDUCER AVAILABLE ALSO
WITH A PRESSURE GAUGE
OPTIONAL NOT INCLUDED

WAY OF EXTRUSION	PNEUMATIC
ART. CODE	1020146
Net weight	350 g.
Work pressure	0-10 bar
Tube lenght	210 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
OPTIONAL	
Micro Pressure reducer	3080114
Pressure Gauge Code	1090091

PACKAGING

Multiple packing			
	56x58x35 cm	20 pz	7 Kg
Single packing			

CARTRIDGE



For the use of aluminum cartridges it is advisable to use the applicator CSG II 450 / CSG II 340 T.

1-components Pneumatic Applicators



CSG II 210

Professional Pneumatic applicator for the extrusion of sealants and adhesives, packed in standard plastic or aluminium cartridges.

WAY OF EXTRUSION	PNEUMATIC
ART. CODE	1020194
Net weight	867 g.
Work pressure	0-10 bar
Tube lenght	220 mm
Max force	200 Kgf (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)

PACKAGING

Multiple packing			
	55x32x44 cm	10 pz	11,80 Kg
Single packing			

CARTRIDGE

--	--

For the use of aluminum cartridges it is advisable to use the applicator CSG II 450 / CSG II 340 T.

1-components Pneumatic Applicators



CSG II 245






Professional Pneumatic applicator for the extrusion of sealants and adhesives, packed in standard plastic or aluminium Cartridges, or soft packs.




ADAPTER FOR CARTRIDGES, INCLUDED IN THE PACKAGE

WAY OF EXTRUSION	MECHANICAL (by means of a piston) for soft-pack PNEUMATIC for Cartridges
ART. CODE	1020184
Net weight	1.072 g.
Work pressure	0-10 bar
Tube lenght	263 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)


PACKAGING

Multiple packing			
	42x49x45 cm	10 pz	16,40 Kg
Single packing			

CARTRIDGE



SOFT-PACK



For the use of aluminum cartridges it is advisable to use the applicator CSG II 450 / CSG II 340 T.

1-components Pneumatic Applicators








CSG II 270



Professional Pneumatic applicator for the extrusion of sealants and adhesives, packed in standard soft-packs.

WAY OF EXTRUSION	MECHANICAL (by means of a piston)
ART. CODE	1020185
Net weight	1.072 g.
Work pressure	0-10 bar
Tube lenght	263 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)

PACKAGING

Multiple packing			
	50x42x61 cm	10 pz	15,20 Kg
Single packing			

SOFT-PACK



1-components Pneumatic Applicators




CSG II 340 T

Pneumatic applicator for the extrusion of sealants and adhesives, packed in standard plastic or aluminium cartridges and soft packs with a telescopic piston.

Thanks to the mechanical piston, the product does not come into contact with pressurised air, making it particularly suitable for use with aluminium cartridges.






Moreover, this device is -100mm shorter and lighter than our other CSG II 450.




TELESCOPIC PISTON

WAY OF EXTRUSION	MECHANICAL (by means of a telescopic piston)
ART. CODE	1020348
Net weight	1.400 g
Work pressure	2-8 bar
Tube lenght	340 mm
Max force	70 Kgf (8 bar - 116 PSI) - 0,69 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)


PACKAGING

Multiple packing			
	59x36x64 cm	10 pz	20,80 Kg
Single packing			

CARTRIDGE



SOFT-PACK




1-components Pneumatic Applicators



CSG II 370






Professional Pneumatic applicator for the extrusion of sealers and adhesives, packed in standard plastic or aluminium cartridges, or soft-packs.




ADAPTER FOR CARTRIDGES. INCLUDED IN THE PACKAGE

WAY OF EXTRUSION	MECHANICAL (by means of a piston) for soft-pack PNEUMATIC for cartridge
ART. CODE	1020182
Net weight	1.252 g.
Work pressure	0-10 bar
Tube length	400 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)


PACKAGING

Multiple packing			
	59x36x64 cm	10 pz	18,70 Kg
Single packing			

CARTRIDGE



SOFT-PACK



For the use of aluminum cartridges it is advisable to use the applicator CSG II 450 / CSG II 340 T

1-components Pneumatic Applicators



CSG II 400




Professional pneumatic applicator for the extrusion of sealers and adhesives, packed in standard soft-packs.

WAY OF EXTRUSION	MECHANICAL (by means of a piston)
ART. CODE	1020181
Net weight	1.119 g.
Work pressure	0-10 bar
Tube lenght	400 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)

PACKAGING

Multiple packing			
	61x49x44 cm	10 pz	17,30 Kg
Single packing			

SOFT-PACK



1-components Pneumatic Applicators



CSG II 450

Professional Pneumatic applicator for the extrusion of sealers and adhesives, packed in standard cartridges (especially suitable for aluminum cartridges) or soft-packs.

Thanks to the mechanical piston the product is not in contact with air pressure.



METAL PISTON INSIDE THE APPLICATOR




PLASTIC ADAPTER INCLUDED FOR EXTRUDING SOFT PACKS

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020193
Net weight	1.416 g.
Work pressure	0-10 bar
Total Lenght	565 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)


PACKAGING

Multiple packing			
	42x49x61 cm	10 pz	19 Kg
Single packing			

CARTRIDGE



SOFT-PACK



1-components Pneumatic Applicators

CSG II MP 450

Professional pneumatic applicator for the extrusion of high viscosity sealers and adhesives, packed in standard cartridges (especially suitable for aluminum cartridges) or soft-packs.

Thanks to the piston single-stage the product is not in contact with air under pressure.

Dump valve integrated (dripless).

The CSG II MP 450 with pneumatic return is also available, upon request.




WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020214
Net weight	1.982 g.
Work pressure	0-10 bar
Total Length	565 mm
Max force	380 Kgf (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Without Pneumatic return.

PACKAGING


Single packing



CARTRIDGE



SOFT-PACK



1-components Pneumatic Applicators



CSG II MP 600

Professional Pneumatic applicator for the extrusion of high viscosity sealers and adhesives, packed in standard cartridges (especially suitable for aluminum cartridges) or soft-packs.

Thanks to the piston single-stage the product is not in contact with air pressure.

Dump valve integrated (dripless)

The CSG II MP 600 with pneumatic return is also available, upon request.




WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020334
Net weight	2.100 g.
Work pressure	0-10 bar
Total Length	820 mm
Max force	380 KgF (10 bar- 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Without Pneumatic return

PACKAGING


Single packing



CARTRIDGE



SOFT-PACK



1-components Pneumatic Applicators



CSG II 660

Pneumatic applicator for the extrusion of sealers and adhesives, packed in specific soft-packs.

Used especially in the nautical sector.



WAY OF EXTRUSION	MECHANICAL (by means of a piston)
ART. CODE	1020303
Net weight	1.500 g.
Work pressure	0-10 bar
Tube lenght	1150 mm
Max force	200 KgF (10 bar - 145 PSI)-1,961 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)

PACKAGING

Single packing



SOFT-PACK



Also available is the CSG II 1100 for extruding 1800 ml soft-pack.

1-components Pneumatic Applicators




CSG II FLOOR RAKE (OPTIONAL)



CSG II FLOOR

Professional Pneumatic applicator for the extrusion of sealers and adhesives on civilian or industrial large surfaces like airport pavimentation or wooden floors. It extrudes the products packed in 1800 ml soft-packs.

SPECIAL SUPPORT SYSTEM (OPTIONAL)




SPECIAL SUPPORT SYSTEM (not included)

Professional support system for CSG FLOOR, which is calibrated for the best comfort during the use by the operator, with our mechanical assistance system on the extrude surface. This system is designed to give the possibility to set-up and adjust the distance of the nozzle from the floor. Easy to move it thanks to the wheels, it represent the innovative way to glue any kind of floors.

WAY OF EXTRUSION	MECHANICAL (by means of a piston)
ART. CODE	1020076
Net weight	3.000 g.
Work pressure	0-10 bar
Tube lenght	1000 mm
Max force	250 KgF (8 bar - 116 PSI) 2,45 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless)

SOFT-PACK





2-components Pneumatic Applicators

In this second section of the catalogue, you will find an overview of our two-component applicators for the extrusion of high-viscosity sealants and adhesives, packaged in cartridges or bags.

Most two-component applicators can be supplied in MP (Medium Power) and P (Power) versions depending on the maximum force required. The main difference between MP (Medium Power) and P (Power) is the pushing force. The MP version has a 75 mm cylinder and can reach 3 kN, whereas the P version has a 96 mm cylinder and can reach 5 kN.

Our ***Made in Italy*** two-component pneumatic applicators are made of aluminium to guarantee high resistance and lightness. The cradles containing the cartridges are closed for maximum safety during extrusion. In the unlikely event of damage, our aluminium cradles can be easily repaired due to their modular construction.

All P.M.T. air guns have an integrated pressure reducer and are equipped with a quick release valve.

Our two-component applicators are normally sold with a pneumatic return.

To improve working comfort, either in a fixed position or in the assembly line, the applicators are equipped with a sturdy metal hook, so that the applicator can be hung while in use or attached to a tool balancer.

The ergonomically balanced handle offers comfortable handling.

They are widely used in various industries: automotive, construction, shipyards, assembly lines, body shops, glassworks and more.

2-components Pneumatic Applicators



CSG II BCX 50

Professional Pneumatic applicator for the extrusion of all types of products, high viscosity sealing and adhesive products, packed in side by side cartridges.

Thanks to the single-stage piston, the product does not come into contact with the air under pressure. Adapter included 1:1.





ADAPTER DETAIL 2:1 optional art. code 4021506

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020336
Net weight	1540 g.
Work pressure	0-10 bar
Tube lenght	240 mm
Max force	160 Kgf (8 bar - 116 PSI)- 1,569 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

2-components Pneumatic Applicators




CSG II MP BCX / 200

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 200 ml packed in side by side cartridges 200 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020346
Net weight	3.125 g
Work pressure	0-10 bar
Max force	380 kgf (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

2-components Pneumatic Applicators




CSG II MP BCX / 250

Professional pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 250 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020398
Net weight	3.800 g
Work pressure	0-10 bar
Max force	380 KgF (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



2-components Pneumatic Applicators








CSG II MP CTX/300

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in coaxial cartridges.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020287
Net weight	1.980 g
Work pressure	0-10 bar
Max force	380 KgF (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



COAXIAL

2-components Pneumatic Applicators



CSG II MP BCX/345


CSG II P BCX/345

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 345 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)	MECHANICAL (rod driven piston)
	CSG II MP BCX / 345	CSG II P BCX / 345
ART. CODE	1020240	1020337
Net weight	3.160 g	3.300 g
Work pressure	0-10 bar	0-10 bar
Total Length	570 mm	570 mm
Max force	380 Kgf (10 bar - 145 PSI) - 3,72 kN	600 Kgf (10 bar - 145 PSI) - 6 kN
Connection	1/4 male gas	1/4 male gas
Noise Level	<80 dBA	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



2-components Pneumatic Applicators



CSG II MP CTX / 400


CSG II P CTX / 400

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in coaxial cartridges.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)	MECHANICAL (rod driven piston)
	CSG II MP CTX / 400	CSG II P CTX / 400
ART. CODE	1020213	1020343
Net weight	3.390 g	3.910 g
Work pressure	0-10 bar	0-10 bar
Total Length	510 mm	510 mm
Max force	380 Kgf (10 bar - 145 PSI) - 3,72 kN	600 Kgf (10 bar - 145 PSI) - 5,88 kN
Connection	1/4 male gas	1/4 male gas
Noise Level	<80 dBA	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return	Pressure reducer integrated Integrated air discharge valve Pneumatic return

PACKAGING

Single packing



2-components Pneumatic Applicators





CSG II MP BCX/400

CSG II P BCX / 400

Professional Pneumatic applicator for the extrusion of all types of products, high viscosity sealing and adhesives products, packed in side by side cartridges of 400 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)	MECHANICAL (rod driven piston)
	CSG II MP BCX/400	CSG II P BCX/400
ART. CODE	1020344	1020345
Net weight	3.150 g	3.920 g.
Work pressure	0-10 bar	0-10 bar
Total Length	520 mm	520 mm
Max force	380 Kgf (10 bar - 145 PSI) - 3,72 kN	600 Kgf (10 bar - 145 PSI) - 6 kN
Connection	1/4 male gas	1/4 male gas
Noise Level	<80 dBA	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return
OPTIONAL		
Micro pressure reducer	3080114	3080114



SIDE BY SIDE

PACKAGING

Single packing



2-components Pneumatic Applicators




CSG II MP BCX/490

CSG II P BCX / 490

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 490 ml ratio 10:1.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)	MECHANICAL (rod driven piston)
	CSG II MP BCX/490	CSG II P BCX/490
ART. CODE	1020288	1020339
Net weight	3.650 g	4.260 g
Work pressure	0-10 bar	0-10 bar
Total Length	520 mm	520 mm
Max force	380 Kgf (10 bar - 145 PSI) - 3,72 kN	600 Kgf (10 bar - 145 PSI) - 5,88 kN
Connection	1/4 male gas	1/4 male gas
Noise Level	<80 dBA	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return



PACKAGING

Single packing



2-components Pneumatic Applicators






CSG II MP BCX / 585

Professional Pneumatic applicator with cradle with side lading for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 385- 400- 470 and 585 ml ratio 3:1.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020285
Net weight	3.600 g.
Work pressure	0-10 bar
Tube lenght	220 mm
Max force	380 KgF (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

2-components Pneumatic Applicators




CSG II MP BCX/600

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridge 600 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020202
Net weight	3.590 g.
Work pressure	0-10 bar
Tube lenght	220 mm
Max force	380 KgF (10 bar - 145 PSI) - 3,72 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



2-components Pneumatic Applicators




CSG II P BCX/825

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packaged in side by side cartridges of 825 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020401
Net weight	4.665 g.
Work pressure	0-10 bar
Max force	600 Kgf (10 bar - 145 PSI) - 5,88 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

2-components Pneumatic Applicators






CSG II P BCX/1200

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packaged in side by side cartridges of 900/1050/1200 ml 2:1/2:1/2,5:1.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020397
Net weight	4.840 g.
Work pressure	0-10 bar
Max force	600 Kgf (10 bar - 145 PSI) - 5,88 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

2-components Pneumatic Applicators




CSG II P BCX / 1500

Professional Pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges of 1.500 ml.

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
ART. CODE	1020349
Net weight	5.430 g
Work pressure	0-10 bar
Max force	600 Kgf (10 bar - 145 PSI) - 5,88 kN
Connection	1/4 male gas
Noise Level	<80 dBA
Features	Pressure reducer integrated Dump valve integrated (dripless) Pneumatic return

PACKAGING

Single packing



SIDE BY SIDE

Nozzle available for soft-pack and cartridges

For the extrusion of product contained in soft-pack and by using the following nozzles, use:

THE ADAPTER FOR SOFT-PACK
Cod. 3080010



NOZZLE
for soft-pack



3080036

ADAPTER
for soft-pack



1060102



Thread 15 x 1,5



Thread 15 x 2,5



NOZZLES
for aluminium
cartridge

Threaded 15 x 1,5
mm



3080005



4020761




3080002



3080009

For the extrusion of product contained
in soft-pack and by using the following
nozzles, use:

THE ADAPTER FOR SOFT-PACK
Cod. 3080225



ADAPTER
for plastic cartridge

Threaded 15 x 2,5 mm



1020054

NOZZLES
for plastic cartridge

Threaded 15 x 2,5 mm



3080003



3080188



3080189



3080190

Nozzles for the extrusion of silicone
and sealants, PU foam in different
lengths.



300 mm

200 mm

100 mm



ADAPTER for PU foam



ADAPTER for cartridges and
soft-pack.
Also available Threaded
12x2,5 mm and 15x1,5 mm



For cartridges and soft-packs

Different openings available in
different positions, depending on user
needs and material viscosity.



For PU foam

PRIVATE LABEL

Private Label is a product PERSONALISATION service that P.M.T. offers its customers. It is possible, on request, to characterise the guns following the style of your brand, inserting your logo, name and description of the article. Many P.M.T. customers use the private label service to personalise their products.



COLOR

In keeping with the style of your brand, we produce individual components in the desired colour, such as the handle or metal components, for which we use special treatments such as anodising and specific paint finishes. We also select the best collaborators to ensure that your product is unique and eye-catching.

LOGO

Private Label is a product PERSONALIZATION service that P.M.T. offers its customers. It is possible, on request, to characterise the guns following the style of your brand, inserting your logo, name and description of the article. Many P.M.T. customers use the private label service to personalise their products.



Customized laser marking upon request



Other available products



Pneumatic Applicators



Manual applicators




Cordless Applicators



Foam guns and Adhesive guns



Coating guns



Spray guns



Fittings



Service guns



REV.10/2023

JAGMAR / tel. +48 62 766 31 01 / www.jag-mar.pl / biuro@jag-mar.pl